

1

**Vulkan.**

## Getting Information Back from the Graphics System

Oregon State University  
Mike Bailey  
mjb@cs.oregonstate.edu

This work is licensed under a [Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License](#)

CC BY NC ND

Oregon State University Computer Graphics

GettingInfoBack.pptx mjb - December 26, 2022

2

### Setting up Query Pools

- There are 3 types of Queries: Occlusion, Pipeline Statistics, and Timestamp
- Vulkan requires you to first setup "Query Pools", one for each specific type
- This indicates that Vulkan thinks that Queries are time-consuming (relatively) to setup, and thus better to set them up in program-setup than in program-runtime

Oregon State University Computer Graphics

mjb - December 26, 2022

3

### Setting up Query Pools

```

VkQueryPoolCreateInfo
vqci.sType = VK_STRUCTURE_TYPE_QUERY_POOL_CREATE_INFO;
vqci.pNext = nullptr;
vqci.flags = 0;
vqci.queryType = << one of: >>
VK_QUERY_TYPE_OCCLUSION
VK_QUERY_TYPE_PIPELINE_STATISTICS
VK_QUERY_TYPE_TIMESTAMP
vqci.queryCount = 1;
vqci.pipelineStatistics = 0; ← bitmask of what stats you are querying for if you
                           are doing a pipeline statistics query
VK_QUERY_PIPELINE_STATISTIC_INPUT_ASSEMBLY_PRIMITIVES_BIT
VK_QUERY_PIPELINE_STATISTIC_INPUT_ASSEMBLY_VERTEXES_BIT
VK_QUERY_PIPELINE_STATISTIC_VERTEX_SHADER_INVOCATIONS_BIT
VK_QUERY_PIPELINE_STATISTIC_GEOMETRY_SHADER_INVOCATIONS_BIT
VK_QUERY_PIPELINE_STATISTIC_GEOMETRY_SHADER_PRIMITIVES_BIT
VK_QUERY_PIPELINE_STATISTIC_CLIPPING_INVOCATIONS_BIT
VK_QUERY_PIPELINE_STATISTIC_CLIPPING_PRIMITIVES_BIT
VK_QUERY_PIPELINE_STATISTIC_FRAGMENT_SHADER_INVOCATIONS_BIT
VK_QUERY_PIPELINE_STATISTIC_TESSELLATION_CONTROL_SHADER_PATCHES_BIT
VK_QUERY_PIPELINE_STATISTIC_TESSELLATION_EVALUATION_SHADER_INVOCATIONS_BIT
VK_QUERY_PIPELINE_STATISTIC_COMPUTE_SHADER_INVOCATIONS_BIT

VkQueryPool      occlusionQueryPool;
result = vkCreateQueryPool( LogicalDevice, IN &vqci, PALLOCATOR, OUT &occlusionQueryPool );

VkQueryPool      statisticsQueryPool;
result = vkCreateQueryPool( LogicalDevice, IN &vqci, PALLOCATOR, OUT &statisticsQueryPool );

VkQueryPool      timestampQueryPool;
result = vkCreateQueryPool( LogicalDevice, IN &vqci, PALLOCATOR, OUT &timestampQueryPool );

```

https://docs.google.com/presentation/d/1JLWVQDfzXyfjwOOGHgkC9GKuIwzrPdLcZBzYRz/edit#slide=id.g16453333333333333333

4

### Resetting, Filling, and Examining a Query Pool

```

vkCmdResetQueryPool( CommandBuffer, occlusionQueryPool, 0, 1 );
vkCmdBeginQuery( CommandBuffer, occlusionQueryPool, 0, VK_QUERY_CONTROL_PRECISE_BIT );
...
vkCmdEndQuery( CommandBuffer, occlusionQueryPool, 0 ); ← query index number

#define DATASIZE 128
uint32_t data[DATASIZE];

result = vkGetQueryPoolResults( LogicalDevice, occlusionQueryPool, 0, 1, DATASIZE*sizeof(uint32_t), data, stride, flags );
// or'ed combinations of:
// VK_QUERY_RESULT_64_BIT
// VK_QUERY_RESULT_WAIT_BIT
// VK_QUERY_RESULT_WITH_AVAILABILITY_BIT
// VK_QUERY_RESULT_PARTIAL_BIT
// stride is # of bytes in between each result

```

Oregon State University Computer Graphics

mjb - December 26, 2022

**Occlusion Query** 5

Occlusion Queries count the number of fragments drawn between the `vkCmdBeginQuery` and the `vkCmdEndQuery` that pass both the Depth and Stencil tests

This is commonly used to see what level-of-detail should be used when drawing a complicated object

**Some hints:**

- Don't draw the whole scene – just draw the object(s) you are interested in
- Don't draw the whole object – just draw a simple bounding volume at least as big as the object(s)
- Don't draw the whole bounding volume – cull away the back faces (two reasons: time and correctness)
- Don't draw the colors – just draw the depths (especially if the fragment shader is time-consuming)

```
uint32_t fragmentCount;
result = vkGetQueryPoolResults( LogicalDevice, occlusionQueryPool, 0, 1,
                               sizeof(uint32_t), &fragmentCount, 0, VK_QUERY_RESULT_WAIT_BIT );
```

 Oregon State University Computer Graphics

mjb - December 26, 2022

**Pipeline Statistics Query** 6

Pipeline Statistics Queries count how many of various things get done between the `vkCmdBeginQuery` and the `vkCmdEndQuery`

```
uint32_t counts[NUM_STATS];
result = vkGetQueryPoolResults( LogicalDevice, statisticsQueryPool, 0, 1,
                               NUM_STATS*sizeof(uint32_t), counts, 0, VK_QUERY_RESULT_WAIT_BIT );
```

```
// vqpc1.pipelineStatistics = or'ed bits of:
// VK_QUERY_PIPELINE_STATISTIC_INPUT_ASSEMBLY_VERTICES_BIT
// VK_QUERY_PIPELINE_STATISTIC_INPUT_ASSEMBLY_PRIMITIVES_BIT
// VK_QUERY_PIPELINE_STATISTIC_VERTEX_SHADER_INVOCATIONS_BIT
// VK_QUERY_PIPELINE_STATISTIC_GEOMETRY_SHADER_INVOCATIONS_BIT
// VK_QUERY_PIPELINE_STATISTIC_FRAGMENT_SHADER_PRIMITIVES_BIT
// VK_QUERY_PIPELINE_STATISTIC_CLIPPING_INVOCATIONS_BIT
// VK_QUERY_PIPELINE_STATISTIC_CLIPPING_PRIMITIVES_BIT
// VK_QUERY_PIPELINE_STATISTIC_FRAGMENT_SHADER_INVOCATIONS_BIT
// VK_QUERY_PIPELINE_STATISTIC_TESSELLATION_CONTROL_SHADER_PATCHES_BIT
// VK_QUERY_PIPELINE_STATISTIC_TESSELLATION_EVALUATION_SHADER_INVOCATIONS_BIT
// VK_QUERY_PIPELINE_STATISTIC_COMPUTE_SHADER_INVOCATIONS_BIT
```

 Oregon State University Computer Graphics

mjb - December 26, 2022

**Timestamp Query** 7

Timestamp Queries count how many nanoseconds of time elapsed between the `vkCmdBeginQuery` and the `vkCmdEndQuery`.

```
uint64_t nanosecondsCount;
result = vkGetQueryPoolResults( LogicalDevice, timestampQueryPool, 0, 1,
                               sizeof(uint64_t), &nanosecondsCount, 0,
                               VK_QUERY_RESULT_64_BIT | VK_QUERY_RESULT_WAIT_BIT );
```

 Oregon State University Computer Graphics

mjb - December 26, 2022

**Timestamp Query** 8

The `vkCmdWriteTimeStamp()` function produces the time between when this function is called and when the first thing reaches the specified pipeline stage.

Even though the stages are "bits", you are supposed to only specify one of them, not "or" multiple ones together

```
vkCmdWriteTimeStamp( CommandBuffer, pipelineStages, timestampQueryPool, 0 );
// VK_PIPELINE_STAGE_TOP_OF_PIPE_BIT
// VK_PIPELINE_STAGE_DRAW_INDIRECT_BIT
// VK_PIPELINE_STAGE_VERTEX_INPUT_BIT
// VK_PIPELINE_STAGE_VERTEX_SHADER_BIT
// VK_PIPELINE_STAGE_TESSELLATION_CONTROL_SHADER_BIT
// VK_PIPELINE_STAGE_TESSELLATION_EVALUATION_SHADER_BIT
// VK_PIPELINE_STAGE_GEOMETRY_SHADER_BIT
// VK_PIPELINE_STAGE_FRAGMENT_SHADER_BIT VK_PIPELINE_STAGE_EARLY_FRAGMENT_TESTS_BIT
// VK_PIPELINE_STAGE_LATE_FRAGMENT_TESTS_BIT VK_PIPELINE_STAGE_COLOR_ATTACHMENT_OUTPUT_BIT
// VK_PIPELINE_STAGE_COMPUTE_SHADER_BIT
// VK_PIPELINE_STAGE_TRANSFER_BIT
// VK_PIPELINE_STAGE_BOTTOM_OF_PIPE_BIT
// VK_PIPELINE_STAGE_HOST_BIT
```

 Oregon State University Computer Graphics



mjb - December 26, 2022