



Push Constants



Oregon State University
Mike Bailey
mjb@cs.oregonstate.edu

CC BY-NC-ND
This work is licensed under a Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License.

Oregon State University Computer Graphics

PushConstants.pptx

mp - December 21, 2022

Push Constants


In an effort to expand flexibility and retain efficiency, Vulkan provides something called **Push Constants**. Like the name implies, these let you "push" constant values out to the shaders. These are typically used for small, frequently-updated data values, such as mat4 transformation matrices. This is a good feature, since Vulkan, at times, makes it cumbersome to send changes to the graphics.

By "small", Vulkan specifies that there will be at least 128 bytes that can be used, although they can be larger. For example, the maximum size is 256 bytes on the NVIDIA 1080ti. (You can query this limit by looking at the **maxPushConstantSize** parameter in the **VkPhysicalDeviceLimits** structure.) Unlike uniform buffers and vertex buffers, these do not live in their own GPU memory. They are actually included inside the Vulkan graphics pipeline data structure.



Oregon State University Computer Graphics

mp - December 21, 2022



Push Constants

On the shader side, if, for example, you are sending a 4x4 matrix, the use of push constants in the shader looks like this:

```
layout( push_constant ) uniform matrix
{
    mat4 modelMatrix;
} Matrix;
```

On the application side, push constants are pushed at the shaders by giving them to the Vulkan Command Buffer:

```
vkCmdPushConstants( CommandBuffer, PipelineLayout, stageFlags, offset, size, pValues );
```

where:
stageFlags are or'ed bits of:
VK_PIPELINE_STAGE_VERTEX_SHADER_BIT
VK_PIPELINE_STAGE_TESSELLATION_CONTROL_SHADER_BIT
VK_PIPELINE_STAGE_TESSELLATION_EVALUATION_SHADER_BIT
VK_PIPELINE_STAGE_GEOMETRY_SHADER_BIT
VK_PIPELINE_STAGE_FRAGMENT_SHADER_BIT

size is in bytes

pValues is a void * pointer to the data, which, in this 4x4 matrix example, would be of type glm::mat4.



Oregon State University Computer Graphics

mp - December 21, 2022

Setting up the Push Constants for the Graphics Pipeline Data Structure

Prior to that, however, the pipeline layout needs to be told about the Push Constants:

```
VkPushConstantRange
vpcr[0].stageFlags =
    VK_PIPELINE_STAGE_VERTEX_SHADER_BIT
    | VK_PIPELINE_STAGE_FRAGMENT_SHADER_BIT;
vpcr[0].offset = 0;
vpcr[0].size = sizeof( glm::mat4 );

VkPipelineLayoutCreateInfo
vpcli.sType = VK_STRUCTURE_TYPE_PIPELINE_LAYOUT_CREATE_INFO;
vpcli.pNext = nullptr;
vpcli.flags = 0;
vpcli.setLayoutCount = 4;
vpcli.pSetLayouts = DescriptorSetLayouts;
vpcli.pushConstantRangeCount = 1;
vpcli.pPushConstantRanges = vpcr;

result = vkCreatePipelineLayout( LogicalDevice, IN &vpcli, PALLOCATOR,
    OUT &GraphicsPipelineLayout );
```


(Note: vpcr[0] and vpcli are circled in red in the original image)

University Computer Graphics

mp - December 21, 2022

A Robotic Example using Push Constants

A robotic animation (i.e., a hierarchical transformation system)



Where each arm is represented by:

```
struct arm
{
    glm::mat4 armMatrix;
    glm::vec3 armColor;
    float armScale; // scale factor in x
};

struct arm Arm1;
struct arm Arm2;
struct arm Arm3;
```



Oregon State University Computer Graphics

mp - December 21, 2022

Forward Kinematics:
You Start with Separate Pieces, all Defined in their Own Local Coordinate System

Oregon State University
Computer Graphics

7

Forward Kinematics:
Hook the Pieces Together, Change Parameters, and Things Move
(All Young Children Understand This)

Oregon State University
Computer Graphics

8

Forward Kinematics:
Given the Lengths and Angles, Where do the Pieces Move To?

Oregon State University
Computer Graphics

9

Positioning Part #1 With Respect to Ground

1. Rotate by θ_1
2. Translate by $T_{1/G}$

Code it

$$[M_{1/G}] = [T_{1/G}] * [R_{\theta_1}]$$

Say it

Oregon State University
Computer Graphics

10

Why Do We Say it Right-to-Left?

Write it

$$[M_{1/G}] = [T_{1/G}] * [R_{\theta_1}]$$

Say it

We adopt the convention that the coordinates are multiplied on the right side of the matrix:

$$\begin{Bmatrix} x' \\ y' \\ z' \\ 1 \end{Bmatrix} = \begin{bmatrix} A & B & C & D \\ E & F & G & H \\ I & J & K & L \\ 0 & 0 & 0 & 1 \end{bmatrix} \begin{Bmatrix} x \\ y \\ z \\ 1 \end{Bmatrix}$$

$$\begin{Bmatrix} x' \\ y' \\ z' \\ 1 \end{Bmatrix} = [M_{1/G}] \begin{Bmatrix} x \\ y \\ z \\ 1 \end{Bmatrix} = [T_{1/G}] * [R_{\theta_1}] * \begin{Bmatrix} x \\ y \\ z \\ 1 \end{Bmatrix}$$

So the right-most transformation in the sequence multiplies the (x,y,z,1) first and the left-most transformation multiplies it last

Oregon State University
Computer Graphics

11

Positioning Part #2 With Respect to Ground

1. Rotate by θ_2
2. Translate the length of part 1
3. Rotate by θ_1
4. Translate by $T_{1/G}$

Code it

$$[M_{2/G}] = [T_{1/G}] * [R_{\theta_1}] * [T_{2/1}] * [R_{\theta_2}]$$

$$[M_{2/G}] = [M_{1/G}] * [M_{2/1}]$$

Say it

Oregon State University
Computer Graphics

12

Positioning Part #3 With Respect to Ground

1. Rotate by Θ_3
2. Translate the length of part 2
3. Rotate by Θ_2
4. Translate the length of part 1
5. Rotate by Θ_1
6. Translate by $T_{1/G}$

Code it

$$[M_{3/G}] = [T_{1/G}] * [R_{\theta_1}] * [T_{2/1}] * [R_{\theta_2}] * [T_{3/2}] * [R_{\theta_3}]$$

$$[M_{3/G}] = [M_{1/G}] * [M_{2/1}] * [M_{3/2}]$$

Say it



#B - December 21, 2022

In the Reset Function

```

struct arm Arm1;
struct arm Arm2;
struct arm Arm3;

...

Arm1.armMatrix = glm::mat4( 1. );
Arm1.armColor = glm::vec3( 0.f, 1.f, 0.f ); // green
Arm1.armScale = 6.f;

Arm2.armMatrix = glm::mat4( 1. );
Arm2.armColor = glm::vec3( 1.f, 0.f, 0.f ); // red
Arm2.armScale = 4.f;

Arm3.armMatrix = glm::mat4( 1. );
Arm3.armColor = glm::vec3( 0.f, 0.f, 1.f ); // blue
Arm3.armScale = 2.f;
    
```

The constructor `glm::mat4(1.)` produces an identity matrix. The actual transformation matrices will be set in `UpdateScene()`.



#B - December 21, 2022

Set the Push Constant for the Graphics Pipeline Data Structure

```

VkPushConstantRange vpcr[0].stageFlags =
    VK_PIPELINE_STAGE_VERTEX_SHADER_BIT
    | VK_PIPELINE_STAGE_FRAGMENT_SHADER_BIT;

vpcr[0].offset = 0;
vpcr[0].size = sizeof( struct arm );

VkPipelineLayoutCreateInfo vplci;
vplci.sType = VK_STRUCTURE_TYPE_PIPELINE_LAYOUT_CREATE_INFO;
vplci.pNext = nullptr;
vplci.flags = 0;
vplci.setLayoutCount = 5;
vplci.pSetLayouts = DescriptorSetLayouts;
vplci.pushConstantRangeCount = 1;
vplci.pPushConstantRanges = vpcr;

result = vkCreatePipelineLayout( LogicalDevice, IN &vplci, PALLOCATOR,
    OUT &GraphicsPipelineLayout );
    
```



#B - December 21, 2022

In the UpdateScene() Function

```

float rot1 = (float)(2.*M_PI*Time); // rotation for arm1, in radians
float rot2 = 2.f * rot1;           // rotation for arm2, in radians
float rot3 = 2.f * rot2;           // rotation for arm3, in radians

glm::vec3 zaxis = glm::vec3(0., 0., 1.);

glm::mat4 m1g = glm::mat4( 1. ); // identity
m1g = glm::translate(m1g, glm::vec3(0., 0., 0.));
m1g = glm::rotate(m1g, rot1, zaxis); // [T]*[R]

glm::mat4 m21 = glm::mat4( 1. ); // identity
m21 = glm::translate(m21, glm::vec3(2.*Arm1.armScale, 0., 0.));
m21 = glm::rotate(m21, rot2, zaxis); // [T]*[R]
m21 = glm::translate(m21, glm::vec3(0., 0., 2.)); // z-offset from previous arm

glm::mat4 m32 = glm::mat4( 1. ); // identity
m32 = glm::translate(m32, glm::vec3(2.*Arm2.armScale, 0., 0.));
m32 = glm::rotate(m32, rot3, zaxis); // [T]*[R]
m32 = glm::translate(m32, glm::vec3(0., 0., 2.)); // z-offset from previous arm

Arm1.armMatrix = m1g; // m1g
Arm2.armMatrix = m1g * m21; // m2g
Arm3.armMatrix = m1g * m21 * m32; // m3g
    
```



#B - December 21, 2022

In the RenderScene() Function

```

VkBuffer buffers[1] = { MyVertexDataBuffer.buffer };


vkCmdBindVertexBuffers( CommandBuffers[nextImageIndex], 0, 1, buffers, offsets );

vkCmdPushConstants( CommandBuffers[nextImageIndex], GraphicsPipelineLayout,
    VK_SHADER_STAGE_ALL, 0, sizeof( struct arm ), (void *) &Arm1 );
vkCmdDraw( CommandBuffers[nextImageIndex], vertexCount, instanceCount, firstVertex, firstInstance );

vkCmdPushConstants( CommandBuffers[nextImageIndex], GraphicsPipelineLayout,
    VK_SHADER_STAGE_ALL, 0, sizeof( struct arm ), (void *) &Arm2 );
vkCmdDraw( CommandBuffers[nextImageIndex], vertexCount, instanceCount, firstVertex, firstInstance );

vkCmdPushConstants( CommandBuffers[nextImageIndex], GraphicsPipelineLayout,
    VK_SHADER_STAGE_ALL, 0, sizeof( struct arm ), (void *) &Arm3 );
vkCmdDraw( CommandBuffers[nextImageIndex], vertexCount, instanceCount, firstVertex, firstInstance );
    
```

The strategy is to draw each link using the same vertex buffer, but modified with a unique color, length, and matrix transformation




#B - December 21, 2022

In the Vertex Shader

```

layout( push_constant ) uniform arm
{
    mat4 armMatrix;
    vec3 armColor;
    float armScale; // scale factor in x
} RobotArm;

layout( location = 0 ) in vec3 aVertex;

...

vec3 bVertex = aVertex; // arm coordinate system is [-1., 1.] in X
bVertex.x += 1.; // now is [0., 2]
bVertex.x -= 2.; // now is [0., 1]
bVertex.x *= (RobotArm.armScale); // now is [0., RobotArm.armScale]
bVertex = vec3( RobotArm.armMatrix * vec4( bVertex, 1. ) );

...

gl_Position = PVMM * vec4( bVertex, 1. ); // Projection * Viewing * Modeling matrices
    
```



#B - December 21, 2022

