



Index

Symbols

!GND node 3-31
\$ comment delimiter 3-28
\$installdir installation directory 3-56
* comment delimiter 3-28

A

A model parameter 12-34
A2D
 function 5-46
 model parameter 5-46
 See also analog to digital, mixed mode
.a2d file 4-3, 4-4, 5-46
A2D function 23-4
ABS element parameter 23-20, 23-26, 23-31, 23-35
abs(x) function 10-6
ABSH option 6-23, 7-11, 9-7
ABSI option 6-22, 6-23
 KCLTEST setting 6-17
ABSMOS option 6-22, 6-24
 KCLTEST setting 6-17
absolute
 power function 10-6

 value function 10-6
absolute value parameter 23-20, 23-26, 23-31, 23-35
ABSTOL option 6-14
ABSV option 6-22, 7-11, 7-14
ABSVAR option 7-11, 7-13, 7-19
ABSVDC option 6-24
AC
 magnitude calculation 9-7
 optimization 9-4
 output calculation 9-7
 output calculation method 9-7
 phase calculation 9-7
 resistance 9-3
 effective value 12-6
 element parameters 12-3
 transmission lines 22-22
 small-signal analysis parameter 5-3
AC resistance parameter 23-91
.AC statement
 external data 3-38
.ac# file 4-2, 4-4
accessing customer support vi
ACCT option 3-47, 4-6
accuracy
 and simulation time 6-22

- tolerance 6-21
- ACCURATE option 7-11, 7-19
- ACM
 - area calculation method 15-3
 - model parameter 7-20, 15-3
 - parameter 16-7, 16-29
- acos(x) function 10-6
- ACOUT option 9-7, 9-9–9-10
- admittance
 - AC input 9-13
 - AC output 9-13
 - Y parameters 9-8
- AF model parameter 9-17
- AGAUSS
 - keyword 10-41
 - Monte Carlo function 10-16
- ALFA .FFT parameter 26-7
- algebraic
 - models 7-20
- algebraic equations, example 20-12
- algorithms
 - Damped Pseudo Transient algorithm 6-34
 - DVDT 7-9, 7-11, 7-25
 - GEAR 7-9, 7-21
 - integration 7-21
 - iteration count 7-25
 - local truncation error 7-10, 7-14, 7-25
 - timestep 7-13
 - Muller 25-3
 - pivoting 6-18
 - timestep control 7-9, 7-25, 7-27
 - transient analysis timestep 7-9
 - TRAP 7-9
 - trapezoidal integration 7-10, 7-21
- ALL keyword 6-8, 6-12
- ALPHA model parameter 12-34
- .ALTER blocks
 - statements in 3-34
 - .LIB and .DEL LIB in 10-30
 - .OPTION statements 10-31
 - .PARAM statements in 10-30
 - and .INCLUDE statements 10-31
 - changing subcircuits in 10-30
 - element parameters 10-31
 - input listing 10-31
 - model parameters 10-31
 - titles 10-31
 - variables in 10-30
- .ALTER statement 3-34, 10-30
 - multiple .ALTER's 10-31
 - with .DEL LIB 10-31
- AM source function 5-18
 - carrier frequency 5-18
 - delay time 5-18
 - modulation frequency 5-18
 - offset constant 5-18
 - signal amplitude 5-18
- AMD models 16-4, 16-5
- AMP model parameter 23-83
- amplifiers
 - pole/zero analysis 25-11, 25-13
- amplitude modulation source function 5-18
- amplitude modulator, behavioral 23-79
- Analog Artist interface 3-47
 - output data format 3-54

- See also Artist
- analog behavioral modeling 23-4
- analog to digital conversion 23-39
- analog to digital output 5-49
- analysis
 - accuracy 6-21–6-22
 - data driven 10-2, 10-3, 20-9
 - distortion 9-14
 - initialization 6-3
 - Monte Carlo 10-3, 10-39–10-59
 - network 9-19
 - optimization 11-5
 - statistical 10-33–10-59
 - Taguchi 10-2
 - transfer function (.TF) 23-63
 - worst case 10-2, 10-33–10-59
 - yield 10-2
- arccos(x) function 10-6
- arcsin(x) function 10-6
- arctan(x) function 10-6
- area
 - JFET and MESFET
 - equations 15-26–15-28
 - units 15-26, 15-28
 - calculation method
 - see ACM
- arithmetic operators 10-6
- ARTIST option 3-47, 3-54
- ASCII output data 3-48, 3-51, 3-53, 3-54
- ASIC
 - device libraries 3-57
 - vendor libraries 3-57
- asin(x) function 10-6
- ASPEC
 - compatibility 3-48
 - option 3-48
 - ASPEC compatibility 16-2, 16-40
 - ASPEC-AMI model 16-4
 - asterisk comment delimiter 3-28
 - asymptotic waveform evaluation 27-2
 - transfer function 27-33
 - AT keyword 4-22
 - AT1 model parameter 22-38
 - atan(x) function 10-6
 - ATEM characterization system 3-56
 - ATLEN model parameter 22-38
- AUNIF
 - keyword 10-41
 - Monte Carlo function 10-16
- AURORA user's group vi
- autoconvergence 6-28
 - algorithm 6-26
 - disabling 6-26
- automatic model selection
 - failure 19-3
 - multisweep or .TEMP effect 19-4
 - See also model selection
- AUTOSTOP option 7-14, 7-18, 20-10, 23-91
- AV model parameter 23-84
- AV1K model parameter 23-84
- Avant! web site vi
- AVD model parameter 23-84
- average deviation 10-3
- average value, measuring 4-23
- AVG keyword 4-24
- AWE

see asymptotic waveform evaluation

B

B# node name in CSOS 3-33

backslash continuation character 3-18,
10-5

double 10-5

in input files 3-18

BADCHR option 3-18

bandwidth 22-109

BART FFT analysis keyword 26-7

Bartlett FFT analysis window 26-3, 26-4

base

charge equations, BJT's 14-36

resistance equations, BJT's 14-37

basic model parameters

BJT's 14-19

JFET TOM model 15-52

MOSFET's

Level 1 17-2

Level 13 17-110

Level 2 17-8

Level 28 17-156

Level 3 17-20

Level 38 17-169

Level 40 17-211

Level 47 17-222

Level 49 17-242

Level 5 17-35

Level 50 17-258

Level 8 17-91

Levels 6, 7 17-53

behavioral

741 op-amp 23-93

amplitude modulator 23-79

BJT modeling 23-109

BJT phase detector model 23-114

BJT VCO model 23-112

CMOS inverter 23-63

comparator 23-96

current source 23-19

data sampler 23-81

differentiator 23-72

d-latch 23-50

elements, analog 23-70

flip-flop 23-54

gates 23-48

integrator 23-70

LC oscillator 23-100

look-up tables 23-57

n-channel MOSFET 23-51

p-channel MOSFET 23-51

phase detector model 23-105

phased locked loop 23-105

ring oscillator 23-67

silicon controlled rectifier 23-76

transformer 23-74

triode vacuum tube 23-77

tunnel diode 23-75

VCO model 23-98

voltage source 23-30

VVCAP model 23-102

behavioral

n-channel MOSFET 23-59

BETA keyword 9-18

BiCMOS devices 14-2

bin description parameters, MOSFET

Level 49 17-248

binary output data 3-53, 3-54

- binary search 28-6–28-12
- bisection
 - error tolerance 28-8
 - function 28-1
 - function syntax 28-7
 - method 28-5
 - pass-fail method 28-5
- bisection data, printing 3-52
- BISECTION model parameter 28-7
- BJT's
 - base
 - area multiplying factor 14-5
 - charge equations 14-36
 - push-out effects 14-47
 - width modulation model parameters 14-22
 - base-collector
 - depletion capacitance equations 14-41
 - diffusion capacitance equations 14-40
 - base-emitter
 - depletion capacitance equations 14-39
 - diffusion capacitance equations 14-38
 - beta temperature equations 14-53–14-57
 - capacitance temperature equations 14-57
 - collector area multiplying factor 14-5
 - conductance 14-7, 14-8
 - control options 14-3
 - current equations 14-34
 - current flow 4-13
 - DC models
 - equations 14-34
 - parameters 14-19
 - elements
 - names 14-4
 - parameters 14-4
 - emitter area multiplying factor 14-5
 - energy gap temperature equations 14-53
 - equivalent circuits 14-7
 - excess phase equation 14-44
 - high current Beta degradation
 - parameters 14-22
 - initial
 - conditions 14-5
 - internal voltages 14-5
 - junction capacitance
 - equations 14-42
 - model parameters 14-23
 - Level 2
 - model parameters 14-26
 - temperature equations 14-60
 - low current Beta degradation
 - parameters 14-21
 - models
 - constants (table) 14-15
 - names 14-16
 - parameters 14-18
 - statements 14-16
 - variables (table) 14-13
 - multiply parameter 14-5
 - noise
 - equations 14-45
 - model parameters 14-26
 - summary printout 14-46

- npn identifier 14-16
 - parasitics
 - capacitance model parameters 14-25
 - resistance model parameters 14-23
 - resistor temperature equations 14-60
 - pnp identifier 14-16
 - power dissipation 4-17
 - saturation temperature equations 14-53–14-57
 - scaling 14-5
 - substrate
 - capacitance equations 14-43
 - current equation 14-36
 - temperature
 - differential 14-5
 - effect parameters 14-27
 - parameters 14-27
 - transit time model parameters 14-25
 - variable base resistance equations 14-37
- BKPSIZ option 7-15
- BLACK FFT analysis keyword 26-7
- Blackman FFT analysis window 26-3
- Blackman-Harris FFT analysis window 26-3
- bond wire example 20
- branch current
 - error 6-14, 6-23
 - output 4-11
- branch matrix 22-35
- breakpoint table
 - reducing size 7-28
 - size 7-15
- BRIEF**
 - keyword 6-8
 - option 3-45, 3-48, 3-50, 3-51, 3-52
- Broyden update data, printing 3-52
- BSIM Level 13 model 3-66, 16-4
- BSIM2 Level 39 model 3-66, 16-5
- BSIM3 Level 47 model 16-5
- bulk
 - charge effect 16-2
 - semiconductor devices 15-2
 - transconductance, MOSFET's 16-19
- bus notation 5-63
- Butterworth filter pole/zero analysis 25-9
- BV diode model parameter 13-3
- BW model parameter 23-86
- BYPASS option 7-8, 16-11
- BYTOL option 7-11

C

C2 model parameter 23-85

Cadence

Analog Artist

see Artist, Analog Artist

Opus 3-48

WSF format 3-48

capacitance

CAPOP model selector 16-6

charge tolerance, setting 7-11

control options 16-71

CSHUNT node-to-ground 7-8

distribution for wire RC model 12-

- 10
- effective 12-6, 12-18, 12-20
- element
 - equation 12-17
 - parameter 12-16
- equations, BJT's 14-38, 14-39, 14-40, 14-42
- function of voltage 12-18, 12-21
- input-output ratio 12-10
- JFET and MESFET 15-5, 15-29–15-35
 - CAPOP=2 parameters 15-33
 - equations 15-6
 - gate to drain 15-5
 - source to gate 15-5
- manufacturing variations 10-48
- model
 - parameters 12-5, 12-19
 - selection 16-59
- MOSFET's
 - diodes 16-49
 - equations 16-77–16-103
 - gate capacitance models 16-59
 - Meyer model 16-59
 - models 16-59
- node to bulk 12-6
- overlap 16-76
- parameters
 - BJT's 14-23
 - MOSFET's
 - Level 38 17-173
 - Level 5 17-37
- parasitic 12-10
- pins 20-6
- plotting 16-69
- scale factor, setting 8-11
- table of values 6-14
- temperature equations 12-21
 - BJT's 14-57
- capacitance, voltage variable 23-102
- capacitance-voltage plots, generating 6-15
- capacitors
 - conductance requirement 6-33
 - current flow 4-12
 - DC sweep evaluation 14-38
 - elements 12-16
 - names 12-16, 12-21
 - parameters 12-3
 - initial voltage 12-18, 12-22
 - length parameter 12-17
 - models 3-65
 - (list) 16-6
 - parameters 12-5
 - node names 12-16, 12-21
 - nonlinear equations 12-3
 - polynomial
 - coefficients 12-21
 - elements 12-21
 - temperature
 - coefficients 12-16
 - equations 12-9
 - width parameter 12-17
- capacitors, switched 27-45
- CAPL model parameter 22-38
- CAPOP model parameter 7-20, 15-3, 16-6, 16-59
- CAPTAB option 6-14
- CASMOS
 - GEC model 16-4
 - GTE model 16-4

- Rutherford model 16-4
- CCCS element parameter 23-27
- CCVS element parameter 23-36
- CDS option 3-54
- cell characterization 10-2
- CENDIF optimization parameter 11-7
- CEXT model parameter 22-17, 22-26, 22-28, 22-30
- channel length modulation, MOSFET's
 - equations
 - Level 2 17-16
 - Level 3 17-27
 - Level 38 17-179
 - Level 5 17-50
 - Level 6 17-82
 - Level 8 17-100
 - parameters
 - Level 6 17-82
 - Level 8 17-95
- characteristic impedance 22-103
- characterization of models 8-3
- charge conservation 16-95
- charge tolerance, setting 7-11
- CHGONLY model parameter 5-50, 23-43
- CHGTOL option 7-11, 7-26
- CHI model parameter 23-41
- circuits
 - subcircuit numbers 3-32
 - temperature 10-62
 - See also subcircuits
- CLEN model parameter 22-38
- CLO model parameter 23-40
- CLOAD model parameter 5-50, 23-43
- clock
 - frequency 22-109
 - skew 20-6
- CLOSE optimization parameter 11-7
- CMOS differential amplifier
 - pole/zero analysis 25-11
- CMRR
 - model parameter 23-85
 - specification 23-5
- CMULT model parameter 22-17, 22-26, 22-28, 22-30
- CO option 3-48, 4-52
- coax
 - see transmission lines
- coefficients
 - Laplace 27-20
 - transfer function 27-18
- column laminated data 3-42
- commands
 - hspice 3-10–3-14
 - arguments 3-11
 - limit descriptors 4-9
 - metaio 24-8
- comment line (digital vector files) 5-56
- comments 3-28
 - \$ delimiter 3-28
 - * delimiter 3-28
- common emitter gain 28
- Common Simulation Data Format 3-49
- COMP model parameter 23-83, 23-85
- comparators
 - behavioral models 23-82

- model 23-96
- complex poles and zeros 27-27
- compression of input files 3-17
- concatenated data files 3-41
- conductance
 - BJT's 14-7, 14-8
 - current source, initialization 6-26
 - diodes 13-12
 - for capacitors 6-33
 - JFET and MESFET 15-5, 15-12
 - minimum, setting 7-15
 - models 6-15
 - MOSFET 16-18, 16-56
 - MOSFET nodes 6-26
 - negative, logging 3-49
 - node-to-ground 6-16, 7-9
 - pn junction 6-40
 - scale, setting 8-11
 - sweeping 6-16
- continuation character, parameter strings 10-5
- continuation of line (digital vector file) 5-57
- control characters in input 3-18
- control options
 - ABSH 6-23, 7-11, 9-7
 - ABSI 6-23
 - ABSMOS 6-24
 - ABSTOL 6-14
 - ABSV 7-11, 7-14
 - ABSVAR 7-11, 7-13
 - ABSVDC 6-24
 - ACCT 3-47, 4-6
 - accuracy, defaults 7-27
 - ACCURATE 7-11
 - ACOUT 9-7
 - algorithm selection 6-14
 - ARTIST 3-47, 3-54
 - ASPEC 3-48
 - AUTOSTOP 7-14
 - BADCHR 3-18
 - BJT's 14-3
 - BKPSIZ 7-15
 - BRIEF 3-45, 3-48, 3-50, 3-51, 3-52
 - BYPASS 7-8
 - BYTOL 7-11
 - capacitance 16-71
 - CAPTAB 6-14
 - CDS 3-54
 - CHGTOL 7-11
 - CO 3-48, 4-52
 - CONVERGE 6-24, 6-28
 - convergence 6-23
 - CPTIME 3-49
 - CSCAL 8-11
 - CSDF 3-49
 - CSHDC 6-14
 - CSHUNT 7-8
 - DC convergence 6-14
 - DCCAP 6-15
 - DCFOR 6-15
 - DCHOLD 6-15
 - DCON 6-25, 6-28
 - DCSTEP 6-15
 - DCTRAN 6-26
 - defaults 3-45, 3-68
 - DELMAX 7-15, 7-16, 7-19
 - DIAGNOSTIC 3-49
 - DV 6-16, 6-28
 - DVDT 7-9, 7-25
 - DVTD 7-9

DVTR 7-15
EPSMIN 3-49
EXPMAX 3-49
FAST 7-12
FMAX 7-12
FS 7-15, 7-17
FSCAL 8-11, 8-12
FT 7-15, 7-17
GMAX 6-26
GMIN 7-15
 stepping 6-26
GMINDC 6-26, 6-28
GRAMP 6-16, 6-26, 6-28
GSCAL 8-11
GSHUNT 6-16, 7-9
H9007 3-49
ICSWEEP 6-17
IMAX 7-16
IMIN 7-16
INGOLD 3-49, 3-51
INTERP 7-9
ITL1 6-17
ITL3 7-16
ITL4 7-16
ITL5 7-16
ITLPZ 8-11
ITRPRT 7-9
JFET's 15-5
KCLTEST 6-17
LENNAM 3-50
LIMPTS 3-50
LIMTIM 3-50
LIST 3-50, 3-55
LSCAL 8-11
LVLTIM 7-9, 7-10, 7-13, 7-14
MAXAMP 6-17, 7-12, 9-7
MAXORD 7-10
MBYPASS 7-12
MEASDGT 3-50
MEASOUT 3-51
MENTOR 3-51
MESFET's 15-5
METHOD 7-10
MOSFET's 16-9
MU 7-12, 7-14
NEWTOL 6-18
NODE 3-51
NOELCK 3-52
NOMOD 3-52
NOPAGE 3-52
NOPIV 6-18
NOTOP 3-52
NOWARN 3-52
NUMDGT 3-52
NXX 3-52
OFF 6-18
OPTLST 3-52
OPTS 3-52
PARHIER 3-53
PATHNUM 3-53
PIVOT 6-18
PIVREF 6-20
PIVREL 6-20
PIVTOL 6-19, 6-20
POST 3-4, 3-53, 4-6
 printing values of 3-52
PROBE 3-54
PZABS 8-12
PZTOL 8-12
RELH 6-27, 7-13, 9-7
RELI 6-27, 7-13
RELMOS 6-24, 6-27

- RELQ 7-13
- RELTOL 7-11, 7-13
- RELV 6-27
- RELVAR 7-13
- RELVDC 6-27
- RESMIN 6-20
- RITOL 8-12
- RMAX 7-16
- RMIN 7-16
- SDA 3-48, 3-54
- SEARCH 3-54, 3-59
 - setting 3-45
- SLOPTOL 7-13
- SPARSE 6-20
- SPICE 3-54
 - table 3-46
- TIMERES 7-14
- TRTOL 7-14
- TSTEP 7-16
- UNWRAP 9-8
- VERIFY 3-55
- VFLOOR 7-17
- VNTOL 7-14
- WARNLIMIT 3-55
- XnR,XnI 8-12
- ZUKEN 3-55
- controlled sources 5-20, 23-4, 23-13
 - element statement 5-20, 23-14
- CONVERGE option 6-24, 6-28, 6-34
- convergence
 - control options 6-23
 - current 6-23, 6-26, 6-27, 7-11, 7-12, 7-13, 9-7
 - ensuring 6-15
 - for optimization 11-9
 - increasing iterations 6-15
 - MOSFET diodes 16-29
 - problems, diodes 13-4
 - steady state 6-16
- convergence problems 6-35
 - .NODESET statement 6-7
 - analyzing 6-35
 - autoconverge process 6-28
 - caused by BYPASS 7-8
 - causes 6-37
 - changing integration algorithm 7-10
 - CONVERGE option 6-34
 - solutions 6-24
 - DCON setting 6-25, 6-30
 - decreasing the timestep 7-15
 - diagnosing 6-35–6-40
 - diagnostic tables 6-35
 - floating point overflow 6-34
 - GMINDC ramping 6-30
 - internal timestep too small 7-9
 - nonconvergent node listing 6-26
 - op-amp models 23-83
 - operating point Debug mode 6-8
 - pole/zero analysis 25-3
 - reducing 6-31
 - setting DCON 6-26
- core model parameters 12-35
 - A 12-34
 - ALPHA 12-34
 - MS 12-34
- CORKD model parameter 22-17, 22-27
- cos(x) function 10-6
- cosh(x) function 10-6
- coupled line noise simulation example
 - 20-26

- CPTIME option 3-49
 - CPU time
 - limiting 3-50
 - reducing 3-52
 - setting maximum 3-49
 - critical frequency 27-5
 - CROSS keyword 4-22
 - crosstalk 22-108
 - CSCAL option 8-11, 25-4
 - CSDF option 3-49
 - CSHDC option 6-14
 - CSHUNT option 7-8
 - CUR element parameter 23-21
 - current
 - ABSMOS floor value for convergence 6-27
 - branch 4-12-4-14
 - branch current error 6-14, 6-23
 - convention
 - BJT's 14-6
 - JFET's 15-9
 - MOSFET's 16-17
 - diodes 13-11
 - epitaxial 14-50
 - in HSPICE elements 4-12-4-14
 - KCL test 6-17
 - operating point table 6-8
 - current controlled
 - current source 5-33, 23-26
 - current sources 23-13, 23-14
 - sources 5-20
 - voltage source 5-42, 23-35
 - voltage sources 23-13
 - CURRENT keyword 6-8
 - Curtice model 15-3, 15-25, 15-26
 - customer support vi
 - CUT optimization parameter 11-8
 - C-V plot 15
 - C-V plots, generating 6-15
 - Cxxx capacitor element statement 12-16, 12-21
 - Cypress model 16-4
- D**
- D12 model parameter 22-30
 - D2A
 - function 5-46
 - model parameter 5-46
 - See also analog to digital, mixed mode
 - .d2a file 5-46
 - D2A function 23-4
 - D2A
 - See also digital to analog, mixed mode
 - Dallas Semiconductor model 16-4
 - Damped Pseudo Transient algorithm 6-34
 - data
 - encryption 29-1
 - sampler, behavioral 23-81
 - sheet parameters 20-1
 - data driven analysis 10-2, 10-3, 20-9
 - data driven PWL source function
 - PV parameter 5-16, 7-38
 - TIME parameter 5-16, 7-38
 - data files, disabling printout 3-48

- DATA keyword 3-37, 7-5, 8-4, 9-4
- .DATA statement 20-9, 20-10
 - data driven analysis 3-37
 - datanames 3-38
 - for sweep data 3-37
 - inline data 3-38
- .DATA sweep 3-41
- datanames 3-38
- db(x) function 10-7
- DC
 - analysis 8-8–8-10
 - capacitor conductances 6-33
 - decade variation 8-5
 - initialization 6-15
 - iteration limit 6-17
 - linear variation 8-5
 - list of points 8-5
 - octave variation 8-5
 - convergence control options 6-14
 - equations
 - BJT's 14-34
 - JFET and MESFET 15-35–15-38
 - operating point
 - analysis 6-8
 - bypassing 7-3
 - See also operating point
 - optimization 8-4
 - parameters, JFET
 - Level 1 15-23
 - Level 2 15-23
 - Level 3 15-25
 - sensitivity analysis 8-9
 - small-signal analysis 8-9
 - sweep 8-3
 - transfer function 8-9
- .DC statement
 - external data with .DATA 3-38
- DCAP
 - equation selector 14-3
 - option 13-4
 - JFET and MESFET
 - capacitance 15-5
 - models 15-6
 - overriding in BJT models 14-3
- DCCAP option 6-15, 13-4, 14-38, 15
 - JFET and MESFET capacitance 15-5
- DCFOR option 6-15
- DCHOLD option 6-15
- DCON option 6-25, 6-28
- DCSTEP option 6-15, 6-33
- DCTRAN option 6-26
- DDL
 - See also Discrete Device Library
- DDLPATH environment variable 3-57, 28
- DEBUG keyword 6-8
- DEC keyword 7-6, 8-5, 9-5
- decibel function 10-7
- decoupling methods 20-6
- DEF model parameter 23-85
- DEFAULT_INCLUDE variable 3-16
- DEFW option 10-22
- .DEL LIB statement 3-21
 - in .ALTER blocks 10-30
 - with .ALTER 10-31
 - with .LIB 10-31

- with multiple .ALTER statements
 - 10-31
- DELAY
 - element parameter 23-21, 23-27, 23-31, 23-36
 - model parameter 22-38
- delays
 - causes 20-3
 - derating curve 20-4
 - element example 5-31
 - Elmore 27-30
 - group 4-14, 9-8
 - measuring 4-20
 - plotting 20-5
 - problems and solutions 20-3
 - simulation example 20-10
 - transmission lines 22-38
 - types 20-6
- DELEN model parameter 22-38
- DELF element parameter 27-6, 27-9
- DELMAX option 7-15, 7-16, 7-19, 7-27, 7-30
 - ideal delay elements 7-19
 - oscillator circuits 7-19
- DELPHS 23-86
- DELTA element parameter 23-17, 23-21, 23-27, 23-31, 23-36, 23-75, 27-9
- DELTA internal timestep 7-15
 - See also timestep
- DELVTO model parameter 10-34
- demo files
 - .ALTER statement 34
 - 2n2222 BJT transistor
 - characterization 40
 - 2n3330 JFET transistor
 - characterization 40
 - A/D flash converter 38
 - A2D 37
 - AC
 - analysis 34
 - resonance analysis 43
 - acl gate 35
 - adders
 - 72-transistor two-bit 36
 - BJT NAND gate two-bit 35
 - BJT two-bit 34
 - digital to analog 37
 - MOS two-bit 35
 - NAND gate four-bit binary 34
 - air core transformer 43
 - algebraic
 - parameters 34
 - transmission lines 47
 - AM source 46
 - amplifier 37
 - amplitude modulator 35
 - analog 36
 - analog to digital 38
 - AND gate 35
 - automatic model selection program
 - 44
 - behavioral models 36
 - diode 35
 - D-latch 35
 - filter 34
 - NAND gate 35
 - ring oscillator 36
 - triode 36
 - voltage to frequency converter

- 34
- bipolar
 - analog circuit 36
 - Schmidt trigger 34
 - sense amplifier 34
- bisection
 - pass-fail 36
 - search 36, 37
- BJT
 - beta plot 37
 - differential amplifier 34, 37
 - ft plot 37
 - gm, gpi plots 37
 - photocurrent 46
- BSIM3 model, Level=47 43
- capacitances
 - MOS models
 - Level=13 43
 - Level=2 43
 - Level=6 44
- cell characterization 34, 35
- charge conservation
 - MOS models
 - Level=3 44
 - Level=6 44
- CMOS
 - differential amplifier 34
 - I/O driver ground bounce 34, 46
 - input buffer 37
 - inverter macro 36
 - output buffer 37
- coax transmission line 47
- crystal oscillator 34
- current controlled
 - current source 36
 - voltage source 36
- D2A 37
- DC analysis, MOS model Level=34 44
- delay 34, 37
 - versus fanout 37
- differential amplifier 34
- differentiator 35
- diffusion effects 35
- diode photocurrent 45
- D-latch 35
- E element 35
- edge triggered flip-flop 35
- exponential source 46
- FFT
 - AM source 41
 - Bartlett window 41
 - Blackman window 41
 - Blackman-Harris window 42
 - data-driven transient analysis 42
 - exponential source 41
 - Gaussian window 42
 - Hamming window 42
 - Hanning window 42
 - harmonic distortion 41
 - high frequency detection 41
 - intermodulation distortion 42
 - Kaiser window 42
 - modulated pulse source 42
 - Monte Carlo, Gaussian distribution 42
 - piecewise linear source 42
 - product of waveforms 42
 - pulse source 42
 - rectangular window 42
 - single-frequency FM source 42
 - sinusoidal source 42

- small-signal distortion 41
- switched capacitor 42
- transient 42
 - sweep 42
- window tests 42
- filter matching 38
- filters
 - behavioral 34
 - fifth-order
 - elliptical switched capacitor 36
 - low-pass 43
 - fourth-order Butterworth 43
 - Kerwin's circuit 43
 - LCR bandpass 43
 - matching lossy to ideal 38
 - ninth-order low-pass 35, 43
 - switched capacitor low-pass 35
- FR-4 microstrip transmission line 43, 46
- G element 34, 35
- GaAsFET amplifier 34
- gamma model Level=6 44
- ground bounce 34, 46
- group time delay 34
- impact ionization plot 44
- installation test 36
- integrator 35
- inverter 35, 36
 - characterization 34, 37
 - sweep 37
- IRF340 NMOS transistor
 - characterization 40
- I-V
 - and C-V plots, Level=3 44
 - plots
 - MOSFET model Level=13 44
 - SOSFET model Level=27 44
- JFET photocurrent 46
- junction tunnel diode 37
- LCR circuit 37
- lumped
 - MOS model 34
 - transmission lines 43, 47
- magnetic core transformer 43
- microstrip transmission lines 43, 47
 - coupled 47
 - optimization 47
 - series 47
- Monte Carlo
 - analysis 35
 - DC 35
 - Gaussian distribution 35
 - limit function 35
 - uniform distribution 35
- MOS
 - amplifier 37
 - simulation 36
- MOSFET's
 - sigma sweep 37
 - sweep 34
- NAND gate 35, 36
- NMOS E-mode model, Level=8 46
- noise analysis 34
- op-amp 34, 35
 - characterization 38–40
 - voltage follower 35, 46
- optimization 35
 - 2n3947 Gummel model 41
 - DC 41
 - diode

- I-V and C-V 41
 - temperature 41
- GaAs
 - FET 41
 - JFET 41
- GaAsFET s-parameter 41
- group delay 37
- hfe 41
- I-V 41
- JFET 41
- Level=2 model beta 40
- Level=28 41
- MOS 41
 - Level=13 I-V 41
 - Level=2 I-V 41
 - Level=3 I-V 41
 - Level=6 I-V 41
- s-parameter 41
- speed, power, area 37
- width 37
- parameters 34
- PCI
 - Monte Carlo analysis 44
 - worst-case modeling 44
- peripheral component interconnect
 - see PCI
- phase detector 35
- phase locked loop 35
- photocurrent 44–46
 - GaAs device 46
- photolithographic effects 35
- piecewise linear source
 - see demo files, PWL
- pll 35
- pole/zero analysis 34, 43
- pulse source 46
- PWL 46
 - CCCS 36
 - CCVS 36
 - switch element 36
 - VCCS 35, 36
 - VCO 36
 - VCVS 36
- radiation effects
 - bipolar devices 44–45
 - DC I-V, JFET 46
 - GaAs differential amplifier 46
 - JFET devices 45
 - MOSFET devices 45
 - NMOS
 - NAND 46
 - voltage divider 46
- RC circuit optimization 38
- resistor temperature coefficients 38
- RG58/AU coax test 43
- ring oscillator 36
- Royer magnetic core oscillator 43
- Schmidt trigger 34
- sense amplifier 34
- series source coupled transmission
 - lines 47
- setup
 - characterization 37
 - time search 36, 37
- shunt terminated transmission lines
 - 47
- silicon controlled rectifier 36
- sine wave sampling 35, 36
- single-frequency FM source 46
- sinusoidal source 46
- skew models 35
- SNAP to HSPICE conversion 37

- s-parameters 37, 43
 - Level=13 44
- sweep 34
- switch 35
 - characterization 35
- switched capacitor 35, 46
 - RC circuit 36
- temperature effects
 - Level=13 44
 - Level=6 44
- total radiation dose 45
- transient analysis 34
- transistor characterization 40
- triode model 36
- tunnel diodes 36, 37
- twinlead transmission line model 47
- U models 47
- unity gain frequency 37
- Viewsim
 - analog to digital input 37
 - digital to analog input 37
- voltage
 - follower 35
 - to frequency converter 34
 - variable capacitor 35
- voltage controlled
 - current source 35, 36
 - oscillator 34, 36
 - resistor inverter 46
 - voltage source 36
- waveform smoothing 36
- worst case skew model 35
- See also demonstration files
- demonstration files
 - algebraic output variables 34
 - behavioral applications 35–36
 - benchmarks 36
 - BJT's and diodes 37
 - cell characterization 37
 - circuit optimization 37–38
 - device optimization 40–41
 - Discrete Device Library 38–40
 - filters 42–43
 - Fourier analysis 41–42
 - general applications 34–35
 - magnetics 43
 - MOSFET's 43–44
 - peripheral component interconnect 44
 - radiation effects 44–46
 - sources 46
 - timing analysis 36
 - transmission lines 46–47
 - See also demo files
- depletion
 - capacitance, DCAP equation selector 13-4, 14-3, 15-6
 - MOS devices 16-2
- DERIVATIVE keyword 4-29
- derivative, measuring 4-25
- design
 - name 3-15
 - partitioning 20-7
 - stability 27-2
 - time, reducing 27-2
- deviation, average 10-3
- device characterization 3-56
- Device Model Builder optimization 11-3
- DFT 26-1
- DI control option 6-26, 7-12, 9-7

- DIAGNOSTIC option 3-49
- diagnostic tables 6-35–6-36
- dielectric constants 12-15
- differentiator, behavioral 23-72
- diffusion layer process parameters,
 - MOSFET Level 13 17-109
- DIFSIZ optimization parameters 11-8
- digital
 - elements 23-40, 23-42
 - files 5-46, 23-39
 - input 5-46
 - input element 5-47
 - input files 20-18
 - models 23-40
- digital to analog
 - conversion 23-39
 - model parameters 23-40
- DIM2
 - distortion measure 9-14
 - parameter 4-15
- DIM3
 - distortion measure 9-14
 - parameter 4-15
- diodes
 - area 13-6
 - breakdown example 5-32
 - capacitance 13-28
 - calculations 13-4
 - equations 13-28
 - depletion capacitance 13-29
 - diffusion capacitance 13-28
 - Level 3 metal 13-30
 - Level 3 poly 13-30
 - Fowler-Nordheim diodes 13-38
 - conductance 13-12
 - control options 13-3
 - convergence problems 13-4
 - current 13-11
 - current flow 4-13
 - effective length 13-7
 - effective width 13-8
 - elements 13-6
 - names 13-6
 - statements 13-6
 - equation example 5-31
 - equations 13-25–13-34
 - Fowler-Nordheim diodes 13-37
 - equivalent circuits 13-12–13-13
 - Fowler-Nordheim 13-2, 13-35
 - element names 13-35
 - initial condition 13-36
 - initial voltage 13-36
 - length 13-35
 - multiplier parameter 13-36
 - width 13-35
 - geometric junction 13-2
 - initial voltage 13-7
 - junction 13-1
 - DC equations 13-26
 - model 13-14
 - capacitance parameters (table) 13-19
 - DC parameters (table) 13-16
 - periphery 13-7
 - temperature parameters 13-22
 - length 13-7
 - metal capacitor 13-7
 - polysilicon capacitor 13-7
 - metal model capacitance parameters (table) 13-20

- models 3-65
 - levels 13-3
 - names 13-7
 - noise parameters (table) 13-21
 - regions 13-26
 - variables (table) 13-25
- MOSFET
 - model selector 16-7
 - models 16-7, 16-29
- noise equations 13-30
- nongeometric junction 13-2
- poly model capacitance parameters (table) 13-20
- power dissipation 4-17
- scaling 13-36
 - options 13-3
 - parameters 13-8–13-11
- series resistance units 13-18
- temperature
 - compensation equations 13-31
 - effects 13-22
 - equations
 - breakdown voltage 13-32
 - contact potential 13-32
 - energy gap 13-31
 - grading coefficient 13-34
 - junction capacitance 13-33
 - leakage current 13-31
 - resistance 13-34
 - transit time 13-32
- terminal names 13-7
- types 13-2
- width 13-8
 - metal capacitor 13-8
 - polysilicon capacitor 13-8
- Zener 13-3
 - See also junction diodes, Zener diodes
- directories
 - installation directory 3-56
 - models 3-60
 - tmp 3-8
- DIS 23-86
- Discrete Device Library 3-56
 - DDLPATH variable 3-57
- discrete device library 23-5
 - models 28
- Discrete Fourier Transform 26-1
- .DISTO statement 9-14, 9-15
- distortion
 - analysis 9-14
 - measures 9-14
- DLEV model parameter 22-15, 22-17, 22-23, 22-26, 22-30
- document conventions iv
- documentation issues iii
- dollar sign comment delimiter 3-28
- dot convention 12-26, 12-29, 12-30
- drain current equation, MOSFET Level 47 17-235
- drain-to-source current, convergence error tolerance 6-24
- DTEMP element parameter 10-61
- DTEMP model parameter 10-61, 10-62, 26
- DV
 - calculation 6-25
 - option 6-16
- DV option 6-28

- DVDT
 - algorithm 7-11, 7-13, 7-21, 7-25
 - option 7-9, 7-25, 7-26
 - timestep control 7-19, 7-27
- DVTR option 7-15
- Dxxx diode element statement 13-6
- dynamic timestep algorithm 7-26
- E**
- E elements 23-13, 27-23–27-30
 - applications 23-13
 - controlling voltage 23-33
 - data points 23-32
 - data sampler application 23-81
 - element name 23-31
 - element value multiplier 23-32
 - gate type 23-31
 - initial conditions 23-31
 - integrator application 23-71
 - maximum voltage 23-32
 - minimum voltage 23-32
 - NAND gate 23-48
 - parameter value multiplier 27-10
 - polynomial
 - coefficients 23-32
 - dimension 23-32
 - SCALE parameter 27-34
 - temperature coefficients 23-32
 - time delay keyword 23-33
 - transformer application 23-74
 - triode application 23-78
 - turns ratio 23-31
 - voltage gain 23-31
- E format 4-49
- Early voltage 17-5
- Ebers-Moll model 14-1, 14-17
- ECL devices 14-2
- effective capacitance 12-6
 - calculation 12-19
- effective channel length, MOSFET's
 - equations
 - Level 1 17-6
 - Level 13 17-114
 - Level 28 17-160
 - Level 39 17-193
 - Level 49 17-255
 - Level 5 17-39
 - Level 6 17-62
 - Level 8 17-97
 - parameters
 - Level 1 17-3
 - Level 2 17-9
 - Level 3 17-21, 17-25
 - Level 38 17-169
 - Level 49 17-247
 - Level 5 17-36
 - Level 8 17-92
 - Levels 6, 7 17-56
- effective channel width
 - equations
 - MOSFET's
 - Level 1 17-6
 - Level 13 17-114
 - Level 2 17-13
 - Level 28 17-160
 - Level 3 17-25
 - Level 39 17-193
 - Level 49 17-255
 - Level 5 17-39
 - Level 6 17-62

- parameters
 - MOSFET's
 - Level 1 17-3
 - Level 2 17-9
 - Level 3 17-21
 - Level 38 17-169
 - Level 49 17-247
 - Level 5 17-36
 - Level 8 17-92, 17-97
- effective length, diodes 13-7
- effective mobility
 - parameters, MOSFET Level 6 17-78
- effective mobility, MOSFET's
 - equations
 - Level 28 17-161
 - Level 3 17-27
 - Level 6 17-78
 - Level 8 17-98
- effective resistance 12-7
 - AC 12-6
- effective width, diodes 13-8
- EISA standard 20-32
- element parameters
 - BJT's 14-4
 - AREA 14-5
 - area value 14-4
 - AREAB 14-5
 - AREAC 14-5
 - DTEMP 14-5
 - IC 14-5
 - M 14-5
 - model name 14-4
 - node names 14-4
 - OFF 14-5
 - Qxxx 14-4
 - capacitors 12-3, 12-16–12-17
 - C0 12-3
 - C1 12-3
 - capacitance 12-16
 - CTYPE 12-18
 - Cxxxx 12-16
 - DTEMP 12-17
 - IV 12-18
 - L 12-17
 - M 12-17
 - POLY 12-3
 - SCALE 12-18
 - TC1 12-16
 - TC2 12-17
 - W 12-17
 - digital elements
 - SIGNAME 23-42
 - digital elements, SIGNAME 23-40
 - diodes 13-5
 - AREA 13-6
 - DTEMP 13-6
 - Dxxx 13-6
 - IC 13-7
 - L 13-7
 - LM 13-7
 - LP 13-7
 - M 13-7
 - OFF 13-7
 - PJ 13-7
 - W 13-8
 - WM 13-8
 - WP 13-8
 - DTEMP 10-61, 12-3
 - E elements
 - ABS 23-31
 - DELAY 23-31

- DELTA 23-31
- IC 23-31
- MAX 23-32
- MIN 23-32
- NPDELAY 23-32
- OPAMP 23-32
- POLY 23-32
- PWL 23-32
- SCALE 23-32
- TC1, TC2 23-32
- TD 23-33
- TRANSFORMER 23-33
- VCVS 23-33
- F elements
 - ABS 23-26
 - CCCS 23-27
 - DELAY 23-27
 - DELTA 23-27
 - IC 23-27
 - M 23-27
 - MAX 23-27
 - MIN 23-27
 - NPDELAY 23-28
 - POLY 23-28
 - PWL 23-28
 - SCALE 23-28
 - TC1, TC2 23-28
 - TD 23-28
- Fowler-Nordheim diodes
 - D 13-35
 - Dxxx 13-35
 - IC 13-36
 - M 13-36
 - model name 13-35
 - node names 13-35
 - OFF 13-36
 - W 13-35
- G and E elements
 - DELTA 27-9
 - FREQ 27-10
 - LAPLACE 27-10
 - LEVEL 27-10
 - M 27-10
 - MAX 27-10
 - MAXF 27-10
 - POLE 27-10
 - SCALE 27-10
 - TC1 27-10
 - TC2 27-10
- G elements
 - ABS 23-20
 - CUR 23-21
 - DELAY 23-21
 - DELTA 23-21
 - Gxxx 23-21
 - IC 23-21
 - M 23-21
 - MAX 23-21
 - MIN 23-21
 - NPDELAY 23-22
 - NPWL 23-22
 - POLY 23-22
 - PPWL 23-22
 - PWL 23-22
 - SCALE 23-22
 - SMOOTH 23-22
 - TC1, TC2 23-23
 - TD 23-23
 - VCCAP 23-23
 - VCCS 23-23
 - VCR 23-23

- geometric 12-3
- H elements
 - ABS 23-35
 - CCVS 23-36
 - DELAY 23-36
 - DELTA 23-36
 - IC 23-36
 - MAX 23-36
 - MIN 23-36
 - NPDELAY 23-37
 - POLY 23-37
 - PWL 23-37
 - SCALE 23-37
 - TC1, TC2 23-37
 - TD 23-37
- independent sources 5-2
 - AC 5-3
 - AM function 5-18
 - data driven PWL function 5-15
 - DC 5-3
 - EXP function 5-11
 - Iyyy 5-3
 - M 5-3
 - PULSE function 5-6
 - PWL function 5-13
 - SFFM function 5-17
 - SIN function 5-9
 - Vxxx 5-2
- inductors 12-3
 - C0 12-3
 - C1 12-3
 - POLY 12-3
- initial conditions 12-4
- JFET and MESFET 15-7
 - AREA 15-8
 - DTEMP 15-8
 - IC 15-8
 - Jxxx 15-7
 - L 15-8
 - M 15-8
 - OFF 15-8
 - W 15-8
- linear inductors 12-24
 - DTEMP 12-24
 - IC 12-23
 - Kxxx 12-26
 - L 12-23
 - LTYPE 12-24
 - Lxxx 12-23
 - M 12-24
 - R 12-24
 - SCALE 12-23
 - TC1 12-23
 - TC2 12-23
- MAG 12-30
- magnetic windings
 - IC 12-29
 - Lxxx 12-29
 - NT 12-29
 - R 12-29
- MOSFET's
 - (list) 16-15
 - AD 16-13
 - AS 16-13
 - DELVTO 16-14
 - DTEMP 16-14
 - GEO 16-14, 16-45
 - L 16-12
 - M 16-14
 - Mxxx 16-12
 - NRD 16-13
 - NRS 16-13

- OFF 16-14
- PD 16-13
- PS 16-13
- RDC 16-13
- RSC 16-13
- W 16-13
- mutual inductors 12-3
 - K 12-26
- nonlinear
 - capacitors 12-3
 - inductors 12-3
- piecewise linear sources
 - PV 5-16, 7-38
 - R 5-13
 - TD 5-13
 - TIME 5-16, 7-38
- polynomial capacitors
 - Cxxx 12-21
 - IC 12-22
 - POLY 12-21
- polynomial inductors
 - IC 12-28
 - Lxxx 12-28
 - POLY 12-28
- R 12-3
- resistors 12-3
 - AC 12-6
 - C 12-6
 - DTEMP 12-6
 - L 12-6
 - M 12-7
 - R 12-7
 - Rxxx 12-7
 - SCALE 12-7
 - TC1 12-7
 - TC2 12-7
 - W 12-7
- T elements
 - F 22-11
 - IC 22-11
 - L 22-11
 - NL 22-11
 - TD 22-11
 - Txxx 22-11
 - Z0 22-11
- U elements
 - cij 22-52
 - cpr 22-52
 - crj 22-52
 - gij 22-52
 - gpr 22-53
 - grj 22-52
 - hti 22-53
 - L 22-14
 - lij 22-53
 - ljj 22-53
 - lri 22-53
 - lrr 22-53
 - LUMPS 22-14
 - ric 22-53
 - ris 22-53
 - rjj 22-53
 - rrc 22-53
 - rrr 22-53
 - rrs 22-53
 - skin 22-53
 - skinb 22-53
 - spi 22-53
 - thi 22-53
 - Uxxx 22-14
 - wdi 22-53
- element statements 3-56, 12-2, 16-3

- BJT 14-4
- capacitor 12-16
- Cxxx 12-16
- digital element 23-42
- diodes 13-6
- G elements 23-18–23-25
- ideal T element 22-10
- independent sources 5-2
- JFET and MESFET 15-7
- linear inductor 12-23
- magnetic winding 12-29
- MOSFET 16-12
- mutual core 12-30
- mutual inductor 12-26
- op-amps 23-83
- polynomial inductor 12-28
- resistor 12-6
- Rxxx 12-6
- transconductance
 - Laplace 27-6
 - pole/zero 27-7
- U element 22-14
- voltage gain
 - Laplace 27-6
 - pole/zero 27-7
- elements
 - analog behavioral 23-70
 - capacitors 12-16
 - checking, suppression of 3-52
 - descriptions 12-2
 - digital 23-40, 23-42
 - diodes 13-6
 - IC parameter 6-6
 - ideal 5-20
 - independent sources 5-6
 - linear inductors 12-23
 - magnetic winding 12-29
 - magnetics 12-29
 - mutual inductors 12-26
 - names 3-26, 3-30, 12-2
 - nonlinear 12-3
 - OFF parameter 6-4, 6-18
 - parameters 12-2–12-4
 - .ALTER blocks 10-31
 - DELTA 23-17
 - POLY 23-14
 - scaling 16-10
 - polynomial capacitors 12-21
 - polynomial inductors 12-28
 - resistors 12-6
 - saturable cores 12-30
 - scale factors 12-7, 12-18
 - statement 3-25
 - subcircuits 23-11
 - temperature 10-62
 - template function 10-7
 - templates 4-35–4-39
 - BJT 4-39
 - capacitor 4-36
 - current-controlled
 - current source 4-38
 - voltage source 4-38
 - independent
 - current source 4-39
 - voltage source 4-38
 - inductor 4-36
 - JFET 4-42
 - MOSFET 4-43
 - mutual inductor 4-37
 - resistor 4-36
 - saturable core
 - element 4-46

- winding 4-46
 - voltage-controlled
 - current source 4-37
 - voltage source 4-37
 - types 3-26
- ELEV model parameter 22-7, 22-15, 22-17
- Elmore delay 27-30
- enable (digital vector file) 5-67
- encrypted data 29-2
- encryption
 - file organization 29-6
 - FREELIB keyword 29-7
 - permit file changes 29-7
 - semicolon bug 29-5
- .END statement
 - for multiple HSPICE runs 3-24
 - in libraries 3-64
 - location 3-24
 - missing 3-17
 - with .ALTER 10-31
- ENDDATA keyword 3-38
- .ENDL statement 3-61, 3-62
- .ENDS statement 23-10
- energy gap temperature equations
 - BJT 14-53
 - JFET and MESFET 15-45
- engineering format 4-49
- environment variables
 - DDLPATH 3-57, 28
- .EOM statement 23-10
- epitaxial charge 14-50
- EPSMIN option 3-49, 27-17
- equivalent circuits
 - BJT 14-7
 - JFET 15-10
 - MOSFET 16-18
- ERR function 4-31, 4-32
- ERR1
 - function 4-31, 4-32
 - keyword 11-3
- ERR2 function 4-31, 4-33
- ERR3 function 4-31, 4-33
- error tolerances
 - ABSMOS 6-24
 - branch current 6-14, 6-23
 - optimization by bisection 28-8
 - pole/zero analysis 8-12
 - relative change 6-27, 7-13
 - RELMOS 6-24
 - voltage 6-27, 7-13
- error, optimization goal 4-21
- errors
 - bulk node not specified 12-15
 - cannot open input file 3-10
 - could not open output spool file 4-9
 - current exceeding MAXAMP 7-12
 - DC 6-31
 - digital file has blank first line 5-46
 - file open 3-8
 - functions 4-31–4-33
 - internal timestep too small 6-5, 6-16, 6-38, 7-3, 7-8, 7-9, 7-17
 - missing .END statement 3-17
 - negative slope for magnetization level 12-34
 - no DC path to ground 6-33
 - no input data 3-7

- parameter name conflict 10-17
 - printing 3-52
 - reference to undefined inductor 12-27
 - special characters in input 3-18
 - system resource inaccessible 4-9
 - timestep control error in
 - transmission lines 22-64
 - excess phase 14-44
 - EXP source function 5-11
 - fall time
 - constant 5-11
 - delay 5-11
 - initial value 5-11
 - pulsed value 5-11
 - rise time
 - constant 5-11
 - delay 5-11
 - exp(x) function 10-7
 - experiment 3-3
 - EXPMAX option 3-49
 - exponential
 - function 10-7
 - source function 5-11
 - SPICE format 4-49
 - expressions for parameters 10-12
 - external data files 3-21, 3-38
 - extraction, layout parameters 20-55
- F**
- F element parameter 22-11
 - F elements 23-13
 - applications 23-14
 - controlling voltage 23-28
 - current gain 23-27
 - data points 23-28
 - gate type 23-27
 - initial conditions 23-27
 - maximum current 23-27
 - minimum current 23-27
 - multiply parameter 23-27
 - name 23-27
 - polynomial
 - coefficients 23-28
 - dimension 23-28
 - temperature coefficients 23-28
 - time delay keyword 23-28
 - value multiplier 23-28
 - FALL keyword 4-22
 - fall time example 20-10
 - fanout, plotting 20-5
 - Fast Fourier Transform
 - see FFT
 - FAST option 7-12, 7-18
 - ferromagnetic core models 12-33
 - FFT
 - analysis
 - alfa control parameter 26-7
 - frequency
 - of interest 26-9
 - range 26-9
 - specification 26-7
 - frequency range 26-10
 - harmonic distortion 26-14
 - maximum frequency 26-7
 - minimum frequency 26-7
 - number of points 26-6
 - output magnitude format 26-6
 - results 26-9–26-10

- spectral leakage 26-14
- start point 26-6
- statement syntax 26-6–26-8
- stop point 26-6
- window type 26-7
- windows 26-2–26-4
 - Bartlett 26-3
 - Blackman 26-3
 - Blackman-Harris 26-3
 - Gaussian 26-3
 - Hamming 26-3
 - Hanning 26-3
 - Kaiser-Bessel 26-3
 - rectangular 26-3
- .FFT statement 26-1, 26-6
- field effect transistor 16-23
 - geometry 16-23
 - See also MOSFET, JFET
- field programmable gate arrays 20-22
- FIL keyword 3-38
- file descriptors limit 4-9
- files
 - .a2d 4-3, 4-4, 5-46
 - .ac# 4-2
 - .ft# 4-3, 4-4, 26-10
 - .gr# 4-3
 - .ic 4-3, 6-5
 - .lis 4-2
 - .ma# 4-2
 - .MEASURE output 20-1
 - .ms# 4-2
 - .mt# 4-2
 - .pa# 4-3
 - .st# 4-3
 - .sw# 4-2
 - .tr# 4-2
- AC analysis
 - measurement 4-4
 - results 4-4
- column lamination 3-42
- concatenated data files 3-41
- d2a 5-46
- DC analysis
 - measurements 4-4
 - results 4-4
- design.ac0 20-1
- design.mt0 20-1
- design.sw0 20-1
- digital input 20-18
- external data 3-21, 3-37
- filenames 3-38
- graph data 3-4, 4-4
- hspice.ini 3-51
 - creation 3-57
- include files 3-21, 3-60, 3-64
- including 3-16
- initialization 3-16
- input 3-4
 - file name 3-11
- limit on number 4-9
- multiple simulation runs 3-24
- names 3-11–3-13, 3-15
 - suffixes 3-11
- output
 - listing 4-3
 - names 3-12
 - status 4-5
 - version number 3-12
- scratch files 3-8
- subcircuit node cross-listing 4-5
- transient analysis

- measurement 4-4
- results 4-4
- transition data 23-4
- filing a documentation bug iii
- filters
 - active low-pass 25-14
 - band reject 27-11
 - low-pass 27-13
 - pole/zero analysis
 - Butterworth 25-9
 - high-pass 25-9
 - low-pass 25-5, 25-14
 - transfer functions 27-28
- FIND keyword 4-25
- fixed and exponential format 4-49
- flicker noise 16-104
- floating point overflow
 - CONVERGE setting 6-25
 - setting GMINDC 6-26
- Fluke-Mosaïd model 16-4
- FMAX
 - .FFT parameter 26-7
 - option 25-4
- FMAX option 8-11
- FMIN .FFT parameter 26-7
- FORMAT .FFT parameter 26-6
- FORTRAN logical units 3-62
- Fourier
 - coefficients 7-31
 - equation 7-31
 - integral 27-5
 - transfer function $H(f)$ 27-5
 - transform 27-5
- .FOURIER statement 7-30
- Fowler-Nordheim diodes 13-2
 - capacitances 13-38
 - element statement 13-35
 - equations 13-37
 - model parameters 13-37
 - scaling 13-36
- FPGA's 20-22
- FR1 model parameter 22-38
- FREELIB keyword 29-7
- FREQ
 - element parameter 27-10
 - function
 - transconductance element statement 27-8
 - voltage gain element statement 27-8
 - keyword 27-5
 - model parameter 4-56, 23-86
- frequency
 - analysis 26-1
 - complex 27-4, 27-17
 - critical 27-5
 - domain, transfer function 27-17
 - maximum 27-6
 - frequency analysis 27-10
 - maximum, setting 8-11
 - Nyquist, frequency analysis 27-10
 - poles and zeros, frequency analysis 27-10
 - ratio 9-15
 - resolution 27-6
 - Fourier analysis 27-6
 - frequency analysis 27-9
 - response 27-4
 - response analysis 27-3

- response table 27-8
- response table, frequency analysis 27-10
- setting scale 8-11
- sweep 9-6
- table 27-3
- variable 10-8
- weighing functions 26-2
- frequency domain to time domain 27-1
- FROM
 - .FFT parameter 26-6
 - keyword 4-32
- FS
 - keyword 9-18
 - option 7-15, 7-17, 7-27
- FSCAL option 8-11, 8-12, 25-4
- FT option 7-15, 7-17, 7-27
 - timestep control 7-27
- .ft# file 4-3, 4-4, 26-10
- functions
 - A2D 5-46, 23-4
 - bisection 28-1
 - built-in 10-6–10-7
 - D2A 5-46, 23-4
 - in parameters 10-13
 - LAPLACE 25-1, 27-2, 27-6
 - NPWL 5-26
 - OPTIMIZE 23-3
 - POLE 25-1, 27-2, 27-7
 - PPWL 5-27
 - redefining 10-8
 - table 10-6
 - See also independent sources
- FV function value 23-14

G

- G elements 23-13, 27-23–27-28
 - amplitude modulator application 23-80
 - AND gate 23-48
 - applications 23-13
 - controlling voltages 23-21, 23-23
 - curve smoothing 23-22
 - data points 23-22
 - DELTA parameter 23-75
 - element value multiplier 23-22
 - gate type 23-21
 - initial conditions 23-21
 - maximum
 - current 23-21
 - resistance 23-21
 - minimum
 - current 23-21
 - resistance 23-21
 - multiply parameter 23-21, 27-10
 - names 23-21
 - parameter value multiplier 27-10
 - polynomial
 - coefficients 23-22
 - dimension 23-22
 - polynomial dimension 23-22
 - temperature coefficients 23-23
 - time delay keyword 23-23
 - transconductance 23-23
 - triode application 23-78
 - tunnel diode application 23-75
 - voltage to resistance factor 23-23
- G format 4-49
- gain, calculating 9-9
- gate

- capacitance
 - equations, JFET and MESFET 15-29–15-35
 - MOSFET Level 39 17-201
 - parameters, JFET 15-20
 - temperature equations, JFET and MESFET 15-46
 - diode DC parameters, JFET 15-18
- GAUSS
 - FFT analysis keyword 26-7
 - keyword 10-41
 - Monte Carlo function 10-16
- Gaussian FFT analysis window 26-3
- Gaussian parameter distribution 10-39
- GBW model parameter 23-86
- GEAR algorithm 7-9, 7-21
- GE-CRD Franz model 16-4
- GE-Intersil model 16-4
- geometric element parameters 12-3
- geometry
 - area calculation method 15-26
 - JFET and MESFET parameters 15-9
 - model parameters 12-5
 - scale factor 12-7, 12-18, 12-23
 - scaling 16-11
 - substrate diode 14-33
- getting customer support vi
- global node names 3-25
- global parameters 3-53, 10-19
- global scaling 16-11
 - overriding 15-9
 - in models 13-3
- GMAX option 6-26
- GMIN
 - option 7-15
- GMIN option 6-40, 15-5
 - stepping 6-26
- GMINDC option 6-26, 6-28, 6-40, 16-29
 - JFET and MESFET conductance 15-5
- GND node 3-31
- GOAL keyword 4-24, 11-3
- .gr# file 4-3, 4-4
 - maximum version number 4-55
- GRAD optimization parameter 11-8
- gradient data, printing 3-52
- GRAMP
 - calculation 6-25
 - option 6-16, 6-26, 6-28, 6-32
- GRAMP conductance option 15-5
- graph data
 - file 3-4
 - Viewlogic format 3-49
- graph data file
 - See also .gr# file
- .GRAPH statement 15
- ground bounce 20-23
- ground node name 3-31
- ground plane, transmission lines 22-5
- group delay, calculating 9-8
- Grove-Frohman model 16-3
- GSCAL
 - multiplier 8-11
 - option 8-11
- GSCAL option 25-4
- GSHUNT option 6-16, 7-9
- Gummel-Poon model 14-1

Gxxx element parameters 23-21

H

H elements 23-13

- applications 23-13
- controlling voltage 23-37
- data points 23-37
- element name 23-36
- element value multiplier 23-37
- gate type 23-36
- initial conditions 23-36
- maximum current 23-36
- minimum current 23-36
- polynomial
 - coefficients 23-37
 - dimension 23-37
- SCR application 23-77
- temperature coefficients 23-37
- time delay keyword 23-37
- transresistance 23-37

H parameters 9-25

H9007 option 3-49

HAMM FFT analysis keyword 26-7

Hamming FFT analysis window 26-3

HANN FFT analysis keyword 26-7

Hanning FFT analysis window 26-3

harmonic distortion 9-14, 26-1

HARRIS FFT analysis keyword 26-7

HD2

- distortion measure 9-14
- parameter 4-15

HD3

- distortion measure 9-14
- parameter 4-15

hertz variable 10-8

Hessian data, printing 3-52

HGP model parameter 22-17, 22-26, 22-28, 22-30

hierarchical designs, flattened 3-29

hold time 28-4

HSPICE

- ground for transmission lines 22-21
- installation directory 3-56
- integration method 22-22
- job statistics report 4-6-4-9
- output
 - redirecting 3-13
- starting 3-7
- version
 - 95.3 compatibility 7-27
 - H9007 compatibility 3-49

VERSION parameter 3-66

version, specifying 3-12

hspice command 3-10-3-14

arguments 3-11

HSPICE model enhancements 17-265

hspice.ini file 3-51

creating 3-57

HT model parameter 22-17, 22-26

HT1 model parameter 22-26

hybrid (H) parameters 9-8

I

I/O cell modeling 31

IB model parameter 23-86

IBIS

converting to HSPICE format 24-4

- specification 24-1
- IBIS to HSPICE program 24-2
- IBOS model parameter 23-86
- IC
 - element parameter 6-6, 22-11, 23-21, 23-27, 23-31, 23-36
 - keyword 6-12
 - parameter 6-6
- .ic file 4-3, 6-5
- .IC statement 6-3, 6-4, 25-3
 - balancing input nodes 23-83
 - from .SAVE 6-11
- .IC statment 12-22
- ICSWEEP option 6-17
- ideal
 - current sources 6-32
 - delay elements 23-13
 - DELMAX setting 7-19
 - op-amp 5-37, 5-40, 23-13, 23-30, 23-32, 23-33
 - transformer 5-38, 5-41, 23-31, 23-34
 - transformers 23-13
 - transmission lines 22-6
- ideal delay elements 23-13, 23-14
- idelay (digital vector file) 5-68
- IDS Cypress depletion model 16-5
- IDS equations, MOSFET's
 - Level 1 17-5
 - Level 13 17-114
 - Level 2 17-12
 - Level 3 17-24
 - Level 38 17-174
 - Level 5 17-38
 - Level 6 17-62, 17-74
 - Level 8 17-96
- IGNOR keyword 4-31
- IKF model parameter 14-2
- IKR model parameter 14-2
- imaginary part of AC voltage 9-10
- imaginary vs. real component ratio 8-12
- IMAX option 7-16, 7-25
 - default 7-25
- IMIN option 7-16, 7-25
 - default 7-25
- impact ionization
 - BSIM2 17-201
 - equations, MOSFET 16-19
 - MOSFET Level 39 17-201
 - MOSFET's 16-55
- impedance 22-101
 - AC 9-13
 - versus time 20-9
 - Z parameters 9-8
- impulse response h(t) 27-5
- inactive devices
 - see latent devices
- include files 3-16, 3-60, 3-64
- .INCLUDE statement 3-21, 3-57, 3-58
 - and .ALTER blocks 10-31
- independent sources
 - AC 5-4
 - magnitude parameter 5-3
 - phase parameter 5-3
 - AM function 5-18
 - current source name 5-3
 - data driven PWL function 5-15
 - DC 5-4
 - source value parameter 5-3

- elements
 - parameters 5-2
 - statements 5-2
- EXP function 5-11
- mixed types 5-5
- PULSE function 5-6
- PWL function 5-13
- SFFM function 5-17
- SIN function 5-9
- transient 5-4
- transient source function 5-3
- types 5-6
- voltage source name 5-2
- See also sources
- inductance 22-104
 - effective value 12-23
 - element parameter 12-23
 - function of current 12-24, 12-28
 - mutual 12-27
 - temperature equation 12-25
- inductance scale 8-11
- inductors
 - coupling 12-27
 - DC resistance 12-24, 12-29
 - dot convention 12-26, 12-29
 - elements
 - names 12-23, 12-26, 12-28
 - parameters 12-3
 - initial current 12-23, 12-28
 - linear 12-23
 - branch relations 12-27
 - mutual 12-26
 - coupling coefficient 12-26
 - models 3-65
 - node names 12-23, 12-28
 - nonlinear equations 12-3
 - number of turns 12-29
 - polynomial 12-28
 - coefficients 12-28
 - temperature coefficients 12-23
- INGOLD option 3-49, 3-51, 4-49
- initial conditions 6-3
 - file 3-16
 - saving and reusing 6-17
 - statement 6-6
 - transient 7-6
- initial conditions, element parameters 12-3, 12-4
- initialization 6-3, 6-4, 6-18
 - saved operating point 6-10
- inline data 3-38
- inner sweep 3-41
- INOISE parameter 4-15
- input admittance 9-13
- input data
 - adding library data 10-31
 - column laminated 3-42
 - concatenated data files 3-41
 - deleting library data 10-32
 - digital stimuli 20-18
 - external, with .DATA statement 3-37
 - filenames on networks 3-43
 - for data driven analysis 3-37
 - formats 3-39, 3-42
 - include files 3-60
 - printing 3-50
 - suppressing printout 3-50
- input files

- character case 3-17
 - compression 3-17
 - control characters 3-18
 - names 3-11, 3-15
 - structure 3-21
 - table of components 3-22
 - unprintable characters 3-18
- input impedance 9-13
- input netlist file 3-4
- .END statement requirement 3-24
 - See also input files
- input/output drivers 20-18
- installation directory \$installdir 3-56
- insulation breakdown devices 13-35
- int(x) function 10-7
- INTEG keyword 4-24, 4-30
- integer function 10-7
- INTEGRAL keyword 4-30
- integration
- algorithms 7-21, 22-45, 22-64
 - backward Euler method 7-10
 - method 22-22
 - order of 7-10
- integrator, behavioral 23-70
- interconnect
- analyzing 20-2
 - See also transmission lines, wires
- interfaces
- Analog Artist 3-47
 - Mentor 3-51
 - MetaWaves 4-2
 - MSPICE 3-51
 - ZUKEN 3-55
- intermodulation distortion 9-14
- internal nodes, referencing 3-31
- INTERP option 7-9
- interstage gain 9-9
- inverse Laplace transform 27-30
- inverter gate 23-34
- io (digital vector file) 5-65
- I/O drivers 20-18
- ion-implanted devices 16-2
- ISA standard 20-32
- ISC model parameter 23-87
- ISPICE Level 6 model 17-75
- iteration
- algorithm 7-23
 - count algorithm 7-25
 - limit 6-17
- iterations
- data, printing 3-52
 - extra 6-18
 - maximum number of 7-16
 - number 11-20
- ITL1
- calculation 6-25
 - option 6-17
- ITL3 option 7-16
- ITL4 option 7-16
- ITL5 option 7-16
- ITLPZ option 8-11, 25-4
- ITROPT optimization parameter 11-8
- ITRPRP option 7-9
- Iyyy source element statement 5-2

J

JFET's

- area multiplying factor 15-8
- capacitance
 - equations 15-6, 15-29
 - parameters 15-33
- CAPOP=2 model parameters 15-33
- control options 15-5
- current convention 15-9
- current flow 4-13
- DC
 - model
 - equation selector 15-16
 - Level 1 parameters 15-23
 - Level 2 parameters 15-23
 - Level 3 parameters 15-25
 - voltage equations 15-35
- elements
 - names 15-7, 15-8
 - statements 15-7
- equivalent circuits 15-10
- gate capacitance parameters 15-20
- gate diode DC parameters 15-18
- initial conditions 15-8
- initial voltages 15-8
- length 15-8
- models
 - constants 15-14
 - names 15-8, 15-16
 - parameters 15-17
 - statements 15-16
 - variables 15-14
- n-channel specification 15-16
- noise
 - equations 15-39

- parameters 15-39
- summary printout 15-41
- output conductance 15-12
- p-channel specification 15-16
- power dissipation 4-18
- scaling 15-9
- temperature
 - differential 15-8
 - equations 15-45–15-49
 - parameters 15-42, 15-43
- TOM model parameters 15-52
- transconductance 15-10
- width 15-8

Jiles-Atherton model examples 12-36

JIS model parameter 23-87

junction diodes

- geometric 13-5
- nongeometric 13-5
- parameters 13-5

K

KAISER FFT analysis keyword 26-7

Kaiser-Bessel FFT analysis window 26-3, 26-5

KCLTEST option 6-17

KD model parameter 22-17, 22-26, 22-28, 22-30

KD1 model parameter 22-26

KD2 model parameter 22-27

Kerwin's circuit, pole/zero analysis 25-7

keywords

- AC 5-2
- ACI 5-2
- AGAUSS 10-41

ALL 6-8, 6-12
AM 5-2
AT 4-22
AUNIF 10-41
AVG 4-24
BART 26-7
BETA 9-18
BISECTION 28-7
BLACK 26-7
BRIEF 6-8
CROSS 4-22
CURRENT 6-8
DATA 3-37, 7-5, 8-4, 9-4
DC 5-2
DEBUG 6-8
DEC 7-6, 8-5, 9-5
DERIV 4-29
DERIVATIVE 4-29
DTEMP 10-61
ENDDATA 3-38
ERR1 11-3
EXP 5-2
FALL 4-22
FIL 3-38
FIND 4-25
FREELIB 29-7
FREQ 27-5
FROM 4-32
FS 9-18
GAUSS 10-41, 26-7
GOAL 4-24, 11-3
HAMM 26-7
HANN 26-7
HARRIS 26-7
IC 6-12
IGNOR 4-31
INTEG 4-24, 4-30
INTEGRAL 4-30
KAISER 26-7
LAM 3-38, 3-42
LAST 4-22, 4-25, 4-27
LIMIT 10-41
LIN 7-6, 8-5, 9-5
MAX 4-24
MAXFLD 9-18
MER 3-38, 3-41
MIN 4-24
MINVAL 4-24, 4-32
MODEL 8-4, 11-5
MONTE 7-5, 9-5, 10-39
NODESET 6-11
NONE 6-9, 6-12
NORM 26-6
NUMF 9-18
OCT 7-6, 8-5, 9-5
OPT 11-4, 28-7
OPTIMIZE 8-4, 11-4
PAR 10-5
PASSFAIL 28-7
PE 5-2
PL 5-2
PLOT 4-56
POI 7-6, 8-5, 9-5
POWER 4-16
PP 4-23, 4-24
PU 5-2
PULSE 5-2
PWL 5-2
R 5-2
RD 5-2
RECT 26-7
RESULTS 8-4

RIN 9-19
 RISE 4-22
 RMS 4-24
 ROUT 9-19
 SFFM 5-2
 SIN 5-2
 source functions 5-2
 START 7-5
 SWEEP 7-6, 8-5, 9-5
 TARG 4-21
 TD 4-14, 4-25
 TEMP 8-5, 9-5
 TO 4-24, 4-32
 TOL 9-18
 TOP 6-12
 TRIG 4-21
 UIC 7-6
 UNIF 10-41
 UNORM 26-6
 VOLTAGE 6-9
 WEIGHT 4-32
 weight 4-25
 WHEN 4-25
 YIN 9-13, 9-20
 YMAX 4-32
 YMIN 4-31
 YOUT 9-13, 9-20
 ZIN 9-13, 9-20
 ZOUT 9-13, 9-20
 KF model parameter 9-17
 Kirchhoff's Current Law test 6-17
 Kxxx inductor element statement 12-26,
 12-30

L

L element parameter 22-11, 22-14
 LAM keyword 3-38, 3-42
 lambda equations, MOSFET Level 6 17-
 63, 17-65
 laminated data 3-42
 LAPLACE
 element parameter 27-10
 function 25-1, 27-2, 27-5, 27-6, 27-
 21-27-25
 transconductance element state-
 ment 27-6
 voltage gain element statement
 27-6
 Laplace
 transfer function 27-2, 27-17
 transform 27-2, 27-6, 27-18, 27-19
 frequency analysis 27-10
 frequency response table 27-8
 inverse 27-30
 LAST keyword 4-22, 4-25, 4-27
 latency option 16-11
 latent devices
 BYPASS option 7-8, 7-11
 BYTOL option 7-11
 excluding 7-12
 MBYPASS option 7-11
 removing from simulation 7-11
 VNTOL option 7-11
 latent devices, bypassing 16-11
 Lattin-Jenkins-Grove model 16-4
 layout parameter extraction 20-55
 LC oscillator model 23-100

- LDAC parameter 16-103
- leadframe example 20
- LENGTH model parameter 10-46
- LENNAM option 3-50
- LEVEL
 - diode parameter 13-3
 - element parameter 27-10
 - model parameter 22-15, 22-17
 - model selector 15-3
 - optimization parameter 11-8
- levels, MOSFET models 16-2, 16-3
- LEVIN model parameter 23-87
- LEVOUT model parameter 23-87
- .LIB
 - call statement 3-61
 - definition statement 3-62
 - building libraries 3-62
 - statement 3-21, 3-58
 - in .ALTER blocks 3-61
 - nesting 3-63
- .LIB statement
 - in .ALTER blocks 10-30
 - with .DEL LIB 10-31
 - with multiple .ALTER statements 10-31
- libraries
 - adding with .LIB 10-31
 - ASIC cells 3-57
 - building
 - rules 3-64
 - with .LIB definition 3-62
 - defining macros 3-62
 - deleting 10-31
 - Discrete Device Library 3-56
 - accessing 3-59
 - duplicated parameter names 10-19
 - .END statement 3-64
 - networks 3-62
 - numbers 3-62
 - parts directory 3-60
 - path names 3-62
 - private 3-67
 - protecting 3-67, 29-1
 - search
 - order 3-57
 - path 3-57
 - selecting 3-59
 - subcircuits 3-58
 - vendors 3-57, 10-29
- LIMIT
 - keyword 10-41
 - Monte Carlo function 10-16
- limit descriptors command 4-9
- LIMPTS option 3-50
- LIMTIM option 3-50
- LIN keyword 7-6, 8-5, 9-5
- linear region equations, MOSFET Level 47 17-234
- .lis file 4-2, 4-3
- LIST option 3-50, 3-55
- listing
 - page width 4-51
 - suppressing 3-67
- LLEV model parameter 22-15, 22-17
- LMAX model parameter 5
- LMIN model parameter 5
- local parameters 3-53, 10-19
- local truncation error algorithm 7-10, 7-

- 14, 7-25, 7-26
 - timestep 7-13
 - log(x) function 10-6
 - log10(x) function 10-6
 - logarithm function 10-6
 - logic interface 20-18
 - logical units, FORTRAN 3-62
 - lossless transmission lines 22-6
 - model 22-99
 - lossy transmission lines 22-6, 22-12
 - model 22-100
 - lossy U model 22-15
 - LSCAL option 8-11, 25-4
 - Lscaled scaled length 12-6
 - Lsim models, calibrating 20-1
 - lumped parameters 22-22
 - LUMPS element parameter 22-14
 - LV 4-35
 - LV18 model parameter 15
 - LVLTIM option 7-9, 7-10, 7-13, 7-14, 7-19, 7-25
 - timestep control 7-27
 - LX 4-35
 - LX7 model parameter 15
 - LX8 model parameter 15
 - LX9 model parameter 15
 - Lxxx inductor element statement 12-23, 12-28, 12-29
- M**
- M
- 10
 - multiplier parameter
 - U and T elements 22-5
 - .ma# file 4-2, 4-4
 - mA741 op-amp 23-93
 - .MACRO statement 10-27, 23-9
 - macros
 - defining with .LIB definition 3-62
 - deleting library data 10-31
 - See also subcircuits
 - magnetic cores
 - models 3-65
 - ferromagnetic core 12-33
 - names 12-31
 - parameters 12-5, 12-32, 12-35
 - saturable core 12-29
 - statement 12-31
 - outputs (table) 12-36
 - magnetic windings
 - DC resistance 12-29
 - element parameters 12-4
 - initial current 12-29
 - names 12-29
 - number of turns 12-29
 - parasitic resistance 12-3
 - magnitude
 - AC voltage 9-10
 - calculating 9-9
 - MANU model parameter 23-87
 - manufacturing tolerances 10-46
 - Marquardt scaling parameter 11-20
 - mask (digital vector file) 5-68
 - matrixes
 - calculations 6-18

- minimum pivot values 6-20
 - parameters 9-19
 - row/matrix ratio 6-20
 - size limitation 6-20
 - MAX
 - element parameter 23-21, 23-27, 23-32, 23-36, 27-10
 - function 28-5
 - keyword 4-24
 - optimization parameter 11-8
 - max(x,y) function 10-7
 - MAXAMP option 6-17, 7-12, 9-7
 - MAXD model parameter 22-17
 - MAXF
 - element parameter 27-10
 - parameter 27-6
 - MAXFLD keyword 9-18
 - maximum number size 3-49
 - maximum value, measuring 4-23
 - MAXORD option 7-10
 - Maxwell matrix 22-36
 - MBYPASS option 7-11, 7-12, 16-11
 - mean, statistical 10-3
 - MEASDGT option 3-50
 - measfail value 28-8
 - MEASOUT option 3-51
 - measure data output formatting 3-50
 - .MEASURE statement 3-50, 3-51
 - failure message 4-20
 - parameters 10-17
 - Mentor interface 3-51
 - MENTOR option 3-51
 - MER keyword 3-38, 3-41
 - MESFET's
 - area multiplying factor 15-8
 - capacitance equations 15-6, 15-29
 - CAPOP=2 model parameters 15-33
 - control options 15-5
 - DC
 - model equation selector 15-16
 - voltage equations 15-35
 - elements
 - names 15-7, 15-8
 - statement 15-7
 - initial conditions 15-8
 - initial voltages 15-8
 - length 15-8
 - models
 - constants 15-14
 - names 15-8, 15-16
 - parameters 15-17
 - statements 15-16
 - variables 15-14
 - n-channel specification 15-16
 - noise
 - equations 15-39
 - parameters 15-39
 - summary printout 15-41
 - p-channel specification 15-16
 - scaling 15-9
 - temperature
 - differential 15-8
 - equations 15-45–15-49
 - width 15-8
- messages
 - pivot change 6-19
 - See also errors, warnings
 - Meta Encryptor 24-2

Meta I/O

- command syntax 24-10
- commands 24-10–24-17
- ExitMeatIoApi function 24-18
- GetConvFunction command 24-15
- GetConvType command 24-17
- GetFileMask command 24-13
- GetHspiceDir command 24-12
- GetIbisDescripDir command 24-11
- GetIbisTemplateDir command 24-12
- GetInFileSuffix command 24-13
- GetOutFileSuffix command 24-14
- GetTmpDir command 24-13
- GetVerDir command 24-12
- Iterate command 24-17
- SelectFiles command 24-7, 24-14
- SetConvFunc command 24-5
- SetConvFunction command 24-15
- SetConvType command 24-16
- SetDefTemplate command 24-6
- SetFileMask command 24-7, 24-13
- SetHspiceDir command 24-5, 24-12
- SetIbisDescripDir command 24-5, 24-11
- SetIbisTemplateDir command 24-5, 24-6, 24-12
- SetInFileSuffix command 24-7, 24-13
- SetOutFileSuffix command 24-7, 24-14
- SetTmpDir command 24-13
- SetVerDir command 24-5, 24-12
- TemplateMap command 24-6
- UnSelectFiles command 24-15
- UnselectFiles command 24-7

- metaio command 24-8
- metal contact 16-25
- MetaWaves interface 4-2
- METHOD option 7-10
- Meyer model 16-59
- microstrip transmission line 22-23
- MIN
 - element parameter 23-21, 23-27, 23-32, 23-36
 - keyword 4-24
- min(x,y) function 10-7
- minimum number size 3-49
- minimum value, measuring 4-23
- MINVAL keyword 4-24, 4-32
- mixed mode
 - See also D2A, A2D
 - simulation 5-46
- mixed mode simulation 23-4
- mixed-signal simulation
 - see mixed mode
- mobility
 - equations, MOSFET Level 47 17-232
 - parameters
 - curve fitting 17-12
 - MOSFET's
 - Level 2 17-11
 - Level 3 17-23
 - Level 38 17-171
 - Level 5 17-36
 - Level 8 17-94
 - reduction equations, MOSFET's
 - Level 2 17-15
 - Level 38 17-179

- Level 5 17-49
- temperature equations, JFET and MESFET 15-48
- MODEL keyword 8-4, 11-5
- model names, periods in 19-3
- model parameters
 - .ALTER blocks 10-31
 - A2D 5-46
 - analog to digital
 - CGGONLY 23-43
 - CLOAD 23-43
 - RLOAD 23-43
 - S19NAME 23-43
 - S19VHI 23-43
 - S19VLO 23-43
 - S1NAME 23-43
 - S1VHI 23-43
 - S1VLO 23-43
 - S2NAME 23-43
 - S2VHI 23-43
 - S2VLO 23-43
 - SONAME 23-43
 - SOVHI 23-43
 - SOVLO 23-43
 - TIMESTEP 23-43
 - BISECTION 28-7
 - BJT's
 - AF 14-26
 - base width modulation 14-22
 - BEX 14-27
 - BEXV 14-27
 - BF 14-19
 - BFM 14-19
 - BR 14-19
 - BRM 14-19
 - BRS 14-26
 - BULK 14-19
 - BV 14-22
 - C2 14-21
 - C4 14-21
 - CBEP 14-25
 - CCSP 14-25
 - CDIS 14-24
 - CJC 14-23
 - CJE 14-24
 - CJS 14-24
 - CPBP 14-25
 - CSUB 14-24
 - CTC 14-28
 - CTE 14-28
 - CTS 14-28
 - EG 14-28
 - ESUB 14-24, 14-29
 - EXPLI 14-19
 - FC 14-24
 - GAMMA 14-26
 - GAP1 14-28
 - GAP2 14-29
 - high current Beta degradation 14-22
 - IBC 14-19
 - IBE 14-19
 - IBR 14-22
 - IK 14-22
 - IKF 14-17, 14-22
 - IKR 14-17, 14-22
 - IOB 14-23
 - IS 14-20
 - ISC 14-17, 14-21
 - ISE 14-17, 14-21
 - ISS 14-20

ITF 14-25
JBF 14-22
JLC 14-21
JLE 14-21
JRB 14-23
JTF 14-25
junction capacitance 14-23
KF 14-26
LEVEL 14-20
Level 2 14-26
low current Beta degradation 14-21
MC 14-24, 14-29
ME 14-24, 14-29
MJC 14-24, 14-29
MJE 14-24, 14-29
MJS 14-24, 14-29
model name 14-16
NC 14-17, 14-21
NE 14-17, 14-21
NEPI 14-26
NF 14-20
NKF 14-22
NLC 14-21
NLE 14-21
noise 14-26
NPN 14-16
NR 14-20
NS 14-20
NSUB 14-19
parasitics
 capacitance 14-25
 resistance 14-23
PC 14-24
PE 14-24
PNP 14-16
PSUB 14-24
PTF 14-25
QCO 14-26
RB 14-23
RBM 14-23
RC 14-23, 14-26
RE 14-23
SUBS 14-20
TB 14-32
TBF1 14-29
TBF2 14-29
TBR1 14-29
TBR2 14-29
TCB 14-32
temperature
 effects 14-27
 parameters 14-27
TF 14-25
TIKF1 14-29
TIKF2 14-29
TIKR1 14-29
TIKR2 14-29
TIRB1 14-29
TIRB2 14-29
TIS1 14-30
TIS2 14-30
TISC1 14-29
TISC2 14-29
TISE1 14-30
TISE2 14-30
TISS1 14-30
TISS2 14-30
TITF1 14-30
TITF2 14-30
TLEV 14-30
TLEVC 14-30

TMJC1 14-30
 TMJC2 14-30
 TMJE1 14-31
 TMJE2 14-31
 TMJS1 14-31
 TMJS2 14-31
 TNC1 14-31
 TNC2 14-31
 TNE1 14-31
 TNE2 14-31
 TNF1 14-31
 TNF2 14-31
 TNR1 14-31
 TNR2 14-31
 TNS1 14-31
 TNS2 14-31
 TR 14-25
 transit time 14-25
 TRB 14-31
 TRB1 14-31
 TRB2 14-31
 TRC 14-31
 TRC1 14-31
 TRC2 14-31
 TRE 14-31
 TRE1 14-31
 TRE2 14-31
 TRM1 14-31
 TRM2 14-31
 TTF1 14-31
 TTF2 14-31
 TTR1 14-32
 TTR2 14-32
 TVAF1 14-32
 TVAF2 14-32
 TVAR1 14-32
 TVAR2 14-32
 TVJC 14-32
 TVJE 14-32
 TVJS 14-32
 UPDATE 14-20
 VA 14-22
 VAF 14-22
 VAR 14-22
 VB 14-22
 VBF 14-22
 VJC 14-24
 VJE 14-24
 VJS 14-24
 VO 14-26
 VRB 14-22
 VTF 14-25
 XCJC 14-24
 XTB 14-32
 XTF 14-25
 XTI 14-32
 BV 13-3
 capacitance 12-5
 CAP 12-19
 CAPSW 12-19
 COX 12-19
 DEL 12-19
 DI 12-19
 L 12-19
 SHRINK 12-19
 TC1 12-19
 TC2 12-19
 THICK 12-19
 TREF 12-19
 W 12-19
 capacitance distribution 10-48
 capacitors 12-5

- D2A 5-46
- DELVTO 10-34
- digital to analog 23-40
 - CHI 5-48, 23-41
 - CLO 5-48, 23-40
 - S19NAME 5-48, 23-41
 - S19RHI 5-48, 23-41
 - S19RLO 5-48, 23-41
 - S19TSW 5-48, 23-41
 - S1NAME 23-41
 - S1RHI 23-41
 - S1RLO 23-41
 - S1TSW 23-41
 - S2NAME 5-48, 23-41
 - S2RHI 5-48, 23-41
 - S2RLO 5-48, 23-41
 - S2TSW 5-48, 23-41
 - SINAME 5-48
 - SIRHI 5-48
 - SIRLO 5-48
 - SITSW 5-48
 - SONAME 5-48, 23-41
 - SORHI 5-48, 23-41
 - SORLO 5-48, 23-41
 - SOTSW 5-48, 23-41
 - TIMESTEP 5-48, 23-41
- diodes 13-5
 - CTA 13-22
 - CTC 13-22
 - CTP 13-22
 - EG 13-23
 - GAP1 13-23
 - GAP2 13-23
 - junction 13-14, 13-15
 - AREA 13-16
 - BV 13-18
- capacitance
 - CJ 13-19
 - CJA 13-19
 - CJO 13-19
 - CJP 13-19
 - CJSW 13-19
 - EXA 13-19
 - EXP 13-19
 - FC 13-19
 - FCS 13-19
 - M 13-19
 - MJ 13-19
 - MJSW 13-19
 - PB 13-19
 - PHA 13-19
 - PHI 13-19
 - PHP 13-20
 - TT 13-20
 - VJ 13-19
- D 13-14, 13-17
- diode type 13-14
- EXPLI 13-16
- IB 13-16
- IBV 13-16
- IK 13-16
- IKF 13-16
- IKR 13-16
- IS 13-17
- ISP 13-17
- JBF 13-16
- JBR 13-16
- JS 13-17
- JSW 13-17
- LEVEL 13-14, 13-17
- model names 13-14
- N 13-17

- PJ 13-17
- RS 13-18
- SHRINK 13-18
- VAR 13-18
- VB 13-18
- VRB 13-18
- XW 13-18
- level 13-3
- noise
 - AF 13-21
 - KF 13-21
- scaling 13-9
- TCV 13-23
- TLEV 13-23
- TLEVC 13-23
- TM1 13-23
- TM2 13-23
- TPB 13-23
- TPHP 13-23
- TREF 13-23
- TRS 13-24
- TTT1 13-24
- TTT2 13-24
- TVJ 13-23
- XTI 13-24
- DTEMP 10-61
- Fowler-Nordheim diodes
 - D 13-37
 - EF 13-37
 - ER 13-37
 - JF 13-37
 - JR 13-37
 - TOX 13-37
 - W 13-37
 - XW 13-37
- FREQ 4-56
- geometric 12-5
- geometry, JFET and MESFET 15-9
- IKF 14-2
- IKR 14-2
- JFET
 - A 15-25
 - ACM 15-18, 15-26
 - AF 15-39
 - ALIGN 15-18
 - ALPHA 15-25
 - AREA 15-18
 - BETA 15-23, 15-25
 - BETATCE 15-43, 15-52
 - BEX 15-43
 - CALPHA 15-20, 15-33
 - capacitance 15-33
 - CAPDS 15-20, 15-52
 - CAPOP 15-20
 - CGAMDS 15-21, 15-33
 - CGD 15-21
 - CGS 15-21
 - CRAT 15-21
 - CTD 15-43
 - CTS 15-43
 - CVTO 15-21, 15-33
 - D 15-25
 - DC
 - Level 1 15-23
 - Level 2 15-23
 - Level 3 15-25
 - DELTA 15-25, 15-52
 - EG 15-43
 - FC 15-21, 15-33
 - GAMDS 15-25
 - GAMMA 15-25
 - GAP1 15-43

GAP2 15-44
 gate capacitance 15-20
 gate diode DC 15-18
 GCAP 15-21
 GDSNOI 15-39
 HDIF 15-18
 IS 15-18
 K1 15-25
 KF 15-39
 L 15-19
 LAM1 15-23
 LAMBDA 15-23, 15-25
 LDEL 15-19
 LDIF 15-19
 LEVEL 15-23, 15-25
 M 15-21, 15-33, 15-44
 MJ 15-33, 15-44
 N 15-19, 15-44
 NCHAN 15-25
 ND 15-23, 15-25
 NG 15-23, 15-24, 15-25
 NLEV 15-39
 noise 15-39
 PB 15-22
 Q 15-26
 RD 15-19
 RG 15-19
 RS 15-19
 RSH 15-19
 RSHG 15-19
 RSHL 15-19
 SAT 15-26
 SATEXP 15-26
 TCV 15-44
 TDR1 15-44
 temperature 15-43
 TLEV 15-44
 TLEVC 15-44
 TPB 15-44
 TRD 15-44
 TRG 15-44
 TRG1 15-44
 TRS 15-44
 TRS1 15-44
 TT 15-22
 UCRIT 15-26
 VBI 15-26
 VDEL 15-33
 VGEXP 15-26
 VP 15-26
 VTO 15-23, 15-24, 15-26
 VTOTC 15-44
 W 15-20
 WDEL 15-20
 XTI 15-45
 JFET and MESFET 15-17
 DCAP 15-29
 LEVEL 15-16
 level selector 15-3
 NIF 15-16
 PIF 15-16
 See also model parameters, JFET
 LENGTH 10-46
 LEVEL 11-8
 magnetic cores 12-32, 12-35
 A 12-35
 AC 12-32, 12-35
 ALPHA 12-35
 AREA 12-35
 BR 12-32
 BS 12-32
 C 12-35

- HC 12-32
- HCR 12-32
- HS 12-32
- K 12-35
- LC 12-32, 12-35
- LEVEL 12-35
- LG 12-32
- MS 12-35
- PATH 12-35
- TC 12-32
- manufacturing tolerances 10-46
- MESFET
 - noise 15-39
 - See also model parameters, JFET
- metal and poly capacitors
 - LM 13-20
 - LP 13-20
 - WM 13-20
 - WP 13-20
 - XM 13-20
 - XOI 13-20
 - XOM 13-20
 - XP 13-20
- MONO 4-56
- MOSFET's
 - LEVEL 16-28
 - NMOS 16-28
 - PMOS 16-28
- op-amps 23-84
 - AV 23-84
 - AV1K 23-84
 - AVD 23-84
 - BW 23-86
 - C2 23-85
 - CMRR 23-85
 - COMP 23-83, 23-85
 - DEF 23-85
 - default values 23-89
 - DELPHS 23-86
 - DIS 23-86
 - FREQ 23-86
 - GBW 23-86
 - IB 23-86
 - IBOS 23-86
 - ISC 23-87
 - JIS 23-87
 - LEVIN 23-87
 - LEVOUT 23-87
 - MANU 23-87
 - PS 23-87
 - PWR 23-87
 - RAC 23-87
 - ROAC 23-87
 - ROUT 23-88
 - SRN 23-88
 - SRNEG 23-88
 - SRP 23-88
 - SRPOS 23-88
 - TEMP 23-88
 - VCC 23-88
 - VEE 23-88
 - VON 23-88
 - VONEG 23-88
 - VOP 23-89
 - VOPOS 23-89
 - VOS 23-89
- PHOTO 10-46
- resistance 12-5
- RSH 10-34
- saturable cores 12-5
- skew 10-33
- SUBS 14-2

- suppressing printout of 3-52
- TEMP 3-43, 10-61
- temperature 12-5
- TIC 4-56
- TOM model 15-50, 15-52
- TOX 10-34
- transmission lines
 - geometric
 - coax models 22-28
 - models 22-26
 - twinlead models 22-30
 - loss parameters 22-19
 - measured parameters 22-38
 - planar models 22-17
 - precomputed parameters 22-32
- TREF 10-62
- U models
 - AT1 22-38
 - ATLEN 22-38
 - CAPL 22-38
 - CEXT 22-17, 22-26, 22-28, 22-30
 - CLEN 22-38
 - CMULT 22-17, 22-26, 22-28, 22-30
 - CORKD 22-17, 22-27
 - D12 22-30
 - DELAY 22-38
 - DELEN 22-38
 - DLEV 22-15, 22-17, 22-26, 22-30
 - ELEV 22-15, 22-17
 - FR1 22-38
 - HGP 22-17, 22-26, 22-28, 22-30
 - HT 22-17, 22-26
 - HT1 22-26
 - KD 22-17, 22-26, 22-28, 22-30
 - KD1 22-26
 - KD2 22-27
 - LEVEL 22-15, 22-17
 - LLEV 22-15, 22-17
 - MAXD 22-17
 - measured parameters 22-37
 - ND 22-17
 - NL 22-26
 - NLAY 22-19, 22-26
 - OD1 22-31
 - PLEV 22-15, 22-17, 22-38
 - RA 22-28
 - RA1 22-30
 - RB 22-28
 - RD 22-28
 - RHO 22-19, 22-26, 22-28, 22-30
 - RHOB 22-19, 22-26, 22-28, 22-31
 - SHTHK 22-28, 22-31
 - SIG 22-19, 22-26, 22-28, 22-30
 - SIG1 22-26
 - SP 22-17, 22-26
 - SP12 22-26
 - TH 22-17, 22-26
 - TH1 22-26
 - THB 22-17, 22-26
 - THK1 22-26
 - THK2 22-26
 - TS 22-17, 22-26
 - TS1 22-30
 - TS2 22-31
 - TS3 22-31
 - VREL 22-38
 - WD 22-17, 22-26
 - WD1 22-26

- WLUMP 22-17
- XW 22-17, 22-26
- ZK 22-38
- wire models 12-5
 - BULK 12-12
 - CAP 12-12
 - CAPSW 12-12
 - COX 12-12
 - CRATIO 12-10
 - DI 12-12
 - DLR 12-12
 - DW 12-12
 - L 12-12
 - LEVEL 12-12
 - R 12-9
 - RAC 12-12
 - RES 12-12
 - RSH 12-12
 - SHRINK 12-12
 - table 12-12
 - TC1C 12-12
 - TC1R 12-12
 - TC2C 12-12
 - TC2R 12-12
 - THICK 12-12
 - TREF 12-12
 - W 12-13
- XGRID 4-56
- XL 10-34
- XMAX 4-56
- XMIN 4-56
- XPHOTO 10-47
- XSCAL 4-56
- XW 10-34
- YGRID 4-56
- YMAX 4-57
- YMIN 4-57
- YSCAL 4-57
- model parameters, MESFET
- model selection
 - automatic 19-1–19-4
 - failure to find a model 19-3
 - program 16-7, 19-3
 - See also automatic model selection
- .MODEL statement 12-4, 16-3
 - BISECTION syntax 28-7
 - BJT 14-16
 - capacitance 12-18
 - digital model 23-40
 - diode junction 13-14
 - ferromagnetic cores 12-35
 - HSPICE version parameter 3-66
 - JFET and MESFET 15-16
 - magnetic core 12-31
 - MOSFET 16-28
 - op-amp 23-83
 - OPT method 28-7
 - optimization syntax 11-7
 - PASSFAIL syntax 28-7
 - U model 22-15
 - wire RC 12-9
- models
 - algebraic 7-20
 - area calculation method selector 15-3
 - automatic selection 16-7
 - BJT's 3-65, 3-66
 - BSIM Level 13 3-66
 - BSIM2 Level 39 3-66
 - bulk charge effect 16-2
 - capacitance 12-18, 16-6

- capacitors 3-65
 - capacitors, model selector 15-3
 - characterization 8-3
 - Curtice 15-3
 - depletion MOS devices 16-2
 - digital 23-40
 - diodes 3-65, 13-3
 - junctions 13-14
 - Ebers-Moll 14-1
 - ferromagnetic cores 12-33
 - Gummel-Poon 14-1
 - ion-implanted devices 16-2
 - JFET and MESFET
 - capacitor 15-5
 - DC models 15-1
 - JFET's 3-65
 - magnetic core 3-65, 12-31
 - MOSFET's 3-65
 - levels 16-2, 16-3
 - mutual inductors 3-65
 - names 12-4, 12-7
 - op-amps 3-65
 - creating 23-82
 - optimization 3-65
 - parameters 12-4
 - DTEMP 26
 - LV18 15
 - LX7, LX8, LX9 15
 - scaling 16-10
 - plot 3-65
 - private 3-67
 - protecting 3-67
 - references 12-2
 - resistors 3-66
 - scaling 16-11
 - selecting 15-3
 - silicon-on-sapphire 16-2
 - simulator access 3-64
 - SOSFET 16-2
 - specifying 3-57
 - Statz 15-2, 15-3
 - TOM 15-2
 - TriQuint 15-2
 - types 12-4
 - typical set 10-37–10-38
 - wire RC 12-9
- MONO model parameter 4-56
 - Monte Carlo
 - AC analysis 9-4
 - analysis 10-3, 10-51–10-59
 - demo files 35
 - distribution options 10-41–10-42
 - functions 10-16
 - DC analysis 8-4
 - time analysis 7-4
 - MONTE keyword 7-5, 9-5, 10-39
 - MOS2 model 16-3
 - MOS3 model 16-3
 - MOSFET's
 - BEX factor 17-129
 - bulk transconductance 16-19
 - capacitance
 - equations 16-77–16-103
 - Meyer model 16-59
 - models 16-59
 - scaling parameters 16-72
 - CAPOP capacitance selector 16-77–16-103
 - channel
 - length 16-12
 - modulation temperature

- equations 16-116
 - width 16-13
- charge
 - conservation model parameters 16-74
 - storage modeling 16-59
- conductance 16-18
- construction 16-25
- control options (list) 16-9
- current convention 16-17
- current flow 4-14
- diodes
 - capacitance
 - equations 16-49
 - model parameters 16-30
 - temperature equations 16-111
- DC
 - current equations 16-48
 - model parameters 16-30
 - effective areas 16-35, 16-38, 16-42, 16-46
 - effective drain and source resistance 16-36, 16-39, 16-44, 16-47
 - effective saturation current 16-35, 16-38, 16-43, 16-47
 - GEO element parameter 16-45
 - geometry model parameters 16-33
 - model parameters 16-30
 - ACM 16-30
 - CBD 16-30
 - CBS 16-30
 - CDB 16-31
 - CJ 16-31
 - CJA 16-31
 - CJGATE 16-31
 - CJP 16-31
 - CJSW 16-31
 - CSB 16-31
 - DLAT 16-33
 - DNB 16-31
 - DW 16-33
 - EXA 16-31
 - EXD 16-31
 - EXJ 16-31
 - EXP 16-31
 - EXS 16-31
 - FC 16-31
 - IS 16-30
 - JS 16-30
 - JSW 16-30
 - LATD 16-33
 - LD 16-33
 - LDIF 16-33
 - LRD 16-32
 - LRS 16-32
 - MJ 16-31
 - MJSW 16-31
 - N 16-30
 - NB 16-31
 - NDS 16-30
 - NSUB 16-31
 - PB 16-31
 - PHA 16-31
 - PHD 16-31
 - PHP 16-31
 - PHS 16-31
 - PRD 16-32
 - PRS 16-32
 - RD 16-32

- RDC 16-32
- RL 16-32
- RS 16-32
- RSC 16-32
- RSH 16-32
- TT 16-31
- VNDS 16-30
- WDEL 16-33
- WMLT 16-33
- WRD 16-32
- WRS 16-32
- XJ 16-33
- XW 16-33
- resistance
 - model parameters 16-32
 - temperature equations 16-116
- suppressing 16-40
- drain
 - diffusion area 16-13
 - resistance due to contact resistance 16-13
- effective output conductance 16-56
- elements
 - names 16-12
 - parameters (list) 16-15
 - statement 16-12
 - variables and constants 16-15
- energy gap temperature equations 16-110
- equation variables and constants 16-16
- equivalent circuits 16-18
- gate
 - capacitance model parameters 16-72
 - overlap capacitance model parameters 16-73
- impact ionization equations 16-19, 16-55
- initial conditions 16-14
- initial voltage values 16-14
- level parameter 16-28
- Levels 6, 7 UPDATE selector 17-59
- Meyer capacitance model parameters 16-74
- mobility temperature equations 16-116
- model names 16-12
- model parameters
 - A 17-142
 - A0 17-225, 17-243
 - A1 17-84, 17-86, 17-95, 17-225, 17-244
 - A1R 17-261
 - A2 17-84, 17-225, 17-244
 - A2R 17-262
 - A3R 17-262
 - ACM 17-188
 - AF 16-104
 - AFC 17-37, 17-173
 - AGS 17-244
 - AI0 17-185
 - AIB 17-185
 - ALPHA 16-55, 17-142, 17-190
 - ALPHA0 17-245
 - ALPR 17-260
 - AT 17-224, 17-248
 - B0 17-244
 - B1 17-151, 17-244
 - B2 17-151
 - BET 17-2, 17-8, 17-20

BETA 17-2, 17-8, 17-20
 BETA0 17-245
 BetaGam 17-170
 BETSQ 17-259
 BEX 16-107, 17-111, 17-158,
 17-173, 17-190
 BFRC 17-172
 BIO 17-186
 BIB 17-186
 BULKMOD 17-226
 C1 16-73
 C2 16-73
 CAPOP 16-72, 17-37, 17-142,
 17-173, 17-188
 CAV 17-93
 CDSC 17-225, 17-244
 CDSCB 17-225, 17-244
 CDSCD 17-244
 CF1 16-74
 CF2 16-74
 CF3 16-74
 CF4 16-74
 CF5 16-74
 CF6 16-74
 CGB 16-73
 CGBEX 16-74
 CGBO 16-73, 17-105, 17-152,
 17-187
 CGBOM 17-105
 CGD 16-73
 CGDO 16-73, 17-105, 17-141,
 17-142, 17-152, 17-186,
 17-212
 CGDOM 17-105
 CGS 16-73
 CGSO 16-73, 17-105, 17-141,
 17-142, 17-152, 17-187,
 17-212
 CGSOM 17-105
 CHI 17-211
 CIT 17-225, 17-244
 CJ 17-109, 17-187
 CJM 17-109
 CJSW 17-109, 17-187
 CJW 17-109
 CLM 17-54, 17-95
 CO 16-72
 COL 17-262
 COX 16-72, 17-2, 17-8, 17-20,
 17-91
 CSC 17-212
 CTA 16-107
 CTP 16-107
 DEFF 17-211
 DEL 17-3, 17-9, 17-21, 17-36,
 17-56, 17-92, 17-169
 DELL 17-186
 DELTA 17-10, 17-22, 17-93, 17-
 245
 DELVTO 16-52, 17-189
 DERIV 17-20, 17-188
 DFS 17-4, 17-10, 17-23, 17-57,
 17-93, 17-94
 DIBL 17-171
 DL 17-4, 17-10, 17-22, 17-57,
 17-93, 17-111, 17-157,
 17-184, 17-223
 DL0 17-105
 DLAT 16-73, 17-3, 17-9, 17-21,
 17-56, 17-92, 17-110,
 17-156
 DLC 17-247

DNB 16-52, 17-4, 17-11, 17-23,
17-35, 17-54, 17-94, 17-
169
DND 17-86
DNF 17-4, 17-11, 17-23, 17-94
DNS 17-54
DP 17-35, 17-169
DROUT 17-225, 17-245
DS 17-109
DSUB 17-225, 17-243
DUM1 17-105
DUM2 17-105
DVIN 17-171
DVSBC 17-170
DVT0 17-223, 17-243
DVT0W 17-243
DVT1 17-223, 17-243
DVT1W 17-243
DVT2 17-223, 17-243
DVT2W 17-243
DW 17-4, 17-10, 17-22, 17-57,
17-93, 17-111, 17-157,
17-184, 17-223
DW0 17-105
DWB 17-247
DWC 17-247
DWG 17-247
E1 17-211
E2 17-211
EC 17-142
ECRIT 17-8, 17-54, 17-81, 17-
91
ECV 17-35, 17-169
EG 16-107
EM 17-224
ESAT 17-8, 17-54, 17-91
ETA 17-22, 17-93, 17-171, 17-
211, 17-224
ETA0 17-105, 17-152, 17-184,
17-224, 17-243
ETAALP 17-260
ETAB 17-184, 17-224, 17-243
ETABET 17-259
ETADSR 17-260
ETAGAMR 17-261
ETAMN 17-152
ETAMR 17-261
ETAZET 17-261
F1 17-79, 17-80, 17-81
F1EX 16-107, 17-172
F2 17-12, 17-80, 17-81, 17-95
F3 17-79, 17-80, 17-81
F4 17-80
FB 17-142
FDS 17-57
FEFF 17-212
FEX 17-111, 17-158, 17-190
FRC 17-36, 17-171
FRCEX 17-172
FREQ 17-212
FSB 17-36, 17-172
FSS 17-36, 17-170
GAMIR 17-260
GAMMA 16-52, 16-53, 17-4,
17-10, 17-22, 17-54, 17-
93
GAMMA1 17-222, 17-249
GAMMA2 17-222, 17-249
GAMMN 17-152
GAMOOR 17-261
GAP1 16-108
GAP2 16-108

GDS 17-54
 GDSNOI 16-104
 GO 17-211
 HEX 17-173
 IIRAT 16-55, 17-190
 IJS 17-109
 impact ionization 16-55
 JS 17-109, 17-187
 JSW 17-109
 K1 17-105, 17-152, 17-184, 17-222, 17-242
 K2 17-106, 17-152, 17-184, 17-212, 17-222, 17-242
 K3 17-222, 17-242
 K3B 17-222, 17-242
 KA 17-58, 17-85
 KAPPA 17-20
 KBeta1 17-173
 KCL 17-85
 KCS 17-169
 KETA 17-225, 17-244
 KF 16-104
 KIO 17-173
 KIO 17-173
 KL 17-84, 17-87
 KOR 17-258
 KP 17-2, 17-8, 17-20
 KR 17-259
 KT1 17-222, 17-248
 KT1L 17-226
 KT2 17-222, 17-248
 KU 17-59, 17-85
 LA 17-2, 17-8, 17-84, 17-85, 17-95
 LALPHA 16-55
 LAM 17-2, 17-8, 17-84, 17-85, 17-95
 LAM1 17-87, 17-95
 LAMBDA 17-2, 17-8, 17-84, 17-85, 17-86, 17-87, 17-95
 LAMEX 16-108
 LAP 17-258
 LATD 16-73, 17-3, 17-9, 17-21, 17-36, 17-56, 17-92, 17-110, 17-156, 17-169
 LB1 17-151
 LB2 17-152
 LBetaGam 17-170
 LBFRC 17-172
 LD 16-73, 17-3, 17-9, 17-21, 17-36, 17-56, 17-92, 17-110, 17-141, 17-142, 17-156, 17-169, 17-188
 LDAC 17-3, 17-9, 17-21, 17-92, 17-110, 17-156, 17-169, 17-189
 LDAC parameter 17-56
 LDD 17-224
 LDEL 17-4, 17-10, 17-22, 17-57, 17-93, 17-111, 17-157
 LDVSBC 17-170
 LER 17-258
 LETA 17-105, 17-152, 17-171
 LETAMN 17-152
 LEVEL 17-2, 17-8, 17-20, 17-35, 17-53, 17-91, 17-105, 17-142, 17-151, 17-169
 LFRC 17-171
 LFSB 17-172
 LGAMMA 17-54

LGAMN 17-152
LINT 17-247
LITL 17-224
LK1 17-106, 17-152
LK2 17-106, 17-152
LKBeta1 17-173
LKIO 17-173
LKIO 17-173
LL 17-247
LLN 17-247
LMAX 17-248
LMIN 17-248
LMLT 17-3, 17-9, 17-21, 17-36,
17-56, 17-92, 17-110,
17-156, 17-170, 17-188
LMS 17-106
LMUS 17-106
LMUZ 17-106, 17-153
LNO 17-10, 17-22, 17-57, 17-94,
17-106, 17-153
LNB 17-106, 17-153
LND 17-10, 17-22, 17-57, 17-
93, 17-107, 17-153
LPHI 17-107, 17-153
LREF 17-9, 17-10, 17-21, 17-56,
17-92, 17-110, 17-156,
17-189
LU0 17-107, 17-153
LU1 17-107, 17-154
LUB 17-172
LUO 17-172
LVAR 17-258
LVCR 16-55
LVFB 17-107, 17-154
LVFRC 17-171
LVT 17-170
LVTO 17-170
LW 17-247
LWFAC 17-154
LWFACU 17-154
LWL 17-247
LWN 17-247
LX2E 17-107, 17-154
LX2M 17-107, 17-154
LX2MS 17-108
LX2MZ 17-107, 17-154
LX2U0 17-108, 17-155
LX2U1 17-108, 17-155
LX33M 17-155
LX3E 17-108, 17-155
LX3MS 17-108, 17-155
LX3U1 17-108, 17-155
MAL 17-59, 17-85
MBL 17-59
MCL 17-85
METO 16-73, 17-37, 17-173
MJ 16-108, 17-109, 17-187
MJ0 17-109
MJSW 16-108, 17-109, 17-187
MJW 17-109
MOB 17-11, 17-54, 17-81, 17-94
MOBMOD 17-241
MOR 17-261
MU0 17-184
MU0B 17-184
MU20 17-184
MU2B 17-184
MU2G 17-184
MU30 17-184
MU3B 17-185
MU3G 17-185
MU40 17-185

MU4B 17-185
MU4G 17-185
MUS 17-106
MUS0 17-184
MUSB 17-184
MUZ 17-106, 17-152
N 16-108
N0 17-10, 17-22, 17-57, 17-94,
17-106, 17-153, 17-185
NB 16-52, 17-4, 17-11, 17-23,
17-94, 17-185
NB0 17-106, 17-153
NCH 17-242
ND 17-10, 17-22, 17-57, 17-94,
17-185
ND0 17-106, 17-153
NEFF 17-9
NF 17-4, 17-10, 17-23, 17-57,
17-94
NFACTOR 17-224, 17-244
NFR 17-262
NFS 17-4, 17-10, 17-23, 17-36,
17-57, 17-93, 17-94, 17-
170, 17-211
NGATE 16-52, 17-242
NI 17-35, 17-54, 17-169
NLEV 16-104
NLX 17-222, 17-242
NPEAK 17-223
NSS 16-52, 17-211
NSUB 16-52, 17-4, 17-11, 17-
23, 17-35, 17-54, 17-94,
17-169, 17-223, 17-242
NTR 17-262
NU 17-59, 17-211
NWE 17-58
NWM 17-36, 17-54, 17-170
OXETCH 17-36, 17-170
PB 17-109, 17-187
PBSW 17-187
PCLM 17-225, 17-244
PDIBL1 17-225
PDIBL2 17-225
PDIBLC1 17-245
PDIBLC2 17-245
PDIBLCB 17-245
PHI 16-52, 16-53, 17-4, 17-11,
17-23, 17-35, 17-94, 17-
169, 17-184, 17-211, 17-
223
PHI0 17-107, 17-153
PHIBR 17-259
PHP 17-109
PJ 17-109
PJW 17-109
PRWB 17-244
PRWG 17-244
PSCBE1 17-225, 17-245
PSCBE2 17-225, 17-245
PSI 17-211
PTA 16-108
PTC 16-108
PTP 16-108
PVAG 17-226, 17-245
RD 17-212
RDS0 17-224
RDSW 17-224, 17-244
RS 17-212
RSH 17-109, 17-141, 17-142,
17-187, 17-245
RSHM 17-109
SATMOD 17-225

SCM 17-36, 17-54, 17-170
 SL2VTO 17-258
 SLA1 17-261
 SLA2 17-262
 SLA3 17-262
 SLALP 17-260
 SLGAM1 17-260
 SLGAMOO 17-261
 SLK 17-259
 SLKO 17-259
 SLMO 17-261
 SLTHE1 17-259
 SLTHE1R 17-259
 SLTHE2R 17-260
 SLTHE3R 17-260
 SLVSBT 17-261
 SLVSBX 17-259
 SLVTO 17-258
 SLZET1 17-261
 SNVB 17-91
 SOSLEV 17-141, 17-143
 SPICE3 17-188
 STA1 17-261
 STLTHE2 17-260
 STLTHE3 17-260
 STMO 17-261
 STTHE1R 17-259
 STTHE2R 17-259
 STTHE3R 17-260
 STVTO 17-258
 SUBTHMOD 17-225
 SWA1 17-261
 SWA2 17-262
 SWA3 17-262
 SWALP 17-260
 SWGAM1 17-260
 SWK 17-259
 SWKO 17-259
 SWTHE1 17-259
 SWTHE2 17-260
 SWTHE3 17-260
 SWVSBX 17-259
 SWVTO 17-258
 T1 17-211
 T2 17-211
 TAU 17-212
 TCV 16-108, 17-111, 17-158,
 17-190
 TDVSBC 17-170
 TEMP 17-183
 THE1R 17-259
 THE2R 17-259
 THE3R 17-260
 THETA 17-11, 17-23, 17-143,
 17-211
 TLEV 16-109
 TLEVC 16-109
 TNOM 17-225
 TOX 16-72, 17-2, 17-9, 17-20,
 17-35, 17-91, 17-107,
 17-141, 17-143, 17-153,
 17-169, 17-183, 17-223,
 17-242, 17-262
 TOXM 17-107, 17-153
 TPG 16-52
 TPS 16-52
 TR 17-258
 TRD 16-109
 TREF 17-107, 17-111, 17-212,
 17-225
 TRS 16-109
 TUH 17-35, 17-173

U0 17-223
 U00 17-107, 17-153
 U1 17-107, 17-153
 U10 17-185
 U1B 17-185
 UID 17-185
 UA 17-224, 17-243
 UA0 17-185
 UA1 17-224, 17-248
 UAB 17-185
 UB 17-12, 17-23, 17-37, 17-54,
 17-95, 17-172, 17-224,
 17-243
 UB0 17-185
 UB1 17-224, 17-248
 UBB 17-185
 UBO 17-12, 17-23, 17-54, 17-95
 UC 17-224, 17-243
 UC0 17-226
 UC1 17-224, 17-248
 UCRIT 17-12, 17-94
 UEXP 17-12, 17-80, 17-81, 17-
 95
 UFDS 17-58
 UH 17-37, 17-173
 UHSAT 17-173
 UO 17-2, 17-12, 17-23, 17-37,
 17-54, 17-95, 17-142,
 17-143, 17-172, 17-211,
 17-243
 UPDATE 17-55
 UTE 17-225, 17-248
 UTRA 17-12, 17-79, 17-80, 17-
 81, 17-95
 VB 17-55
 VB0 17-55
 VBB 17-183
 VBI 17-249
 VBM 17-223, 17-243
 VBX 17-223, 17-249
 VCR 16-55, 17-190
 VDD 17-183
 VDDM 17-107, 17-154
 VF1 17-80
 VFB 17-107, 17-154, 17-184,
 17-226
 VFB0 17-107, 17-154
 VFDS 17-58
 VFRC 17-171
 VGG 17-183
 VGHIGH 17-184, 17-225
 VGLAM 17-86, 17-87
 VGLOW 17-184, 17-224
 VMAX 17-9, 17-20, 17-55, 17-
 80, 17-91, 17-211
 VMX 17-9, 17-20, 17-55, 17-80,
 17-91
 VOF0 17-185
 VOFB 17-185
 VOFD 17-185
 VOFF 17-224, 17-244
 VPR 17-261
 VSAT 17-9, 17-91, 17-224, 17-
 244
 VSBTR 17-261
 VSBXR 17-259
 VSH 17-58
 VST 17-37, 17-173
 VT 16-52, 17-4, 17-11, 17-23,
 17-36, 17-58, 17-94, 17-
 170
 VTH0 17-242

VTHO 17-222, 17-242
VTIME 17-212
VTO 16-52, 16-53, 17-4, 17-11,
17-23, 17-36, 17-58, 17-
94, 17-142, 17-143, 17-
170, 17-211
VTOR 17-258
W0 17-222, 17-242
WALPHA 16-55
WB1 17-151
WB2 17-152
WBetaGam 17-170
WBFRC 17-172
WD 16-73, 17-3, 17-9, 17-21,
17-56, 17-92, 17-110,
17-157, 17-189
WDAC 17-3, 17-10, 17-21, 17-
57, 17-92, 17-110, 17-
157, 17-189
WDEL 17-4, 17-10, 17-22, 17-
36, 17-57, 17-93, 17-111,
17-157, 17-169
WDF 17-109, 17-186
WDVSBC 17-170
WER 17-258
WETA 17-105, 17-152, 17-171
WETAMN 17-152
WEX 17-58
WFAC 17-154
WFACU 17-154
WFRC 17-171
WFSB 17-172
WGAMN 17-152
WIC 17-11, 17-23, 17-58, 17-94
WINT 17-247
WK1 17-106, 17-152
WK2 17-106, 17-152
WKBeta1 17-173
WKIO 17-173
WKIO 17-173
WLN 17-247
WMAX 17-248
WMIN 17-248
WMLT 17-3, 17-10, 17-21, 17-
36, 17-57, 17-92, 17-110,
17-157, 17-170, 17-189
WMS 17-106
WMUS 17-106
WMUZ 17-106, 17-153
WN0 17-11, 17-23, 17-58, 17-
94, 17-106, 17-153
WNB 17-106, 17-153
WND 17-11, 17-23, 17-58, 17-
94, 17-107, 17-153
WOT 17-258
WPHI 17-107, 17-153
WR 17-244
WREF 17-10, 17-22, 17-57, 17-
93, 17-111, 17-157, 17-
189
WS2MZ 17-108
WU0 17-107, 17-153
WU1 17-107, 17-154
WUB 17-172
WUO 17-172
WVAR 17-258
WVCR 16-55
WVFB 17-107, 17-154
WVFRC 17-172
WVT 17-170
WVTO 17-170
WW 17-247

WWFAC 17-154
WWFACU 17-154
WWL 17-247
WWN 17-247
WX2E 17-107, 17-154
WX2M 17-108, 17-154
WX2MS 17-108
WX2MZ 17-154
WX2U0 17-108, 17-155
WX2U1 17-108, 17-155
WX33M 17-155
WX3E 17-108, 17-155
WX3MS 17-108, 17-155
WX3U1 17-108, 17-155
X2E 17-107, 17-154
X2M 17-107, 17-154
X2M2 17-107
X2MS 17-108
X2MZ 17-154
X2U0 17-108, 17-154
X2U1 17-108, 17-155
X33M 17-155
X3E 17-108, 17-155
X3MS 17-108, 17-155
X3U1 17-108, 17-155
XJ 17-4, 17-10, 17-22, 17-36,
17-57, 17-93, 17-171,
17-223, 17-242
XL 17-4, 17-10, 17-22, 17-57,
17-93, 17-111, 17-157,
17-188
XLREF 17-157, 17-189
XPART 17-109, 17-155, 17-226
XQC 16-74
XT 17-223, 17-249
XTI 16-109
XW 17-4, 17-10, 17-22, 17-57,
17-93, 17-111, 17-157,
17-189
XWREF 17-157, 17-189
ZENH 17-35
ZET1R 17-261

models

- AMD 16-4, 16-5
- ASPEC-AMI 16-4
- BSIM 16-4
- BSIM2 16-5
- BSIM3 16-5
- CASMOS 16-4
- CASMOS GEC 16-4
- CASMOS Rutherford 16-4
- Cypress 16-4
- Dallas Semiconductor 16-4
- Fluke-Mosaid 16-4
- GE-CRD-Franz 16-4
- GE-Intersil 16-4
- Grove-Frohman 16-3
- HSPICE PC version 16-3
- IDS Cypress depletion 16-5
- Lattin-Jenkins-Grove 16-4
- MOS2 16-3
- MOS3 16-3
- Motorola 16-5
- National Semiconductor 16-5
- Schichman-Hodges 16-3
- SGS-Thomson 16-5
- Sharp 16-5
- Siemens 16-4, 16-5
- Sierra 1 16-4
- Sierra 2 16-4
- Siliconix 16-4
- SOSFET 16-5

- STC-ITT 16-4
- Taylor-Huang 16-4
- TI 16-5
- user defined 16-4
- VTI 16-5
- multiply parameter 16-14
- n-channel specification 16-28
- node names 16-12
- noise 16-104
 - model equations 16-104
 - model parameters 16-104
 - summary printout 16-106
- p-channel specification 16-28
- perimeter
 - drain junction 16-13
 - source junction 16-13
- power dissipation 4-18
- saturation current temperature
 - equations 16-111
- sensitivity factors 17-158
- source
 - diffusion area 16-13
 - resistance due to contact resistance 16-14
- source/drain sharing selector 16-14
- SPICE compatibility 16-3
- squares per drain diffusion 16-13
- squares per source diffusion 16-13
- surface potential temperature
 - equations 16-114
- temperature
 - coefficient model parameters 16-110
 - differential 16-14
 - parameters 16-107
- threshold voltage
 - model parameters 16-52
 - temperature equations 16-115
- transconductance 16-18
- UPDATE parameter usage 17-130
- voltages, initial 16-14
- WIC ids current selector 17-76
- zero bias threshold voltage shift 16-14
- Motorola model 16-5
- MS model parameter 12-34
- .ms# file 4-2, 4-4
- MSPICE simulator interface 3-51
- .mt# file 4-2, 4-4
- MU option 7-12, 7-14
- Muller algorithm 25-3
 - starting points 8-12
- multiple .ALTER statements 10-31
- multiplier
 - function, U and T elements 22-5
 - G and E element values 27-10
 - GSCAL 8-11
- multiply parameter 5-3, 10-27, 12-7, 12-17, 12-24, 13-7, 23-7
- subcircuits 23-11
- multipoint experiment 3-3
- mutual
 - core elements 12-30
 - coupling element parameters 12-4
 - inductance 22-105
 - inductors
 - coupling coefficient 12-27
 - element parameters 12-3

N

- narrow width effect 17-14
- National Semiconductor model 16-5
- natural frequency 25-2
- natural log function 10-6
- n-channel
 - JFET models 3-65
 - MOSFET models 3-65
- ND model parameter 22-17
- NDIM 5-20
- negative conductance, logging 3-49
- nested library calls 3-63
- .NET statement 9-19
- netlists 3-29
 - encrypting 29-1
 - flat 3-29
- networks
 - analysis 9-19
 - filenames 3-43
 - output 9-20
- NEWTOL option 6-18
- NL
 - element parameter 22-11
 - model parameter 22-26
- NLAY model parameter 22-19, 22-26
- NODE option 3-51
 - suppressing listing 3-67
- nodes
 - connection requirements 3-31
 - cross-reference table 3-51
 - floating supply 3-31
 - global versus local 3-25
 - internal 3-31
 - MOSFET substrate 3-31
 - names 3-29, 3-31, 3-33, 23-6, 15
 - ground node 3-31
 - period in 3-30
 - subcircuits 3-30, 3-31
 - zeros in 3-33
 - numbers 3-29, 3-31
 - phase or magnitude difference 9-9
 - printing 3-51
 - shorted 6-33
 - terminators 3-31
 - voltages, encrypting 29-1
- NODESET keyword 6-11
- .NODESET statement 6-3, 6-15, 25-3
 - balancing input nodes 23-83
 - DC operating point initialization 6-7
 - from .SAVE 6-11
- node-to-element list 6-19
- NOELCK option 3-52
- noise
 - calculations 9-17
 - coupled line noise 20-26
 - equations
 - BJT 14-45
 - JFET and MESFET 15-39
 - folding 9-18
 - input 4-15
 - JFET and MESFET
 - equations 15-39
 - summary printout 15-41
 - MOSFET 16-104
 - numerical 7-8
 - output 4-15, 9-17
 - parameters
 - BJT 14-26

- JFET and MESFET 15-39
 - problems and solutions 20-3
 - quota 20-6, 20-8
 - resistor 12-8
 - sampling 9-18
 - sources 20-3, 20-5
 - thermal 12-8
 - .NOISE statement 9-16
 - NOMOD option 3-52
 - NONE keyword 6-9, 6-12
 - nonlinear
 - capacitor element parameters 12-3
 - elements 12-3, 27-2
 - inductor element parameters 12-3
 - NOPAGE option 3-52
 - NOPIV option 6-18
 - NORM FFT analysis keyword 26-6
 - norm of the gradient 11-19
 - NOTOP option 3-52
 - NOWARN option 3-52
 - NP .FFT parameter 26-6
 - NPDELAY element parameter 23-22, 23-28, 23-32, 23-37
 - npn BJT models 3-65
 - NPWL
 - element parameter 23-22
 - function 5-26, 23-20
 - NMOS transistor function 23-17
 - numbers
 - formatting 3-49, 3-50
 - maximum size 3-49
 - minimum size 3-49
 - NUMDGT option 3-52
 - numerical integration
 - algorithms 7-10
 - order of 7-10
 - numerical noise 7-8
 - problems 6-16, 7-9
 - NUMF keyword 9-18
 - NXX option 3-52
 - Nyquist critical frequency 27-5, 27-10
- O**
- O.C.G. matrix 22-35
 - obtaining customer support vi
 - OCT keyword 7-6, 8-5, 9-5
 - OD1 model parameter 22-31
 - odelay (digital vector file) 5-68
 - OFF
 - element parameter 6-4, 6-18
 - option 6-4, 6-18
 - ONoise parameter 4-15
 - .OP statement 6-5, 7-3, 8-8
 - OPAMP element parameter 23-32
 - op-amps
 - .MODEL statement 23-83
 - automatic generation 23-5
 - behavioral models 23-82
 - characterization 20-7
 - common mode rejection ratio 23-85
 - compensation level selector 23-85
 - diode and BJT saturation current 23-86
 - element statement 23-83
 - excess phase parameter 23-86
 - gain parameter 23-84

- input
 - bias current 23-86
 - bias offset current 23-86
 - level type selector 23-87
 - offset current 23-86
 - offset voltage 23-89
 - short circuit current 23-87
- internal feedback compensation
 - capacitance 23-85
- JFET saturation current 23-87
- mA741 model 23-93
- manufacturer's name 23-87
- model
 - generator 23-82
 - parameter defaults 23-89
 - parameters 23-84
 - selector 23-85
- models 3-65
- open loops 6-32
- output
 - level type selector 23-87
 - resistance ROAC 23-87
 - slew rate 23-88
 - voltage 23-88, 23-89
- phase margin 23-86
- power
 - dissipation 23-87
 - supply voltage 23-88
- subcircuit generator 23-5
- temperature parameter 23-88
- unity gain frequency 23-86
- operating point
 - capacitance values table 6-14
 - estimate 6-5, 7-3
 - .IC statement initialization 6-6
 - initial conditions 3-16
 - .NODESET statement initialization 6-7
 - pole/zero analysis 25-3
 - restoring 6-13
 - saving 3-33, 6-11
 - solution 6-3, 6-4, 6-18
 - transient 7-3
 - voltage table 6-9
- operating point capacitor voltage 12-18
- operators, arithmetic 10-6
- operators, Laplace transforms 27-19
- OPT keyword 11-4, 28-7
- optimization
 - AC analysis 9-4, 11-27
 - algorithm 11-8
 - analysis statements 11-5
 - behavioral models 23-63, 23-67
 - bisection method 28-7
 - convergence options 11-2
 - curve-fit 11-3
 - cv 41
 - data output specification 3-52
 - data-driven vs. s-parameters 11-27
 - DC analysis 8-4, 11-12, 11-14, 11-30, 11-34
 - Device Model Builder 11-3
 - error function 4-21
 - example 32
 - goal 11-3
 - incremental 11-30
 - iterations 11-8
 - lengths and widths 11-37
 - MODEL keyword 11-5
 - .MODEL statement 11-7
 - models 3-65

- MOS level 13 11-14
- network 11-27
- of parameters
 - magnitude and phase 11-27
 - measured vs. calculated 11-27
- .PARAM statement 11-6
- parameters 11-27
 - CENDIF 11-7
 - CLOSE 11-7
 - CUT 11-8
 - DIFSIZ 11-8
 - GRAD 11-8
 - ITROPT 11-8
 - MAX 11-8
 - PARMIN 11-8
 - RELIN 11-9
 - RELOUT 11-9
- results
 - Marquadt scaling parameter 11-20
 - norm of the gradient 11-19
 - number of function evaluations 11-20
 - number of iterations 11-20
 - residual sum of squares 11-19
 - simultaneous 11-22, 11-34, 11-37
 - s-parameters 11-27
 - statements 11-4
 - time analysis 7-5
 - time required 11-2, 11-7
- OPTIMIZE function 23-3
- OPTIMIZE keyword 8-4, 11-4
- .OPTION statement, .ALTER blocks 10-31
- options
 - AUTOSTOP 23-91
 - DI 6-26, 7-12, 9-7
 - EPSMIN 27-17
 - OPTLST 28-8
 - OPTLST option 3-52, 28-8
 - printing bisection results 28-8
 - OPTS option 3-52
 - OPTxxx parameter 11-3, 11-4
 - Opus 3-48
 - oscillation, eliminating 7-10
 - oscillators
 - behavioral models 23-82
 - DELMAX option setting 7-19
 - LC 23-100
 - VCO 23-98
 - out (digital vector file) 5-71
 - outer sweep 3-41
 - output
 - admittance 9-13
 - current 4-10, 4-11
 - graphing 4-54
 - impedance 9-13
 - measfail value 28-8
 - .MEASURE results 4-19
 - noise 9-17
 - plotting 4-52–4-53
 - specifying variables 4-54
 - printing 4-47–4-51
 - printout format 4-49
 - saving 4-54
 - variables
 - AC formats 9-11
 - probing 4-54
 - voltage 4-10

- output data
 - format 3-48, 3-50, 3-54
 - limiting 3-54, 7-9
 - number format 3-49
 - optimization 3-52
 - redirecting 3-13
 - significant digits specification 3-52
 - specifying 3-50, 3-54
 - storing 3-51, 3-53
- output driver example 20
- output files
 - names 3-12, 3-15
 - redirecting 3-15
 - reducing size of 3-54, 3-55
 - version number, specifying 3-12
- output variables
 - function 10-7
 - printing 7-9
 - specifying significant digits for 3-52
- outputs, magnetic cores, LX1 - LX7 12-36
- outz (digital vector file) 5-71
- overlap capacitors 16-76
- overlay dielectric transmission line 22-23

P

- .pa# file 4-3, 4-5
- packed input files 3-17
- Pade approximation 27-37
- PADS-LPE extraction module 20-55, 20-59
- page eject, suppressing 3-52
- PAR keyword 10-5, 10-12

- PAR parameter, example 20-12
- .PARAM statement 10-9–10-18, 23-11
 - in .ALTER blocks 10-30
 - optimization 11-6
- parameters
 - AC sweep 9-4
 - ACM 7-20
 - admittance (Y) 9-8
 - AF 9-17
 - algebraic 10-6
 - expressions 10-4, 10-12
 - CAPOP 7-20
 - cell geometry 10-18
 - constants 10-11
 - data driven analysis 3-37
 - data type 10-10
 - DC sweep 8-3
 - defaults 10-23
 - defining 10-11, 10-20
 - DIM2 4-15
 - DIM3 4-15
 - elements 12-2–12-4
 - encrypting 29-1
 - evaluation order 10-10
 - .FFT statement
 - ALFA 26-7
 - FMAX 26-7
 - FMIN 26-7
 - FORMAT 26-6
 - FREQ 26-7
 - FROM 26-6
 - NP 26-6
 - START 26-6
 - STOP 26-6
 - TO 26-6

- WINDOW 26-7
 - global 3-53
 - HD2 4-15
 - HD3 4-15
 - hierarchical 4-34, 10-18
 - hybrid (H) 9-8
 - IC 6-6
 - impedance (Z) 9-8
 - inheritance 10-22, 10-23
 - INOISE 4-15
 - KF 9-17
 - libraries 10-20–10-22
 - local 3-53
 - M 23-7
 - M (multiply) 10-27
 - matrix 9-19
 - measurement 10-17
 - models 12-4
 - modifying 3-37
 - Monte Carlo analysis 10-16
 - names 4-6
 - ONoise 4-15
 - optimization 10-15, 10-18
 - OPTxxx 11-3, 11-4
 - overriding
 - assignments 10-20
 - default values 10-14
 - PAR keyword 10-12
 - PARHIER option 10-23
 - passing 3-53, 10-18–10-26
 - example 20-12
 - problems 10-26
 - Release 95.1 and earlier 10-25
 - repeated 4-34
 - scattering (S) 9-8
 - scope 10-18–??, 10-19, ??–10-26
- See also model parameters, optimization parameters
- SIM2 4-15
- simple 10-11
- simulator access 3-64
- skew, assigning 3-65
- subcircuits 10-13
- time sweep 7-4
- UIC 6-7
- user-defined 10-13
- UTRA 6-31
- See also model parameters
- parasitics
 - capacitance
 - parameters, BJT's 14-25
 - RC wire model 12-10
 - diode, MOSFET Level 39 17-202
 - element parameters 12-3
 - generation 16-40
 - MOSFET Level 13 17-128
 - resistance 12-3
 - parameters, BJT's 14-23
 - temperature equations
 - BJT's 14-60
 - JFET's and MESFET's 15-49
- PARHIER option 3-53, 10-23
- PARMIN optimization parameter 11-8
- parts directory 3-60
- PASSFAIL keyword 28-7
- path names 3-53
 - subcircuits 3-31
- path numbers, printing 3-53
- PATHNUM option 3-53

- p-channel
 - JFET models 3-65
 - MOSFET models 3-65
- PCI
 - demo files 20-36
 - Speedway 20-34
 - timing data extraction macro 20-44
- PD model parameter 23-87
- peak-to-peak value, measuring 4-23
- period (digital vector file) 5-66
- peripheral component interconnect
 - see PCI
- permit.hsp file, encryption capability 29-7
- phase
 - AC voltage 9-10
 - calculating 9-9
- phase detector model 23-105, 23-114
- phase locked loop, BJT model 23-109
- PHOTO model parameter 10-46
- piecewise linear sources
 - data driven 5-15
 - delay time 5-13
 - output values 5-13
 - parameters 5-13
 - repeat parameter 5-13
 - segment time values 5-13
 - simulation time 7-28
 - start point 5-13
 - see PWL
- pin capacitance, plotting 20-6
- pivot
 - algorithm, selecting 6-18
 - matrix calculations 6-18
 - reference 6-20
 - selection 7-17
- pivot change message 6-19
- PIVOT option 6-18, 7-17
- PIVREF option 6-20
- PIVREL option 6-20
- PIVTOL option 6-19, 6-20
- planar conductor parameters 22-23
- PLEV model parameter 22-7, 22-15, 22-17, 22-38
- PLL
 - see phase locked loop
- plot
 - limits 4-52
 - models 3-65
 - value calculation method 9-7
- PLOT keyword 4-56
- .PLOT statement
 - in .ALTER block 3-34
- pn junction conductance 6-40
- pnp BJT models 3-66
- POI keyword 7-6, 8-5, 9-5
- POLE
 - element parameter 27-10
 - function 25-1, 27-2, 27-7, 27-25–27-30
 - transconductance element statement 27-7
 - voltage gain element statement 27-7
- pole/zero
 - analysis 27-2
 - absolute tolerance 25-4

- capacitance scale 25-4
- conductance scale 25-4
- frequency scale 25-4
- imaginary to real ratio 25-5
- inductance scale 25-4
- iteration limit 25-4
- maximum frequency 25-4
- operating point 25-3
- .PZ statement 25-3
- real to imaginary ratio 25-5
- relative error tolerance 25-4
- conjugate pairs 27-8
- control options
 - CSCAL 25-4
 - FMAX 25-4
 - FSCAL 25-4
 - GSCAL 25-4
 - ITLPZ 25-4
 - LSCAL 25-4
 - PZABS 25-4
 - PZTOL 25-4
 - RITOL 25-5
- pole/zero analysis
 - absolute tolerances 8-12
 - frequency, maximum 8-11
 - maximum number of iterations 8-11
 - real/imaginary component ratio 8-12
 - starting points for Muller algorithm 8-12
- poles and zeros, complex 27-27
- POLY 5-20
 - element parameter 23-14, 23-22, 23-28, 23-32, 23-37
- polynomial
 - capacitor coefficients 12-21
 - functions 5-20, 23-14
 - FV function value 23-14
 - inductor coefficients 12-28
- polysilicon 16-25
- POST option 3-4, 3-53
- pow(x,y) function 10-6
- power
 - dissipation 4-15–4-19
 - subcircuits 4-15
 - function 10-6
 - operating point table 6-8
 - stored 4-15
- POWER keyword 4-16
- PP keyword 4-23, 4-24
- PPWL
 - element parameter 23-22
 - function 5-27, 23-20
 - PMOS transistor function 23-17
- precision
 - constants 10-4
 - numbers 10-4
 - parameters 10-4
 - sweep variables 10-4
- print control options 4-49
- .PRINT statement, in .ALTER 3-34
- printed circuit boards
 - analyzing 20-55
 - models 20-2
- printer, device specification 4-54
- printout
 - columns, number 3-48
 - disabling 3-48
 - suppressing 3-67
 - suppressing page ejects 3-52

- value calculation method 9-7
 - PROBE option 3-54
 - .PROTECT statement 29-2
 - protecting data 3-67
 - PRTDEFAULT printer 4-54
 - PSF option 3-54
 - PSRR specification 23-5
 - PULSE source function 5-6
 - delay time 5-7
 - initial value 5-7
 - onset ramp duration 5-7
 - plateau value 5-7
 - recovery ramp duration 5-7
 - repetition period 5-7
 - width 5-7
 - PWL
 - current controlled gates 23-13, 23-14
 - element parameter 23-22, 23-28, 23-32, 23-37
 - functions 23-14, 23-17
 - gates 23-13
 - NMOS and PMOS transistor functions 23-17
 - sources 5-13
 - data driven 5-15
 - voltage controlled
 - capacitors 23-13
 - gates 23-13
 - sources
 - See also piecewise linear sources, data driven PWL source
 - PWR model parameter 23-87
 - pwr(x,y) function 10-6
 - Pxxx 17-190
 - .PZ statement 8-8, 25-3, 27-2
 - PZABS option 8-12, 25-4
 - PZTOL option 8-12, 25-4
- ## Q
- quality assurance 10-2
 - quasi-saturation BJT model 14-47
 - Qxxx BJT element statement 14-4
- ## R
- RA model parameter 22-28
 - RA1 model parameter 22-30
 - RAC model parameter 23-87
 - radix (digital vector file) 5-63
 - random limit parameter distribution 10-39
 - RB model parameter 22-28
 - RC wire model 12-9
 - RD model parameter 22-28
 - real part of AC voltage 9-10
 - real vs. imaginary component ratio 8-12
 - RECT FFT analysis keyword 26-7
 - rectangular FFT window 26-3
 - reference plane, transmission lines 22-5
 - reference temperature 3-43, 10-61
 - regions charge equations, MOSFET Level 13 17-120
 - related documents iii
 - RELH option 6-27, 7-13, 9-7
 - RELI option 6-22, 6-27, 7-13
 - KCLTEST setting 6-17

- RELIN optimization parameter 11-9
 - RELMOS option 6-22, 6-24, 6-27, 7-19
 - KCLTEST setting 6-17
 - RELOUT optimization parameter 11-9
 - RELQ option 7-13, 7-26
 - RELTOL option 7-11, 7-13
 - RELV option 6-22, 6-27, 7-12
 - multiplier for 7-12
 - RELVAR option 7-13, 7-19
 - RELVDC option 6-27
 - repeat function 11
 - residual sum of squares 11-19
 - resistance
 - AC 9-3
 - effective 12-7
 - minimum 6-20
 - model parameters 12-5
 - resistors
 - current flow 4-12
 - elements 12-6
 - names 12-7
 - parameters 12-3
 - equation 12-7
 - length parameter 12-6
 - models 3-66
 - node names 12-7
 - node to bulk capacitance 12-6
 - noise equation 12-8
 - parameter 12-7
 - temperature
 - coefficients 12-7
 - equations 12-9
 - width parameter 12-7
 - wire model parameters 12-12
 - See also wire models
 - RESMIN option 6-20
 - RESULTS keyword 8-4
 - RHO model parameter 22-19, 22-26, 22-28, 22-30
 - RHOB model parameter 22-19, 22-26, 22-28, 22-31
 - RIN keyword 9-19
 - ripple calculation 20-3
 - rise and fall times 4-20
 - RISE keyword 4-22
 - rise time 22-109
 - simulation example 20-10
 - RITOL option 8-12, 25-5
 - RLOAD model parameter 5-50, 23-43
 - RMAX option 7-16, 7-27
 - RMIN option 7-16, 7-27
 - RMS keyword 4-24
 - rms value, measuring 4-23
 - roac model parameter 23-87
 - ROUT keyword 9-19
 - ROUT model parameter 23-88
 - row/matrix ratio 6-20
 - RSH model parameter 10-34
 - runtime statistics 3-47
 - Rxxx resistor element statement 12-6
- S**
- S19NAME model parameter 5-50, 23-41, 23-43
 - S19RHI model parameter 23-41
 - S19RLO model parameter 23-41

- S19TSW model parameter 23-41
- S19VHI model parameter 5-50, 23-43
- S19VLO model parameter 5-50, 23-43
- S1NAME model parameter 5-50, 23-41, 23-43
- S1RHI model parameter 23-41
- S1RLO model parameter 23-41
- S1TSW model parameter 23-41
- S1VHI model parameter 5-50, 23-43
- S1VLO model parameter 5-50, 23-43
- S2NAME model parameter 5-50, 23-41, 23-43
- S2RHI model parameters 23-41
- S2RLO model parameter 23-41
- S2TSW model parameter 23-41
- S2VHI model parameter 5-50, 23-43
- S2VLO model parameter 5-50, 23-43
- .SAMPLE statement 9-18
- sampling noise 9-18
- saturable cores
 - dot convention 12-30
 - elements 12-30
 - names 12-30
 - initial magnetization 12-30
 - models 12-29
 - parameters 12-5
 - winding names 12-30
- saturation
 - current, temperature equations, JFET and MESFET 15-46
 - temperature equations, BJT's 14-53
 - voltage equations, MOSFET's
 - Level 1 17-7
 - Level 13 17-117
 - Level 2 17-15
 - Level 28 17-162
 - Level 3 17-26
 - Level 38 17-178
 - Level 47 17-232
 - Level 5 17-49
 - Level 6 17-67, 17-73
 - Level 8 17-98
- SCALE
 - element parameter 23-22, 23-28, 23-32, 23-37, 27-10
 - option 15
 - parameter 27-34
- scale
 - diode parameters 13-9
 - factor 12-7
 - JFET and MESFET 15-5
 - parameters 15-9
 - resistors 12-6
- SCALE option 12-13, 12-20, 13-3, 16-10, 16-14
- scaling 16-11
 - BJT's 14-5
 - effect on delays 31
 - global SCALM override 16-11
 - global vs model 13-3, 16-11
 - MOSFET capacitance parameters 16-72
- SCALM
 - option 12-13, 12-20, 13-3
 - JFET and MESFET scaling 15-5
 - parameter
 - global scaling 16-11
 - in a diode model statement 13-3

- overriding in a model 16-11
- scaling by model 16-11
- scattering (S) parameters 9-8
- schematics, netlisting 3-29
- Schichman-Hodges model 16-3
- Schmitt trigger example 8-7
- scope of parameters 10-19
- scratch files 3-8
- SDA option 3-48, 3-54
- s-domain 27-17
 - equivalent circuit 27-22
- SEARCH option 3-54, 3-58, 3-59, 28
- search path, setting 3-59
- self inductance 22-106
- .SENS statement 8-8
- sensitivity analysis 8-9
- sensitivity factors, MOSFET Level 28 17-158
- setup time 28-4
 - analysis 28-6, 28-9
- SFFM source function 5-17
 - carrier frequency 5-17
 - modulation index 5-17
 - output amplitude 5-17
 - output offset 5-17
 - signal frequency 5-17
- sgn(x) function 10-7
- SGS-Thomson MOS model 16-5
- Sharp model 16-5
- short-channel effect 17-14
- shorted nodes 6-33
- SHRINK model parameter 12-13, 12-20
- SHTHK model parameter 22-28, 22-31
- Siemens model 16-4, 16-5
- Sierra 1 model 16-4
- Sierra 2 model 16-4
- SIG
 - conductivity 22-119
 - model parameter 22-19, 22-26, 22-28, 22-30
- SIG1 model parameter 22-26
- sigma model parameter, sweeping 20-4
- sign function 10-7
- sign transfer function 10-7
- sign(x,y) function 10-7
- SIGNAME element parameter 5-49, 23-40, 23-42
- signed power function 10-6
- Signetics FAST I/O drivers 20-18
- silicon controlled rectifier, behavioral 23-76
- Siliconix model 16-4
- silicon-on-sapphire devices 16-2
- silicon-on-sapphire devices, bulk node name 3-33
- SIM2
 - distortion measure 9-14
 - parameter 4-15
- Simpson Integration 16-90
- simulation
 - accuracy 7-10, 7-11, 7-18, 11-2, 17-5
 - improvement 7-9
 - reduced by BYPASS 7-8
 - tolerances 6-21, 6-22

- accuracy, option defaults 7-27
- multiple analyses, .ALTER
 - statement 3-34, 10-30
- multiple runs 3-24
- results
 - graphing 4-54
 - output variables 3-54
 - plotting 4-52-4-53
 - printing 4-47-4-51
 - specifying 4-19-4-34
 - storing 3-53
- speed 3-52, 7-18
- time 17-5
 - ABSVAR option 7-27
 - reducing 3-37, 7-8, 7-9, 7-12, 7-13, 7-14, 7-16, 7-28
 - with TRTOL 7-14
 - RELVAR option 7-27
- time, reducing 27-45
- title 3-23
- SIN source function 5-9
 - amplitude 5-9
 - damping factor 5-9
 - delay time 5-9
 - frequency 5-9
 - offset 5-9
 - phase delay 5-9
- sin(x) function 10-6
- single point experiment 3-3
- single-frequency FM source function 5-17
- sinh(x) function 10-6
- sinusoidal source function 5-9
- skew
 - file 10-37
 - parameters 10-33
 - assigning 3-65
- skin effect frequency 22-21
- slope (digital vector file) 5-69
- SLOPETOL option 7-13
 - simulation time 7-28
 - timestep control 7-27
- small-signal
 - DC sensitivity 8-9
 - distortion analysis 9-14
 - transfer function 8-9
- SMOOTH element parameter 23-22
- SOI model 17-146
- SONAME model parameter 5-50, 23-41, 23-43
- SORHI model parameter 23-41
- SORLO model parameter 23-41
- SOSFET model 16-2, 16-5
- SOTSW model parameter 23-41
- sources
 - AC sweep 9-4
 - controlled 23-4, 23-13
 - data driven 5-15
 - DC sweep 8-3
 - element types 23-13
 - keywords 5-2
 - Laplace transforms 27-18
 - time sweep 7-4
 - See also independent sources
- SOVHI model parameter 5-50, 23-43
- SOVLO model parameter 5-50, 23-43
- SP model parameter 22-17, 22-26
- SP12 model parameter 22-26

- SPARSE option 6-20
- spatial extent of leading edge 22-112
- spectral leakage 26-2, 26-14
- spectrum analysis 26-1
- SPICE
 - compatibility 3-54, 15-26
 - BSIM model 17-125
 - diodes 16-40
 - models 17-265
 - MOSFET's
 - Level 13 parameters 17-125
 - Level 3 17-30
 - Level 39 17-186, 17-195
 - models 16-3
 - numeric format 3-49
 - output format 4-49
 - plot
 - limits 4-52
 - UTRA model parameter 17-12
 - model parameters, MOSFET Level 39 17-186
 - option 3-54
- SPICE compatibility
 - AC
 - output calculations 9-7
 - output variables 9-9-9-10
- SPICE to IBIS program 24-2
- sqrt(x) function 10-6
- square root function 10-6
- SRN model parameter 23-88
- SRNEG model parameter 23-88
- SRP model parameter 23-88
- SRPOS model parameter 23-88
- .st# file 4-3, 4-5
- stacked devices 16-45
- START .FFT parameter 26-6
- START keyword 7-5
- statements
 - .AC 9-4, 11-5
 - .ALTER 3-34
 - .DATA 3-37, 20-9, 20-10
 - .DC 8-3, 11-5
 - .DCVOLT 6-7
 - .DISTO 9-14
 - .END 3-24
 - .ENDL 3-61, 3-62
 - .ENDS 23-10
 - .EOM 23-10
 - .FFT 7-33, 26-6
 - .FOUR 7-30
 - .GLOBAL 3-25
 - .GRAPH 4-54
 - .IC 6-7
 - .INCLUDE 3-60
 - .LIB 3-61
 - call 3-61
 - nesting 3-63
 - .LOAD 6-13
 - .MACRO 23-9
 - .MEASURE 3-50, 3-51, 4-19
 - .MODEL 3-65, 4-56, 11-7
 - .NET 9-19
 - .NODESET 6-7, 6-15
 - .NOISE 9-16
 - .OP 6-8
 - .OPTIONS 3-45
 - .PARAM 10-12, 11-6
 - .PLOT 4-52
 - .PRINT 4-47

- .PROBE 4-54
- .PROTECT 3-67
- .PZ 8-10
- .SAMPLE 9-18
- .SAVE 6-11
- .SENS 8-9
- .SUBCKT 23-9, 23-82
- .TEMP 3-43, 10-62
- .TF 8-10
- .TITLE 3-24
- .TRAN 7-4, 11-5
- .UNPROTECT 3-67
- .WIDTH 4-51
 - elements 3-25
 - initial conditions 6-6
- statistical analysis 10-33–10-59
- statistics
 - calculations 10-3
 - listing 4-6
 - report 3-47
- Statz model 15-2, 15-3, 15-26
 - capacitance equations 15-32
- STC-ITT model 16-4
- stimulus input files 20-18, 23-4
- STOP .FFT parameter 26-6
- stripline transmission line 22-23
- subcircuits 10-26
 - .PRINT and .PLOT statements 23-8
 - calling 23-10, 23-11
 - calling tree 3-32
 - changing in .ALTER blocks 10-30
 - element names 23-11
 - generator 23-5
 - global versus local nodes 3-25
 - library structure 3-58
 - model names 23-11
 - multiply parameter 23-11
 - multiplying 23-7
 - names 23-9
 - node names 3-30, 23-6, 23-11
 - node numbers 23-9
 - parameter example 20-12
 - parameter passing 23-10, 23-11
 - parameters 23-9
 - path names 3-31
 - power dissipation computation 4-15
 - printing path numbers 3-53
 - search order 23-12
 - zero prefix 3-33
- .SUBCKT statement 23-9
 - search order 23-82
- SUBS model parameter 14-2
- substrate
 - capacitance equations, BJT's 14-43
 - current equations, BJT's 14-36
 - diodes 14-32
- subthreshold current equations,
 - MOSFET's
 - Level 13 17-117
 - Level 2 17-18
 - Level 3 17-29
 - Level 38 17-180
 - Level 5 17-50
 - Level 6 17-76
 - Level 8 17-102
- .sw# file 4-2, 4-4
- sweep
 - data 3-41
 - data, storing 3-51
 - frequency 9-6

- inner 3-41
 - outer 3-41
 - variables 26
 - SWEEP keyword 7-6, 8-5, 9-5
 - switch example 5-30
 - switched capacitor 27-45
 - filter example 27-47
 - switch-level MOSFET example 5-30
 - Synopsys models, calibrating 20-1
 - systems, simulating 20-2
- T**
- T elements 22-2
 - lossless transmission line model 22-118
 - multiplier function M 22-5
 - parameters 22-10
 - statement 22-10
 - transient effects modeling 22-104
 - Taguchi analysis 10-2
 - tan(x) function 10-6
 - tanh(x) function 10-6
 - TARG keyword 4-21
 - target specification 4-20
 - Taylor-Huang model 16-4
 - TC1, TC2 element parameters 23-23, 23-28, 23-32, 23-37, 27-10
 - TD
 - element parameter 22-11, 23-23, 23-28, 23-33, 23-37
 - keyword 4-14, 4-25
 - tdelay (digital vector file) 5-68
 - TDR (time domain reflectometry) 20-9
 - TEMP
 - keyword 8-5, 9-5
 - model parameter 3-43, 10-61, 23-88
 - sweep variable 26
 - .TEMP statement 3-43–3-44, 10-61, 10-62–10-63
 - temper variable 10-8
 - temperature
 - AC sweep 9-4
 - BJT's
 - beta equations 14-53–14-57
 - capacitance equations 14-57
 - energy gap equations 14-53
 - Level 2 equations 14-60
 - parasitic resistor equations 14-60
 - saturation equations 14-53–14-57
 - capacitor equations 12-9
 - circuit 10-62
 - default 10-61
 - coefficients 12-7, 12-16, 12-23
 - G and E elements 27-10
 - compensation
 - equations, MOSFET Level 47 17-237
 - parameters, MOSFET Level 13 17-129
 - DC sweep 8-3, 8-6
 - derating 3-43, 10-61
 - diodes 13-22
 - effects
 - MOSFET Level 39 17-200
 - parameters, BJT's 14-27
 - element 10-61, 10-62
 - parameters 12-3

- relative to circuit 12-6
- equations
 - BJT Level 2 14-60
 - BJT's 14-53
 - MOSFET 16-110
 - resistors 12-9
- JFET
 - equations 15-45–15-49
 - TLEV parameter 15-42
 - TLEVC parameter 15-42
- MESFET equations 15-45–15-49
- model parameters 12-5
- optimizing coefficients 26
- parameters
 - JFET 15-42
 - JFET and MESFET 15-43
 - MOSFET's 16-107
 - Level 13 17-111
 - Level 28 17-158
 - Level 49 17-248
- reference 3-43, 10-61
- sweeping 26
- time sweep 7-4
- variable 10-8
- .TF statement 8-8, 23-63
- tfall (digital vector file) 5-70
- TH model parameter 22-17, 22-26
- TH1 model parameter 22-26
- THB model parameter 22-17, 22-26
- THD (total harmonic distortion) 26-1
- The 3-67
- thermal noise 12-8
- THK1 model parameter 22-26
- THK2 model parameter 22-26
- threshold temperature equations, JFET and MESFET 15-48
- threshold voltage
 - equations, MOSFET's
 - Level 1 17-6
 - Level 13 17-116
 - Level 2 17-14
 - Level 28 17-160
 - Level 3 17-26
 - Level 38 17-176
 - Level 47 17-230
 - Level 5 17-46
 - Level 6 17-63
 - Level 8 17-98
 - parameters, MOSFET's
 - Level 1 17-4
 - Level 2 17-10
 - Level 3 17-22
 - Level 38 17-170
 - Level 5 17-36
 - Level 8 17-93
 - Levels 6, 7 17-57
- TI model 16-5
- TIC model parameter 4-56
- time 6-9
 - domain
 - to frequency domain 27-1
 - maximum 27-6
 - resolution 27-5
 - sweep 7-4
 - variable 10-8
 - versus impedance 20-9
 - See also CPU time
 - time domain
 - algorithm 7-22

- time-domain reflectometry 20-9
- TimeMill models, calibrating 20-1
- TIMERES option 7-14
- TIMESCALE model parameter 5-50
- timestep
 - algorithms 7-9, 7-25
 - calculation for DVDT=3 7-15
 - changing size 7-13
 - control 7-13, 7-14, 7-15
 - algorithms 7-24–7-27
 - DELMAX 7-27
 - error 22-64
 - FS 7-27
 - FT 7-27
 - minimum internal timestep 7-27
 - Minimum Timestep Coefficient 7-27
 - options 7-19, 7-27
 - CHGTOL 7-26
 - IMAX 7-25
 - IMIN 7-25
 - RELQ 7-26
 - TRTOL 7-26
 - RMAX 7-27
 - RMIN 7-27
 - TSTEP 7-28
 - default control algorithm 7-21
 - DVDT algorithm 7-26
 - internal 7-15
 - local truncation error algorithm 7-26
 - maximum 7-16
 - minimum 7-16
 - reversal 7-26
 - definition 7-11
 - setting initial 7-15
 - transient analysis algorithm 7-9
 - variation by HSPICE 7-15
- TIMESTEP model parameter 5-50, 23-41, 23-43
- timing
 - analysis 28-1
 - constraints 28-1
 - failures 28-2
 - hold time 28-4
 - setup time 28-4
 - violation analysis 28-2
- title for simulation 3-23
- tmp directory 3-8
- TMPDIR environment variable 3-8
- TNOM option 3-43, 10-61
- TO
 - keyword 4-24, 4-32
- TO .FFT parameter 26-6
- TOL 9-18
- tolerance options 6-14
- TOM model 15-2, 15-50
 - Level 3 parameters 15-50
 - parameters 15-52
 - See also TriQuint model
- TOP keyword 6-12
- topology check, suppressing 3-52
- TOX model parameter 10-34
- .tr# file 4-2, 4-4
- .TRAN statement, external data 7-38
- transcapacitance 16-61
- transconductance
 - FREQ function 27-8
 - JFET and MESFET 15-10

- LAPLACE function 27-6
- MOSFET 16-18
- POLE function 27-7
- transfer function 8-9
 - algebraic 23-3
 - analysis 23-63
 - coefficients 27-27
 - filters 27-28
 - frequency domain 25-2, 27-17
 - general form 27-17, 27-26
 - inverse Laplace transform 27-30
 - poles 25-2
 - reduced form 27-27
 - roots 25-2
 - voltage gain 27-21
 - zeros 25-2
- transfer sign function 10-7
- TRANSFORMER element parameter 23-33
- transformer, behavioral 23-74
- transforms, Fourier 27-5
- transient analysis
 - Fourier analysis 7-30
 - initial conditions 6-6
 - number of iterations 7-16
- transient modeling 27-2
- transistors
 - lateral 14-33
 - geometry 14-33, 14-49
 - process parameters, MOSFET's
 - Level 13 17-105
 - Level 28 17-151
 - Level 49 17-241, 17-249, 17-250, 17-251
 - substrate diodes 14-32
 - geometry 14-33
 - vertical 14-33
 - geometry 14-33, 14-48
- transit time parameters, BJT's 14-25
- transition files 23-4
- transmission lines
 - AC resistance 22-22
 - analysis guidelines 22-112
 - attenuation 22-118
 - calculations 22-115
 - effects 22-124
 - factor 22-39
 - bandwidth 22-109
 - branch capacitances 22-35, 22-36
 - capacitance
 - definitions 22-34
 - matrix 22-54
 - to ground 22-21
 - CEXT parameter 22-34
 - characteristic impedance 22-11, 22-99, 22-103
 - Cjk symbol 22-34
 - clock frequency 22-109
 - coax
 - example 22-59
 - models 22-27
 - common ground inductance 22-104
 - conductance definitions 22-34
 - conductor
 - length 22-34
 - width 22-34
 - conductor resistance 22-123
 - coupled
 - lines 22-12
 - microstrips example 22-62

- stripline example 22-57
- crosstalk 22-104, 22-108
- CX symbol 22-34
- CXY symbol 22-34
- delay parameter 22-11
- delay too small warning 22-5
- delays 22-38
- dielectric loss 22-120
- dispersion 22-118
- dissipation 22-121
 - factor 22-119
- dual dielectric 22-23
- effects 20-7
- elements 22-2
 - names 22-11
 - selection 22-4
- example 20
- geometric parameters 22-19
- Gjk symbol 22-34
- GPR parameter 22-34
- ground plane 22-5
- GX symbol 22-34
- GXY symbol 22-34
- HSPICE
 - ground 22-20
 - reference plane 22-5
- ideal, properties 22-6
- impedance 22-101
 - lumped elements 22-101
 - mismatch 22-69
- inductance 22-104
 - matrix 22-54
- initial conditions 22-11
- input attenuation 22-39
- integration
 - algorithms 22-45
 - method 22-64
- interconnect properties 22-3
- LLEV parameter 22-34
- loss
 - calculations 22-115
 - factor 22-39
- lossless model 22-99
- lossy model 22-15, 22-100, 22-121
 - properties 22-6
 - selector 22-15
 - statement 22-15
- lumped
 - parameters 22-22
 - RC model 22-6
 - RLC model 22-100
- matrixes 22-35, 22-36, 22-54–22-56
- measured parameters 22-37
- microstrip 22-23
- models 22-2
 - selection 22-4
- multiple
 - conductors 22-34
 - stripline, example 22-41
- mutual inductance 22-105
- normalized length 22-11
- number of lumps 22-48, 22-64
 - computation 22-65
 - default 22-65
 - specification 22-65
- oscillation problems 22-63
- overlay dielectric 22-23
- parameter error 22-20
- parameters, combining 22-39
- physical
 - length parameter 22-11
 - parameters 22-18

- planar 22-16
 - conductors 22-23
 - models 22-17
- precomputed parameters 22-32
 - keywords 22-33
- printed circuit boards 20-55
 - example 22-58
- properties 22-1
- reflection calculations 22-114
- ringing 22-22, 22-63–22-68
- risetime 22-109
- sea of dielectric 22-23
 - example 22-46
- self inductance 22-106
- SIG conductivity parameter 22-119
- signal reflections 22-69
- simulation 20-2
- skin depth 22-119
 - calculation 22-115
- skin effect frequency 22-21
- source properties 22-3
- stripline 22-23
- switching noise 22-104
- theory 22-99
- timestep control errors 22-64
- total conductor resistance 22-53
- transient impedance effects 22-104
- twinlead
 - example 22-61
 - models 22-29
- U element 22-100
 - See also T elements, U elements, U models
- TRAP algorithm 7-9
 - See also trapezoidal integration
- trapezoidal integration
 - algorithm 7-21
 - coefficient 7-12, 7-14
- TREF model parameter 10-61, 10-62
- TRIG keyword 4-21
- trigger specification 4-20
- triode tube example 5-32
- triode tube, behavioral 23-77
- TriQuint model 15-2
 - extensions 15-50
 - Level 3 parameters 15-50
 - See also TOM model
- trise (digital vector file) 5-70
- triz (digital vector file) 5-71
- TRTOL option 7-14, 7-26
- truncation algorithm 7-25
- TS model parameter 22-17, 22-26
- TS1 model parameter 22-30
- TS2 model parameter 22-31
- TS3 model parameter 22-31
- tskip (digital vector file) 5-66
- TSTEP
 - multiplier 7-16
 - setting 7-16
 - option 7-16
 - timestep control 7-28
- TTL devices 14-2
- tunit (digital vector file) 5-65
- tunnel diode, behavioral 23-75
- twinlead
 - see transmission lines
- Txxx element parameter 22-11

U

- U elements 5-46, 22-2, 23-39
 - attenuation effects 22-124
 - digital element 23-40, 23-42
 - element name 22-14
 - input node names 22-14
 - lossy transmission line model 22-100, 22-118
 - model name 22-14
 - multiplier function M 22-5
 - number of lumps 22-14
 - output node names 22-14
 - parameters 22-14
 - physical length parameter 22-14
 - reference plane name 22-14
 - statement 22-14
 - transient effects modeling 22-104
 - transmission line model 22-107
- U models
 - conductor
 - height 22-17
 - resistivity 22-19
 - spacing 22-17
 - thickness 22-17
 - width 22-17
 - dielectric
 - conductivity 22-19
 - configurations 22-16
 - constant 22-17
 - electrical specification format 22-15
 - ELEV parameter 22-7
 - external capacitance 22-17
 - model selector 22-15, 22-17
 - number of conductors 22-17
 - number of layers 22-19
 - number of lumps 22-17
 - parameters 22-15, 22-17–22-40
 - perturbation
 - multiplier 22-17
 - parameter 22-17
 - PLEV parameter 22-7
 - reference plane
 - configuration 22-15
 - height 22-17
 - resistivity 22-19
 - separation distance 22-17
 - thickness 22-17
 - selection 22-7
 - transmission line type selector 22-15
 - .MODEL statement 22-15
- UIC
 - keyword 7-6
 - parameter 6-7
 - transient analysis parameter 7-3
- UIC analysis parameter 6-5
- UNIF
 - keyword 10-41
 - Monte Carlo function 10-16
- uniform parameter distribution 10-39
- unity gain frequency 28
- UNORM FFT analysis keyword 26-6
- unprintable characters in input 3-18
- .UNPROTECT statement 29-2
- UNWRAP option 9-8
- UPDATE parameter
 - MOSFET Level 13 17-130
 - MOSFET Levels 6, 7 17-59
- URL for Avant! vi
- UTRA model parameter restriction 6-31

Uxxx element parameter 22-14

V

variables

AC formats 9-11

changing in .ALTER blocks 10-30

DEFAULT_INCLUDE 3-16

output 4-5

AC analysis 9-8

names 4-6

plotting 15

sweeping 26

TMPDIR 3-8

variance, statistical 10-3

VCC model parameter 23-88

VCCAP element parameter 23-23

VCCS element parameter 23-23

VCO

example 23-34

model 23-112

See also voltage controlled oscillator

VCR element parameter 23-23

VCVS

element parameter 23-33

inverting comparator application 23-96

VEE model parameter 23-88

VERIFY option 3-55

Verilog models, calibrating 20-1

Verilog value format 5-61

version

95.3 compatibility 7-27

H9007 compatibility 3-49

HSPICE 3-66

specifying 3-12

VFLOOR option 7-17

VHDL

models, calibrating 20-1

Viewlogic 5-46

graph data file 3-49

Viewsim simulator 5-46, 23-39

vih (digital vector file) 5-72

vil (digital vector file) 5-72

vname (digital vector file) 5-63

Vnn node name in CSOS 3-33

VNTOL option 7-11, 7-12, 7-14

voh (digital vector file) 5-74

vol (digital vector file) 5-74

VOL keyword 5-41, 23-34

voltage

error tolerance

DC analysis 6-27

transient analysis 7-13

failure 6-35

gain

FREQ function 27-8

LAPLACE function 27-6

POLE function 27-7

initial conditions 6-6

iteration-to-iteration change 6-16

JFET and MESFET DC models 15-35

limiting, in transient analysis 7-15

maximum change 7-11

minimum

DC analysis 6-24

listing 7-17

transient analysis 7-14

- MOSFET model parameters 16-52
 - operating point table 6-9
 - relative change, setting 7-13
 - summer 5-40, 23-33
 - tolerance
 - BYTOL option 7-11
 - MBYPASS multiplier 7-12
 - value for BYPASS 7-11
 - variable capacitance model 23-102
 - voltage controlled
 - capacitor 23-20
 - current 23-21
 - capacitor example 5-31
 - current source 5-25, 5-33, 23-13, 23-18
 - oscillator 5-41, 23-34
 - See also VCO
 - oscillator model 23-98
 - resistor 23-13, 23-19
 - sources 5-20
 - voltage source 5-37, 23-13, 23-30
 - VOLTAGE keyword 6-9
 - VON model parameter 23-88
 - VONEG model parameter 23-88
 - VOP model parameter 23-89
 - VOPOS model parameter 23-89
 - VOS model parameter 23-89
 - Vos specification 23-5
 - vref (digital vector file) 5-72
 - VREL model parameter 22-38
 - vth (digital vector file) 5-73
 - VTI model 16-5
 - VVCAP model 23-102
 - Vxxx source element statement 5-2
- W**
- warnings
 - all nodes connected together 6-33
 - capacitance too large 12-19
 - floating power supply nodes 3-31
 - inductance too large 12-25
 - invalid value for CRATIO 12-10
 - IS parameter too small 13-17
 - limiting repetitions 3-55
 - MAXF ignored 27-10
 - misuse of VERSION parameter 3-66
 - resistance smaller than RESMIN 12-14
 - suppressing 3-52
 - T-line delay too small 22-5
 - zero diagonal value detected 6-35
 - WARNLIMIT option 3-55
 - WD model parameter 22-17, 22-26
 - WD1 model parameter 22-26
 - WDAC parameter 16-103
 - WEIGHT keyword 4-25, 4-32
 - WHEN keyword 4-25, 28
 - WIC weak inversion current selector 17-76
 - width of printout 4-51
 - winding elements 12-3
 - WINDOW .FFT parameter 26-7
 - wire models
 - capacitance
 - calculation 12-14
 - distribution 12-10
 - effective length and width 12-13
 - model parameters 12-5
 - parameters 12-9, 12-12

- resistance calculation 12-13
- wires 22-2
 - critical length 20-7
 - model selection 22-72
 - types 20-7
 - See also transmission lines
- WLUMP model parameter 22-17
- WMAX model parameter 5
- WMIN model parameter 5
- worst case analysis 10-33–10-59
 - example 20-10
- Wscaled scaled width 12-7
- WSF output data 3-48
- WWW site for Avant! vi

X

- XGRID model parameter 4-56
- XL model parameter 10-34
- XMAX model parameter 4-56
- XMIN model parameter 4-56
- XnR, XnI option 8-12
- XPHOTO model parameter 10-47
- XSCAL model parameter 4-56
- XW model parameter 10-34, 22-17, 22-26

Y

- Y-parameter modeling 27-36
- YGRID model parameter 4-56
- yield analysis 10-2
- YIN keyword 9-13, 9-20
- YMAX

- keyword 4-32
- model parameter 4-57

YMIN

- keyword 4-31
- model parameter 4-57

YOUT keyword 9-13, 9-20

YSCAL model parameter 4-57

Z

- Z0 element parameter 22-11
- Zener diodes 13-3
- zero delay
 - gate example 5-31
 - inverter gate 5-41
- ZIN keyword 9-13, 9-20
- ZK model parameter 22-38
- ZOUT keyword 9-13, 9-20
- ZUKEN option 3-55