

Displacement Textures



Oregon State
University
Mike Bailey


mjb@cs.oregonstate.edu



This work is licensed under a [Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License](https://creativecommons.org/licenses/by-nc-nd/4.0/)




Displacement Textures are a Special Way to Model 3D Geometry




**Think of the Textures as 2D Data Tables:
One to Hold RGB Values and One to Hold Height Values**


3

Image Texture



Displacement Texture
(light = high, dark = low)





Oregon State
University
Computer Graphics

mjb - December 31, 2023

Why Use a Texture to Hold Height Values?


4

Displacement Texture
(light = high, dark = low)



Textures:

1. Can be very large.
2. Have been architected for fast lookup.
3. Are capable of bilinear interpolation if you lookup an (s,t) that doesn't fall exactly on a height value. Therefore, you have lots of flexibility with how dense your vertex mesh is.


Oregon State
University
Computer Graphics

mjb - December 31, 2023

Displacement Textures are a Special Way to Model 3D Geometry

5

moondisp.glib

```

##OpenGL GLIB
Perspective 70
LookAt 0 0 3 0 0 0 0 1 0


Texture2D 6 lroc_color_poles_4k.bmp
Texture2D 7 ldem_16_uint.bmp

Vertex moondisp.vert
Fragment moondisp.frag
Program MoonDisp

        uDoElevations <false> \
        uDoLighting <false> \
        uLightX <-10. 0. 10.> \
        uLightY <-10. 0. 10.> \
        uLightZ < 1. 10. 10.> \
        uKa <0. 0.2 1.0> \
        uKd <0. 0.9 1.0> \
        uSeaLevel <0. 0.25 1.0> \
        uHeightScale <0. 0.25 0.50> \
        uNormalScale <0. 0.04 0.10> \
        uColorUnit 6 \
        uDispUnit 7

Color 1. .3 0.
Sphere 1. 600 600

```



mjb - December 31, 2023

Displacement Textures are a Special Way to Model 3D Geometry

6

moondisp.vert

```

#version 330 compatibility

uniform float          uLightX, uLightY, uLightZ;
uniform float          uHeightScale;
uniform float          uSeaLevel;
uniform sampler2D      uDispUnit;
uniform bool           uDoElevations;

out vec2               vST;
out vec3               vN; // normal vector
out vec3               vL; // vector from point to light
vec3 LIGHTPOS = normalize( vec3( uLightX, uLightY, uLightZ ) );

void
main()
{
    vec2 st = gl_MultiTexCoord0.st;
    vST = st;

    vec3 norm = normalize( gl_NormalMatrix * gl_Normal ); // normal vector
    vN = norm;
    vec4 ECposition = gl_ModelViewMatrix * gl_Vertex; // eye coordinate position
    vL = LIGHTPOS - ECposition.xyz; // vector from the point to the light position

    vec3 vert = gl_Vertex.xyz;
    if( uDoElevations )
    {
        float disp = texture( uDispUnit, st ).r; // in half-meters, relative to a radius of 1727400 meters
        disp -= uSeaLevel;
        disp *= uHeightScale;
        vert += normalize(gl_Normal) * disp;
    }

    gl_Position = gl_ModelViewProjectionMatrix * vec4( vert, 1. );
}

```



mjb - December 31, 2023

Displacement Textures are a Special Way to Model 3D Geometry

7

moondisp.frag, I

```

#version 330 compatibility

uniform bool      uDoLighting;
uniform float     uKa, uKd;
uniform float     uHeightScale;
uniform float     uNormalScale;
uniform sampler2D uColorUnit;
uniform sampler2D uDispUnit;
in vec2          vST;
in vec3          vN;
in vec3          vL;
const float DELTA = 0.01;

void main( )
{
    vec3 newColor = texture( uColorUnit, vST ).rgb;
    gl_FragColor = vec4( newColor, 1. );
    if( uDoLighting )
    {
        ...
    }
}

```



mjb - December 31, 2023

Displacement Textures are a Special Way to Model 3D Geometry

8

moondisp.frag, II

```

if( uDoLighting )
{
    vec2 stp0 = vec2( DELTA, 0. );
    vec2 st0p = vec2( 0. , DELTA );
    float west = texture2D( uDispUnit, vST-stp0 ).r;
    float east = texture2D( uDispUnit, vST+stp0 ).r;
    float south = texture2D( uDispUnit, vST-st0p ).r;
    float north = texture2D( uDispUnit, vST+st0p ).r;
    vec3 stangent = vec3( 2.*DELTA, 0., uNormalScale * ( east - west ) );
    vec3 ttangent = vec3( 0., 2.*DELTA, uNormalScale * ( north - south ) );
    vec3 Normal = normalize( cross( stangent, ttangent ) );
    vec3 Light = normalize(vL);

    vec3 ambient = uKa * newColor;
    float d = 0.;
    if( dot(Normal,Light) > 0. ) // only do diffuse if the light can see the point
    {
        d = dot(Normal,Light);
    }
    vec3 diffuse = uKd * d * newColor;
    gl_FragColor = vec4( ambient+diffuse, 1. );
}
}

```



mjb - December 31, 2023

Displacement Textures are a Special Way to Model 3D Geometry

9

Just the image texture



Lighting only, no displacements



Displacements only, no lighting



Displacements + Lighting



Note: as you can imagine, static images do not do this justice. Being able to dynamically rotate the Moon and change the height exaggeration and light position makes a big difference!



mjb - December 31, 2023