

Two Side-by-side Non-symmetric Perspective Viewing Volumes

Cyclops eye:

$$L0p = -Z0p * \tan(\theta/2)$$

$$R0p = Z0p * \tan(\theta/2)$$

$$B0p = -Z0p * \tan(\theta/2)$$

$$T0p = Z0p * \tan(\theta/2)$$

OSU Oregon State University Computer Graphics #10 - February 27, 2018

Two Side-by-side Non-symmetric Perspective Viewing Volumes

Use the Cyclops's left and right boundaries as the left and right boundaries for each eye, even though the scene has been translated. In the left eye view, the boundaries must then be shifted by +E to match the +E shift in the scene. In the right eye view, the boundaries must be shifted by -E to match the -E shift in the scene.

Left eye:

$$R0p = Z0p * \tan(\theta/2) + E$$

$$L0p = -Z0p * \tan(\theta/2) + E$$

Right eye:

$$R0p = Z0p * \tan(\theta/2) - E$$

$$L0p = -Z0p * \tan(\theta/2) - E$$

OSU Oregon State University Computer Graphics #10 - February 27, 2018

Stereo Perspective

```
float
Tand( float deg )
{
    float rad = deg * (float)M_PI / 180.f;
    return (float)tan( rad );
}

void
FrustumZ( float left, float right, float bottom, float top, float znear, float zfar, float zproj )
{
    if( zproj != 0.0 )
    {
        left *= ( znear/zproj );
        right *= ( znear/zproj );
        bottom *= ( znear/zproj );
        top *= ( znear/zproj );
    }
    glFrustum( left, right, bottom, top, znear, zfar );
}

```

OSU Oregon State University Computer Graphics #10 - February 27, 2018

Stereo Perspective

```
void
StereoPers( float fovxdeg, float aspect_y_over_x, float znear, float zfar, float z0p, float eye )
{
    float tanfovx = Tand( fovxdeg / 2.f );

    float right = z0p * tanfovx;
    float left = -right;

    float bottom = aspect_y_over_x * left;
    float top = aspect_y_over_x * right;

    left = left - eye;
    right = right - eye;

    FrustumZ( left, right, bottom, top, znear, zfar, z0p );

    glTranslatef( -eye, 0.0, 0.0 );
}

```

OSU Oregon State University Computer Graphics #10 - February 27, 2018

Spherical Stereo Strategy (S³?)

Strategy:

1. Leave the eye in the center of the 3D scene
2. Rotate the look-at position 360° in a series of discrete steps
3. For each look-at position, render two stereo views, each essentially a very narrow vertical strip of pixels
4. Upload the pixels from each render and collect them in a single image as left- and right-eye panoramic views

OSU Oregon State University Computer Graphics #10 - February 27, 2018

Program Setup

```
const int PHIDEG = 5;
const int NUMSEGS = 360 / PHIDEG;
const int PIXELS_PER_SEG = 20;
const int WIDTH = NUMSEGS * PIXELS_PER_SEG;
const int HEIGHT = WIDTH / 2;
const float ASPECT_Y_OVER_X = (float)HEIGHT / (float)PIXELS_PER_SEG;
const float Z0P = 100.f;
const float ZNEAR = 1.0f;
const float ZFAR = 200.0f;
const float EYESEP = 0.25f;
const float EX = 0.f;
const float EY = 0.f;
const float EZ = 0.f;

unsigned char LeftRight[ 3*2*WIDTH*HEIGHT ]; // 3 = color components, 2 = L+R images

```

OSU Oregon State University Computer Graphics #10 - February 27, 2018

Program Setup

```

void
InitGraphics( )
{
    glutInitDisplayMode( GLUT_RGBA | GLUT_SINGLE | GLUT_DEPTH );
    glutInitWindowPosition( 0, 0 );
    glutInitWindowSize( PIXELS_PER_SEG, HEIGHT );

    MainWindow = glutCreateWindow( WINDOWTITLE );
    glutSetWindowTitle( WINDOWTITLE );

    glClearColor( BACKCOLOR[0], BACKCOLOR[1], BACKCOLOR[2], BACKCOLOR[3] );
    glutDisplayFunc( Display );

#ifdef WIN32
    GLenum err = glewInit();
    if( err != GLEW_OK )
    {
        fprintf( stderr, "glewInit Error\n" );
    }
    else
    {
        fprintf( stderr, "GLEW initialized OK\n" );
    }
    printf( stderr, "Status: Using GLEW %s\n", glewGetString(GLEW_VERSION));
#endif
}
    
```

13

Drawing the Scene in Strips, I

```

void
DrawAndWriteSegments( )
{
    unsigned char array[3*PIXELS_PER_SEG*HEIGHT];

    glutSetWindow( MainWindow );
    glDrawBuffer( GL_FRONT );
    glEnable( GL_DEPTH_TEST );
    glShadeModel( GL_FLAT );
    glViewport( 0, 0, PIXELS_PER_SEG, HEIGHT );

    for( int eye = 0; eye <= 1; eye++ )
    {
    
```

14

Drawing the Scene in Strips, II

```


for( int eye = 0; eye <= 1; eye++ )
{
    glMatrixMode( GL_PROJECTION );
    glLoadIdentity();
    StereoPersp( (float)PHIDEG, ASPECT_Y_OVER_X, ZNEAR, ZFAR, ZOP,
                eye == 0 ? -EYSEPP : EYSEPP );

    // left goes on the top -- right goes on the bottom
    unsigned char *FullArray = ( eye == 1 ? &LeftRight[0] : &LeftRight[3*WIDTH*HEIGHT] );

    int col = 0; // column in the full array
    for( int lookDeg = 90; lookDeg > -270; lookDeg -= PHIDEG )
    {
        glClear( GL_COLOR_BUFFER_BIT | GL_DEPTH_BUFFER_BIT );
        glMatrixMode( GL_MODELVIEW );
        glLoadIdentity();

        float lx = Cosd( (float)lookDeg ) + EX;
        float ly = Sind( (float)lookDeg ) + EY;
        float lz = EZ;
        gluLookAt( EX, EY, EZ, lx, ly, lz, 0., 0., 1. );

        glCallList( LidarList );
        glFlush();
        glFinish();
    }
}
    
```



15

Drawing the Scene in Strips, III

```

glPixelStorei( GL_PACK_ALIGNMENT, 1 );
glReadPixels( 0, 0, PIXELS_PER_SEG, HEIGHT, GL_RGB, GL_UNSIGNED_BYTE, array );

for( int y = 0; y < HEIGHT; y++ )
{
    memcpy( &FullArray[3*y*WIDTH + 3*col],
            &array[3*y*PIXELS_PER_SEG + 0], 3*PIXELS_PER_SEG );

    //for( int x = 0; x < PIXELS_PER_SEG; x++ )
    // {
    //     //FullArray[3*y*WIDTH + 3*(col+x) + 0] = array[3*y*PIXELS_PER_SEG + 3*x + 0];
    //     //FullArray[3*y*WIDTH + 3*(col+x) + 1] = array[3*y*PIXELS_PER_SEG + 3*x + 1];
    //     //FullArray[3*y*WIDTH + 3*(col+x) + 2] = array[3*y*PIXELS_PER_SEG + 3*x + 2];
    // }


    col += PIXELS_PER_SEG;
} // lookDeg
} // eye

WriteArray( (char *)Lidar.bmp, LeftRight);
}
    
```

16

Displaying on your Phone

Go to: <http://vrails.io>


VRails stands for:

- VR – Awesome In Space
- It's also the French word for "true"

If you've already registered, sign in here.
If not, sign up here.


17

Displaying on your Phone



Click here and **Browse** to your JPEG file.
Click **Upload**.

Supply the **Title**, **Description**, and **Convergence distance (Z0p)**.



18

Displaying on your Phone 19

The VRAIS app exists for both Android and iOS. Load it on your phone. Run it and login with the same information you registered on the VRAIS web site.

You see this screen. Swipe left a couple of times until you see this screen. Click on the image you want to load.

University of Central Florida Computer Graphics #JP - February 27, 2018

Displaying on your Phone 20

You get this stereopair. If you rotate your phone, you see that the view changes to look in that direction.

If you have a headset, plug your phone into it.

Voilà! That's French for "voilà". ☺

University of Central Florida Computer Graphics #JP - February 27, 2018

Getting your own Headset 21

Go to https://www.amazon.com/Mattel-DTH61-View-Master-Deluxe-Viewer/dp/B01CNSO79Q/ref=sr_1_6?ie=UTF8&qid=1519763407&sr=8-6&keywords=view-master

Or, go to <http://amazon.com> and enter: **View-Master**

This is the **Mattel View-Master Deluxe VR Viewer**. It sells for under \$25. Mine is an earlier model of this one, and I am very happy with it. I trust View-Master to get the mechanical design and the optics right. They've been doing this for years.

But, really, anything that claims to be compatible with **Google Cardboard** should work.

University of Central Florida Computer Graphics #JP - February 27, 2018