

## Bearing Capacity of Spread Footings on Aggregate Pier Reinforced Clay

Armin W. Stuedlein<sup>1</sup>, *Ph.D., P.E., M. ASCE* and Robert. D. Holtz<sup>2</sup>, *Ph.D., P.E., D.GE, Dist. M. ASCE*

<sup>1</sup> Assistant Professor, Oregon State University, 220 Owen Hall, Corvallis, OR, 97331

<sup>2</sup> Professor Emeritus, University of Washington, Box 352700, Seattle, WA 98195

### ERRATUM

Several copy-editing / typographical errors found their way into this manuscript; corrections to the errors follow:

1. Equations (7) and (8) represent the ultimate minor total principal stress, rather than the total initial in-situ radial stress, and appear as:

$$\sigma_{3,ult} = \frac{\tan \delta}{A_s} \left( q \cdot A_a + \frac{s_u \cdot A_c}{\sin \delta} \right) \quad (7)$$

$$\sigma_{3,ult} = \left( q + \frac{2 \cdot s_u}{\sin 2 \cdot \delta} \right) \left( 1 + \frac{\tan \delta_p}{\tan \delta} \right) \quad (8)$$

2. Equation (9):  $\delta_s$  should be  $\delta_p$

3. Below Equation (11),  $\delta_p$  should be  $\phi_p$