


# Logic Synthesis

- ▶ Logic synthesis transforms RTL code into a gate-level netlist
  - ▶ RTL Verilog converted into Structural Verilog

```
Assign zero_det = (data_bus == '0') ? 1'b0 : 1'b1
```

Verilog source code


TRANSLATION  
(YCAD\_SVERILOG)



Generic Boolean Gates  
(GTECH)

- no timing or loading information
- A virtual library, not "real gates"

OPTIMIZATION +  
MAPPING  
(compile)



TARGET LIBRARY  
(SAED Cell Library)

# Logic Synthesis - The process and steps

## ▶ Translation

- ▶ Check RTL for valid syntax
- ▶ Transform RTL to unoptimized generic (GTECH) gates
- ▶ Parameters applied
- ▶ Replace arithmetic operators with DesignWare components
- ▶ Link all the parts of the design



# Logic Synthesis - Process and Steps


## ▶ Optimization and Mapping

- ▶ Optimization and Mapping driven by constraints and cell library
- ▶ Choose best DesignWare implementation
- ▶ Factor out common logical sub-expressions and share terms
- ▶ Flatten logic into 2-level realization - hurts area
- ▶ Map logic into best fit implementation for given cell library
- ▶ Iterate to find "best" realization

# Logic Synthesis - Process and Steps

- ▶ 4-bit Counter, optimized, mapped, with constraints:

```
create_clock -period 4 [get_ports clk]
set_input_delay 3.0 -max -clock clk [remove_from_collection [all_inputs]\
[get_ports clk]]
```



# Logic Synthesis - Constraints

- ▶ Constraints guide optimization and mapping process
- ▶ The designer sets goals (timing, area) through *constraints*


```
# design constraints below #
set_operating_conditions -max TYPICAL
set_wire_load_model -name 8000
set_wire_load_mode top
create_clock -period 20 -name my_clock [get_ports clk_50]
set_output_delay 2.0 -max -clock my_clock [all_outputs]
set_load [expr 5 * [load_of saed90nm_typ/AND2X1/IN1]] [all_outputs]
```

- ▶ DC works to build a circuit that meets your constraints.
- ▶ Typically this is the smallest design that just meets timing
- ▶ Different constraints give *different circuits* but *same function*
- ▶ We provide DC our constraints via a TCL synthesis script

# Logic Synthesis - Constraints

- ▶ Back to our 4-bit counter
- ▶ Tightening the constraints even tighter...

```
set_input_delay 3.8 -max -clock clk [remove_from_collection [all_inputs] \  
    [get_ports clk ]]
```



- ▶ Same function, but bigger and faster

# Logic Synthesis - Cell Library

- ▶ ASIC vendor supplies the technology file (.lib) for your library
- ▶ The .lib file is compiled into a .db file with *library\_compiler*
- ▶ DC uses the .db file to guide optimization and mapping
- ▶ Cell library contains cell delay, wire table, loading table, etc.
- ▶ DC maps to the cell library given in the .synopsys\_dc\_setup file

# Logic Synthesis - DC setup file

## ▶ .synopsys\_dc\_setup

```
# Tell DC where to look for files
lappend search_path ../libs
set synop_lib /nfs/guille/a1/cadlibs/synop_lib/SAED_EDK90nm
# Set up libraries
set target_library $synop_lib/Digital_Standard_Cell_Library/synopsys/models/saed90nm_typ_lt_pg.db
set link_library "*" $target_library
```

## ▶ The .lib file we are using:

[http://web.engr.oregonstate.edu/~traylor/ece474/saed90nm\\_typ\\_lt\\_pg.lib](http://web.engr.oregonstate.edu/~traylor/ece474/saed90nm_typ_lt_pg.lib)

## ▶ Cell delay matrix produced by SPICE,... very, very time intensive!

# Logic Synthesis - Available saed90nm Libraries

## Worst Case Libraries

Library Name	Temperature	Vdd	Process
saed90nm_min_hth_pg.lib(.db)	125deg C	Vdd = 1.08	P = 1.2
saed90nm_min_lth_pg.lib(.db)	-40deg C	Vdd = 1.08	P = 1.2
saed90nm_min_lt_pg.lib(.db)	-40deg C	Vdd = 0.70	P = 1.2
saed90nm_min_nth_pg.lib(.db)	25deg C	Vdd = 1.20	P = 1.2
saed90nm_min_nt_pg.lib(.db)	25deg C	Vdd = 0.70	P = 1.2

## Typical Case Libraries


Library Name	Temperature	Vdd	Process
saed90nm_typ_htl_pg.lib(.db)	125deg C	Vdd = 0.80	P = 1.0
saed90nm_typ_ltl_pg.lib(.db)	-40deg C	Vdd = 0.80	P = 1.0
saed90nm_typ_ht_pg.lib(.db)	125deg C	Vdd = 1.20	P = 1.0
saed90nm_typ_ntl_pg.lib(.db)	25deg C	Vdd = 0.80	P = 1.0
saed90nm_typ_lt_pg.lib(.db)	-40deg C	Vdd = 1.20	P = 1.0
saed90nm_max_pg.lib(.db)	-40deg C	Vdd = 1.30	P = 1.0
saed90nm_min_pg.lib(.db)	125deg C	Vdd = 0.70	P = 1.0
saed90nm_typ_pg.lib(.db)	25deg C	Vdd = 1.20	P = 1.0

## Best Case Libraries

Library Name	Temperature	Vdd	Process
saed90nm_max_htl_pg.lib(.db)	125deg C	Vdd = 0.90	P = 0.8
saed90nm_max_ltl_pg.lib(.db)	-40deg C	Vdd = 0.90	P = 0.8
saed90nm_max_ht_pg.lib(.db)	125deg C	Vdd = 1.32	P = 0.8
saed90nm_max_nt_pg.lib(.db)	25deg C	Vdd = 1.32	P = 0.8
saed90nm_max_ntl_pg.lib(.db)	25deg C	Vdd = 0.90	P = 0.8

# Logic Synthesis

- ▶ Synthesis optimization works primarily on combo logic
- ▶ Design is split into paths at FF or block i/o
- ▶ These paths are broken into:
  - ▶ Input to register
  - ▶ Register to register
  - ▶ Register to output



# Logic Synthesis - Register to Register Constraints

- ▶ Comprised of:
  - ▶ Clock period, clock uncertainty, FF setup time
- ▶ We define the clock period and clock uncertainty
- ▶ FF setup time will come from the library

# Logic Synthesis - Register to Register Constraints


- ▶ In a synchronous design, everything is relative to the clock

```
#define the clock period and clock port (20ns clock period)
create_clock -period 20 -name my_clock [get_ports clk]
```

```
#set the clock uncertainty to +/- 10pS
set_clock_uncertainty -setup 0.01 [get_clocks my_clock]
set_clock_uncertainty -hold 0.01 [get_clocks my_clock]
```

```
#set block internal clock network delay to 100pS
set_clock_latency 0.1 [get_clocks my_clock]
```

```
#global and distributed (external) clock buffer delays (0.5ns)
set_clock_latency -source 0.5 [get_clocks my_clock]
```



# Logic Synthesis - Register to Register Constraints

- ▶ The statements:

```
set_clock_uncertainty -setup 0.01 [get_clocks my_clock]
set_clock_uncertainty -hold 0.01 [get_clocks my_clock]
set_clock_latency      0.1 [get_clocks my_clock]
set_clock_latency -source 0.5 [get_clocks my_clock]
```


After clock tree routing will be replaced with

```
set_propagated_clock [get_clocks my_clock]
```


- ▶ After clock tree routing, the actual clock skew, routing and buffer delays will be known.

# Logic Synthesis - Register to register constraints

- ▶ Constraining clock constrains register to register delays (Q to D)




- ▶ Important relationships:
- ▶  $\text{combo\_delay} \leq (\text{clock\_cycle} - t_{su} - t_{ckq} - \text{clock\_skew})$
- ▶  $\text{min\_cycle\_time} = (t_{ckq} + t_{su} + \text{clock\_skew} + \text{combo\_delay})$



# Logic Synthesis - Input to Register Constraints

- ▶ Specify delay external to our block
- ▶ DC optimizes our input logic cloud in the remaining time

```
set_input_delay 5.2 -max -clock serial_clock \  
[remove_from_collection [all_inputs] [get_ports serial_clock]]  
set_driving_cell -lib_cell SDFFAR1 \  
[remove_from_collection [all_inputs] [get_ports clk_50]]
```





- ▶ An SDFFAR1 output asserts our input 5.2ns after clock edge

# Logic Synthesis - Register to output constraints

- ▶ We specify what how much time the downstream logic requires
- ▶ DC optimizes our output decode logic in the remaining time

```
set_output_delay -max 3.5 -clock serial_clock [all_outputs]  
set_load [expr 5 * [load_of saed90nm_typ/AND2X1/IN1]] [all_outputs]
```



Output At "B" must be valid  
At least 3.5 ns prior to  
clock edge.

- ▶ Downstream stage requires data valid 3.5ns before next clock edge
- ▶ Downstream load is equivalent to 5 AND2X1 loads

# Logic Synthesis - Global Constraints

- ▶ What constraints are missing?
- ▶ These are chip-wide, global constraints
- ▶ Temperature
  - ▶ 40 deg C, 25 deg C, 125 deg C
- ▶ Voltage
  - ▶ 1.32V, 1.2V, 0.7V
- ▶ Process
  - ▶ min, max, typ
- ▶ Wire load model
  - ▶ enclosed, top
  - ▶ die area estimate

# Logic Synthesis - Temp, Voltage, Process

- ▶ Cell libraries are characterized at multiple TVP corners
- ▶ CMOS fastest at: low temperature, high voltage, best process
- ▶ CMOS slowest at: high temperature, low voltage, worst process
- ▶ Actual delays/speeds vary greatly over PVT

```
library (saed90nm_max) {
technology ( cmos ) ;
delay_model      : table_lookup;
date : "2007 (INF CREATED ON 12-MAY-2008)" ;
time_unit : "1ns" ;
leakage_power_unit : "1pW" ;
voltage_unit : "1V" ;

power_supply() {
    power_rail(vdd, 1.32000000);
    power_rail(vddg, 1.32000000);
    default_power_rail : vdd ;
}

operating_conditions("BEST") {
process : 1.0;
temperature : -40;
voltage : 1.32;
power_rail(vdd, 1.32000000);
    power_rail(vddg, 1.32000000);
tree_type : best_case_tree;
}

/*****
** user supplied k_factors **
*****/
/*****
** PVT values used in k-factor calculations **
** Process   min,max :   0.800  1.200  **
** Voltage   min,max :   1.188  1.452  **
** Temperature min,max : -40.000 125.000  **
*****/
/*****
** user supplied nominals **
*****/
nom_voltage      : 1.320;
nom_temperature  : -40.000;
nom_process      : 1.000;
```

# Logic Synthesis - Temp, Voltage, Process

- ▶ Find setup time failures with worst corner - Why?
- ▶ Find hold time failures with best corner - Why?
- ▶ Setting TVP constraints:


```
set_operating_conditions -max "WORST"
```

```
set_operating_conditions -max "TYPICAL"
```

```
set_operating_conditions -max "BEST"
```


## Logic Synthesis - Wire delays

- ▶ Wire delay dominates in deep sub-micron ( $<0.35\mu\text{m}$ ) circuits
- ▶ Getting a good estimate of routing delay is vital for timing closure
- ▶ A *wireload model* relates fanout to RC parasitic prior to layout



## Logic Synthesis - Wire delays

- ▶ The model also specifies a per length resistance, capacitance and area and a statistical mapping from fanout to wire length
- ▶ Wire lengths are averages of previous designs of same size and fanout
- ▶ Using the wire length and R/C values, a delay can be calculated



# Logic Synthesis - Wire delays

- ▶ Wire load model from our saed90nm\_typ library

```
library (saed90nm_typ) {  
  
time_unit : "1ns" ;  
leakage_power_unit : "1pW" ;  
pulling_resistance_unit : "1kohm" ;  
capacitive_load_unit(1000.000,ff) ;  
  
wire_load("8000") {  
capacitance : 0.000312;  
resistance : 0.00157271;  
area : 0.01;  
slope : 90.646360 ;  
fanout_length( 1 , 13.940360);  
fanout_length( 2 , 31.804080);  
fanout_length( 3 , 51.612120);  
fanout_length( 4 , 73.611440);  
...  
...  
fanout_length( 17 , 671.375880);  
fanout_length( 18 , 749.983920);  
fanout_length( 19 , 834.487640);  
fanout_length( 20 , 925.134000);  
}
```

# Logic Synthesis - Computing wire delays

- ▶ Determine fanout on the net
- ▶ Look up length in the wire load model
- ▶ Calculate capacitance and resistance by multiplying length by per unit R and C in the wire load model
- ▶ Calculate delay from RC
- ▶ For example, if fanout = 4, in 8000 sq micron area:

Our scenario is: `fanout_length( 4 , 73.611440);`


`lumped C = (0.000312 * 73.611440)`

`lumped R = (0.00157271 * 73.611440)`

`net area = (0.01 * 73.611440)`

# Logic Synthesis - Computing wire delays


- ▶ RC delay is calculated depending on the interconnect model
- ▶ Best case tree, balanced tree, worst case tree
  - ▶ Best case tree: load is adjacent to the driver,  $R=0$
  - ▶ Balanced tree: each load shares  $R/n$  and  $C/n$  where  $n$ =fanout
  - ▶ Worst case tree: lumped load at end of line



Best Case Tree


$$R=0$$

only capacitive load  
no interconnect delay



Balanced Tree

each path gets  $C/n$ ,  $R/n$



Worst Case Tree

All loads at end


# Logic Synthesis - Wire load model

- ▶ Setting the wire model
- ▶ Wire load model names (e.g. "8000") are in .lib file

```
#Setting wire load model constraint  
set_wire_load_model -name 8000
```

# Logic Synthesis - Wire load mode


- ▶ The Wire load mode specifies the wire load model for nets that cross hierarchical boundaries
  - ▶ Top Model:



- ▶ Most pessimistic
- ▶ Uses WLM of the top level ignoring the WLMs of lower level blocks

## Logic Synthesis - Wire load mode

- ▶ Enclosed Model:




- ▶ Less pessimistic
- ▶ Uses WLM of the level that completely encloses the net

# Logic Synthesis - Wire load mode

## ▶ Segmented Model:

- ▶ Sum of the cell areas of the designs containing the net is used
- ▶ Nets crossing hierarchical boundaries are divided into segments
- ▶ Each net segment is estimated from the wire load model of the design containing the segment



# Logic Synthesis - Wire load mode



- ▶ Setting the wire mode

```
set_wire_load_mode top
```

# Logic Synthesis

- ▶ Hold time Violations
  - ▶ Running at speed is the greatest challenge
  - ▶ Hold time is usually dealt with later on, Why?
    - ▶ Layout introduces unexpected delay
    - ▶ Test structures add delay in some places...
    - ▶ .... and introduce hold time problems elsewhere
    - ▶ Fixing hold time problems too early often fixes non-problems
    - ▶ Fixing after layout you only fix real problems
    - ▶ Best strategy: Only fix big hold time problems up front
    - ▶ These will show up under best case TVP

# Logic Synthesis - Setup and Hold Review



At this edge, FF1 Acquires value 0. Value 0 must hold stable for  $t_h$  After the clock edge

At this edge, FF1 Acquires value 1. Value 1 must have been stable for at least  $t_{su}$  before the clock edge.


Also, FF0 launches value 1

Also, FF1 launches value 1

# Logic Synthesis - Constraining for Hold Time

- ▶ Constrain input hold time
- ▶ Supply the minimum delay external to our block


```
set_input_delay -min 0.3 -clock clk_50 \  
[remove_from_collection [all_inputs][get_ports clk_50]]
```



# Logic Synthesis - Constraining for Hold Time

- ▶ Constrain output hold time
- ▶ Supply the minimum delay external to our block
- ▶ Hint: Find hold time our block must supply and negate

```
set_output_delay -min [expr 0.3 - 0.5] -clock clk_50 [all_outputs]
# [expr external_logic_delay - FF_hold_time_reqmt] OR ....
set_output_delay -min -0.2 -clock clk_50 [all_outputs]
```



# Logic Synthesis - Checking Constraints

- ▶ Check to see if constraints were met

```
report_constraint:  
  [-all_violators] (show all constraint violators)  
  [-max_delay]     (show only setup and max_delay information)  
  [-min_delay]     (show only hold and min_delay information)
```

- ▶ DC can fix hold time problems after routing by:

```
compile -incr -only_hold_time
```