


## Looking Glass Quilts for a Web Page- Embedded 3D Display, Using both OpenGL and Blender



This work is licensed under a [Creative Commons  
Attribution-NonCommercial-NoDerivatives 4.0  
International License](#)



Oregon State  
University  
Mike Bailey  
mjb@cs.oregonstate.edu



Oregon State  
University  
Computer Graphics

LookingGlassQuilts.pptx

1

## Here is How to Generate a Quilt from OpenGL

Here are some pre-defined constants you will need:

```
const int QUILTWIDTH = 3360;
const int QUILTHEIGHT = 3360;
const int QUILTNUMWIDTH = 8;
const int QUILTNUMHEIGHT = 6;
const int QUILTTOTALBLOCKS = QUILTNUMWIDTH * QUILTNUMHEIGHT;
const int BLOCKWIDTH = QUILTWIDTH / QUILTNUMWIDTH; // 420
const int BLOCKHEIGHT = QUILTHEIGHT / QUILTNUMHEIGHT; // 560
const float QUILTZOF = 5.f;
const float QUILTDELTAEYE = 0.1f;
const float QUILT_ASPECT_Y_OVER_X = (float)BLOCKHEIGHT / (float)BLOCKWIDTH; // 4:3 = 1.3333
const char * QUILTFILENAME = "Quilt_qs8x6a0.75.bmp"; // must be in the format "*_qs8x6a0.75.*"
unsigned char QuiltArray[QUILTHEIGHT][QUILTWIDTH][3]; // holds the entire quilt
unsigned char BlockArray[BLOCKHEIGHT][BLOCKWIDTH][3]; // holds one block
```

2



mjb - September 18, 2023

## Triggering the File Output

3

```
void Keyboard( unsigned char c, int x, int y )
{
    switch( c )
    {
        case 'w':
        case 'W':
            CreateAndWriteQuilt(); // Hit the 'W' key to trigger the 48 renderings and file-writing
            break;

        . . .

        case 'q':
        case 'Q':
        case ESCAPE:
            DoMainMenu( QUIT ); // will not return here
            break; // happy compiler

        default:
            fprintf( stderr, "Don't know what to do with keyboard hit: '%c' (0x%0x)\n", c, c );
    }

    // force a call to Display():
    glutSetWindow( MainWindow );
    glutPostRedisplay();
}
```



Oregon State  
University  
Computer Graphics

mjb - September 18, 2023

## Generating the 48 Individual Images for the Quilt, I

4

```
void CreateAndWriteQuilt()
{
    glutSetWindow( MainWindow );

    float eyex = - QUILTDELTAEYE*(float)(QUILTTOTALBLOCKS)/2.f;
    for( int y = 0; y < QUILTNUMHEIGHT; y++ )
    {
        for( int x = 0; x < QUILTNUMWIDTH; x++ )
        {
            glDrawBuffer(GL_FRONT);
            glEnable(GL_DEPTH_TEST);
            glShadeModel(GL_FLAT);
            int vx = glutGet(GL_WINDOW_WIDTH);
            int vy = glutGet(GL_WINDOW_HEIGHT);
            int xl = (vx - BLOCKWIDTH) / 2;
            int yb = (vy - BLOCKHEIGHT) / 2;
            glViewport(xl, yb, BLOCKWIDTH, BLOCKHEIGHT);
            glClear(GL_COLOR_BUFFER_BIT | GL_DEPTH_BUFFER_BIT);

            glMatrixMode(GL_PROJECTION);
            glLoadIdentity();
            OffAxisIsPersp( 70.f, QUILT_ASPECT_Y_OVER_X, 0.1f, 1000.f, QUILTZOF, eyex );
            glMatrixMode(GL_MODELVIEW);
            glLoadIdentity();
            gluLookAt(0.f, 0.f, 8.f, 0.f, 0.f, 0.f, 1.f, 0.f);

            DisplayScene();

            glFlush();
            glFinish();
        }
    }
}
```



mjb - September 18, 2023

## Generating the 48 Individual Images for the Quilt, II

5

```
    . . .

    // done rendering -- upload the pixels:
    glReadBuffer(GL_FRONT);
    glPixelStorei(GL_PACK_ALIGNMENT, 1);
    glReadPixels(x1, yb, BLOCKWIDTH, BLOCKHEIGHT, GL_RGB, GL_UNSIGNED_BYTE, BlockArray);

    // location for this block in the large QuiltArray:
    for( int yb = 0; yb < BLOCKHEIGHT; yb++)
    {
        for( int xb = 0; xb < BLOCKWIDTH; xb++)
        {
            QuiltArray[y*BLOCKHEIGHT+yb][x*BLOCKWIDTH+xb][0] = BlockArray[yb][xb][0];
            QuiltArray[y*BLOCKHEIGHT+yb][x*BLOCKWIDTH+xb][1] = BlockArray[yb][xb][1];
            QuiltArray[y*BLOCKHEIGHT+yb][x*BLOCKWIDTH+xb][2] = BlockArray[yb][xb][2];
        }
    }

    Sleep(250);

    eyex += QUILTDELTAEYE;
} // x
} // y
WriteArray( QUILTFILENAME );
}
```



Oregon State  
University  
Computer Graphics

mjb - September 18, 2023

## DisplayScene( ) – just do the scene drawing, I

6

```
void
DisplayScene()
{
    // rotate the scene:
    glRotatef((GLfloat)Yrot, 0.f, 1.f, 0.f);
    glRotatef((GLfloat)Xrot, 1.f, 0.f, 0.f);

    // uniformly scale the scene:
    if (Scale < MINSCALE)
        Scale = MINSCALE;
    glScalef((GLfloat)Scale, (GLfloat)Scale, (GLfloat)Scale);

    // possibly draw the axes:
    if (AxesOn != 0)
    {
        glColor3fv(&Colors[WhichColor][0]);
        glCallList(AxesList);
    }

    // since we are using glScalef( ), be sure the normals get unitized:
    glEnable(GL_NORMALIZE);
    . .
}
```



Oregon State  
University  
Computer Graphics

mjb - September 18, 2023

## DisplayScene( ) – just do the scene drawing, II

7

```
    . . .

    glShadeModel(GL_FLAT);
    if (SmoothOn)
    {
        glShadeModel(GL_SMOOTH);
    }

    glDisable(GL_LIGHTING);
    glTexEnvf(GL_TEXTURE_ENV, GL_TEXTURE_ENV_MODE, GL_REPLACE);
    if (LightingOn)
    {
        glEnable(GL_LIGHTING);
        glEnable(GL_LIGHT0);
        glTexEnvf(GL_TEXTURE_ENV, GL_TEXTURE_ENV_MODE, GL_MODULATE);
    }

    glBindTexture(GL_TEXTURE_2D, Tex);
    glDisable(GL_TEXTURE_2D);
    if (TextureOn)
    {
        glEnable(GL_TEXTURE_2D);
    }

    . .
}
```



Oregon State  
University  
Computer Graphics

mjb - September 18, 2023

## DisplayScene( ) – just do the scene drawing, III

8

```
    . . .

    // draw the objects by calling up their display lists:
    glTranslatef(0.f, -2.25f, 0.);
    glColor3f(0.8f, 0.2f, 0.2f);
    SetMaterial(0.8f, 0.2f, 0.2f, 10.f);
    glCallList(SphereDL);

    glTranslatef(0.f, 1.75f, 0.);
    glColor3f(0.8f, 0.8f, 0.2f);
    SetMaterial(0.8f, 0.8f, 0.2f, 8.f);
    glCallList(ConeDL);

    glTranslatef(0.f, 2.5f, 0.);
    glColor3f(0.2f, 0.8f, 0.2f);
    SetMaterial(0.2f, 0.8f, 0.2f, 6.f);
    glCallList(TorusDL);

    glDisable(GL_LIGHTING);
    glDisable(GL_TEXTURE_2D);
    glShadeModel(GL_FLAT);
}
```



Oregon State  
University  
Computer Graphics

mjb - September 18, 2023

### Doing the Off-Axis Projection

9

```
void FrustumZ( float left, float right, float bottom, float top, float znear, float zfar, float zproj )
{
    if( zproj != 0.0 )
    {
        left *= ( znear/zproj );
        right *= ( znear/zproj );
        bottom *= ( znear/zproj );
        top *= ( znear/zproj );
    }

    glFrustum( left, right, bottom, top, znear, zfar );
}

void OffAxisPersp( float fovxdeg, float aspect_y_over_x, float znear, float zfar, float zOp, float eyex )
{
    float tanfovz = tanf( (float)(M_PI/180.) * fovxdeg / 2.f );

    float right = zOp * tanfovz;
    float left = -right;

    float bottom = aspect_y_over_x * left;
    float top = aspect_y_over_x * right;

    left -= eyex;
    right -= eyex;

    FrustumZ( left, right, bottom, top, znear, zfar, zOp );
    glTranslate( -eyex, 0.0, 0.0 );
}
```




Oregon State  
University  
Computer Graphics

mjb – September 18, 2023

### Quilt\_qs8x6a.075.bmp

10



mjb – September 18, 2023

### How the usual Display() function calls DisplayScene()

11

```
void Display()
{
    glutSetWindow( MainWindow );
    glDrawBuffer( GL_BACK );
    glClear( GL_COLOR_BUFFER_BIT | GL_DEPTH_BUFFER_BIT );
    glEnable( GL_DEPTH_TEST );
    glShadeModel( GL_FLAT );

    // set the viewport to a square centered in the window:
    GLsizei vx = glutGet( GLUT_WINDOW_WIDTH );
    GLsizei vy = glutGet( GLUT_WINDOW_HEIGHT );
    GLsizei v = vx < vy ? vx : vy; // minimum dimension
    GLint xl = ( vx - v ) / 2;
    GLint yb = ( vy - v ) / 2;
    glviewport( xl, yb, v, v );

    // set the viewing volume:
    glMatrixMode( GL_PROJECTION );
    glLoadIdentity();
    if( WhichProjection == ORTHO )
        glortho( -2.f, 2.f, -2.f, 2.f, 0.1f, 1000.f );
    else
        gluPerspective( 70.f, 1.f, 0.1f, 1000.f );

    // place the objects into the scene:
    glMatrixMode( GL_MODELVIEW );
    glLoadIdentity();
    gluLookAt( 0.f, 0.f, 7.f, 0.f, 0.f, 0.f, 0.f, 1.f, 0.f );

    // draw just the scene:
    DisplayScene( );

    glutSwapBuffers();
    glFlush();
}
```



Oregon State  
University  
Computer Graph


mjb – September 18, 2023

### Here is How to Generate a Quilt from Blender

12

You can also generate these quilts automatically from Blender.

The first thing you need to do is retrieve a Blender Add-on.  
The Add-on's name is **AliceLG.zip** and it can be found at <https://github.com/regcs/AliceLG/releases>







Click here and save this file anywhere.  
Do not un-zip it!



Oregon State  
University  
Computer Graphics

mjb – September 18, 2023



### Getting the AliceLG.zip Blender Add-on, V

17

When it's done, you will see this:

#### Preferences:

All required Python modules were installed.

**⚠ Please restart Blender to activate the changes!**



Oregon State  
University  
Computer Graphics

Now exit Blender and start it up again.


mjb – September 18, 2023

### Finding the Looking Glass Tab in Blender

18

Hit the '**n**' key and you will see the usual Transform panel, but something new has been added.

Click on the **Looking Glass** tab.




mjb – September 18, 2023


### Using the Looking Glass Tab, I

19

Click here and select Camera



This will bring up a viewing volume, like this:




mjb – September 18, 2023


### Using the Looking Glass Tab, II

20

Now adjust the **Clip Start** and **Clip End** to completely surround your scene.



Then adjust the **Focal Plane** to be roughly down the middle of the scene, like this:




Select **Portrait, 48 Views**

mjb – September 18, 2023


### Using the Looking Glass Tab, III

21




### Using the Looking Glass Tab, IV

22



### Monkey\_qs8x6a0.75.png

23



### How to Go From a Quilt to a Live “Hologram”, I

24

Navigate to <https://blocks.glass>

If you don't have an account, **sign up** to get one. If you are under 18 years old, be sure to have your parents help you do this!

If you do have an account, **Log in** to it.



**How to Go From a Quilt to a Live “Hologram”, II** 25

Click on the big Plus Sign

To download a Blender or OpenGL quilt, click here.

**Create a hologram**

- 3D Image**: Turn any regular image into a hologram using AI magic.
- Light field**: Capture a light-field accurate quilt from Unity, Blender, or Unreal.

Oregon State University Computer Graphics

**How to Go From a Quilt to a Live “Hologram”, III** 26

Drag-and-Drop your quilt file here, or click here and navigate

**Light field**

Upload a quilt that was exported from Unity, Unreal, or Blender. [Learn more](#)

Drag & drop to upload  
(png jpg jpeg webp bmp)

Or choose a file

< Back

Oregon State University Computer Graphics

**How to Go From a Quilt to a Live “Hologram”, IV** 27

Click on **Manage**, then click on the name of the file you just uploaded

Wiggle the mouse left and right to see your hologram move in 3D

Oregon State University Computer Graphics

**How to Go From a Quilt to a Live “Hologram”, V** 28

Click on **Manage** again then click here


Title	Type	Uploaded
Monkey	Light field	6 minutes ago

Oregon State University Computer Graphics

## How to Go From a Quilt to a Live “Hologram”, VI

29

That will bring up a bunch of things you can do with your new “hologram”



Clicking here will copy the embedded HTML code, to get at this hologram from the web, to the clipboard. Paste that into one of your HTML web pages!

Be sure this permission is set to **Unlisted**.



Oregon State  
University  
Computer Graphics

## “Casting” a Quilt to a 3D Image on a Looking Glass Portrait Display

30



<https://lookingglassfactory.com/looking-glass-portrait>



mjb – September 18, 2023