



1


The GLSL API



Oregon State University
Mike Bailey
mjb@cs.oregonstate.edu



This work is licensed under a [Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License](https://creativecommons.org/licenses/by-nc-nd/4.0/)





glsapi.pptx

mjb - November 22, 2022

2

The GLSL Shader-Creation Process





Oregon State University
Computer Graphics

mjb - November 22, 2022

3


Initializing the GL Extension Wrangler (GLEW)

```

#include "glew.h"
...
GLenum err = glewInit();
if( err != GLEW_OK )
{
    fprintf( stderr, "glewInit Error\n" );
    exit( 1 );
}
fprintf( stderr, "GLEW initialized OK\n" );
fprintf( stderr, "Status: Using GLEW %s\n", glewGetString(GLEW_VERSION) );
    
```

Do this *immediately* after opening the window

GLEW cannot be initialized until a graphics window is open. Like OpenGL itself, GLEW's calls will not work unless it can see a graphics context (i.e., a graphics state).



Oregon State University
Computer Graphics

<http://glew.sourceforge.net>

mjb - November 22, 2022

4

Reading a Shader source file into a character array

```

#include <stdio.h>


FILE *fp = fopen( filename, "r" );
if( fp == NULL ) { ... }

fseek( fp, 0, SEEK_END );
int numBytes = ftell( fp ); // length of file


GLchar * buffer = new GLchar [numBytes+1];

rewind( fp ); // same as: "fseek( in, 0, SEEK_SET )"

fread( buffer, 1, numBytes, fp );
fclose( fp );
buffer[numBytes] = '\0'; // the entire file is now in a byte string
    
```



Oregon State University
Computer Graphics



mjb - November 22, 2022

Creating and Compiling a Vertex Shader from that character buffer 5 (Geometry and Fragment files work the same way)

This is the only part of this process that is specific to the type of shader it is


```
int status;
int logLength;

GLuint vertShader = glCreateShader( GL_VERTEX_SHADER );

glShaderSource( vertShader, 1, (const GLchar **)&buffer, NULL );
delete [ ] buffer;
glCompileShader( vertShader );
CheckGLErrors( "Vertex Shader 1" );

glGetShaderiv( vertShader, GL_COMPILE_STATUS, &status );
if( status == GL_FALSE )
{
    fprintf( stderr, "Vertex shader compilation failed.\n" );
    glGetShaderiv( vertShader, GL_INFO_LOG_LENGTH, &logLength );
    GLchar *log = new GLchar [logLength];
    glGetShaderInfoLog( vertShader, logLength, NULL, log );
    fprintf( stderr, "%n%s\n", log );
    delete [ ] log;
    exit( 1 );
}
CheckGLErrors( "Vertex Shader 2" );
```

An array of strings



Creating Different Shader Types 6

```
GLuint shader = glCreateShader( GL_VERTEX_SHADER );
GLuint shader = glCreateShader( GL_GEOMETRY_SHADER );
GLuint shader = glCreateShader( GL_TESS_CONTROL_SHADER );
GLuint shader = glCreateShader( GL_TESS_EVALUATION_SHADER );
GLuint shader = glCreateShader( GL_FRAGMENT_SHADER );
GLuint shader = glCreateShader( GL_COMPUTE_SHADER );
```

Other than this, the rest of the create, compile, link process is the same for each shader type.

How does that array-of-strings thing work? 7

```
GLchar *ArrayOfStrings[3];
ArrayOfStrings[0] = "#define SMOOTH_SHADING";
ArrayOfStrings[1] = "... a commonly-used procedure ... ";
ArrayOfStrings[2] = "... the real vertex shader code ... ";
glShaderSource( vertShader, 3, ArrayOfStrings, NULL );
```

These are two ways to provide a *single* buffer:

```
GLchar *buffer[1];
buffer[0] = "... the entire shader code ... ";
glShaderSource( vertShader, 1, buffer, NULL );
```

```
GLchar *buffer = "... the entire shader code ... ";
glShaderSource( vertShader, 1, (const GLchar **)&buffer, NULL );
```

Why use an array of strings as the shader input, instead of just a single string? 8

1. You can use the same shader source and insert the appropriate "#defines" at the beginning
2. You can insert a common header file (≈ a .h file)
3. You can simulate a "#include" to re-use common pieces of code

if-tests vs. preprocessing

```
if( Mode == SmoothShading )
{ ... }
else if( Mode == PhongShading )
{ ... }
```


```
#ifdef SMOOTH_SHADING
{ ... }
#endif
```

```
#ifdef PHONG_SHADING
{ ... }
#endif
```

Creating the Program and Attaching the Shaders to It

9

```
GLuint program = glCreateProgram( );
glAttachShader( program, vertShader );
glAttachShader( program, fragShader );
glAttachShader( program, geomShader );
```



mjb - November 22, 2022

Linking the Program and Checking its Validity

10

```
glLinkProgram( program );
CheckGLErrors( "Shader Program 1" );
glGetProgramiv( program, GL_LINK_STATUS, &status );
if( status == GL_FALSE )
{
    fprintf( stderr, "Link failed.\n" );
    glGetProgramiv( program, GL_INFO_LOG_LENGTH, &logLength );
    log = new GLchar [logLength];
    glGetProgramInfoLog( program, logLength, NULL, log );
    fprintf( stderr, "\n%s\n", log );
    delete [] log;
    exit( 1 );
}
CheckGLErrors( "Shader Program 2" );

glValidateProgram( program );
glGetProgramiv( program, GL_VALIDATE_STATUS, &status );
fprintf( stderr, "Program is %s.\n", status == GL_FALSE ? "invalid" : "valid" );
```



mjb - November 22, 2022

Making the Program Active

11

```
glUseProgram( program );
```

Making the Program Inactive
(use the fixed function pipeline instead)

```
glUseProgram( 0 );
```



mjb - November 22, 2022

Using Multiple Shader Programs

12

```
glUseProgram( program0 );
<draw some stuff>

glUseProgram( program1 );
<draw some more stuff>

glUseProgram( program2 );
<draw some more stuff>

glUseProgram( program3 );
<draw some more stuff>

glUseProgram( program4 );
<draw some more stuff>

glUseProgram( program5 );
<draw some more stuff>
```

A specified shader program is an "attribute" – it stays in effect until you change it



mjb - November 22, 2022

Passing in Uniform Variables

13

You first need to find the variable's location in the shader program's symbol table.

```
float lightLoc[3] = { 0., 100., 0. };  
GLint location = glGetUniformLocation( program, "uLightLocation" );  
if( location < 0 )  
    fprintf( stderr, "Cannot find Uniform variable 'uLightLocation'\n" );  
else  
    glUniform3fv( location, 1, lightLoc );
```



Oregon State
University
Computer Graphics

Then you need to fill it.

mjb - November 22, 2022

Passing in Attribute Variables

14

You first need to find the variable's location in the shader program's symbol table.

```
GLint location = glGetAttribLocation( program, "aArray" );  
if( location < 0 )  
{  
    fprintf( stderr, "Cannot find Attribute variable 'aArray'\n" );  
}  
else  
{  
    glBegin( GL_TRIANGLES );  
        glVertexAttrib2f( location, a0, b0 );  
        glVertex3f( x0, y0, z0 );  
        glVertexAttrib2f( location, a1, b1 );  
        glVertex3f( x1, y1, z1 );  
        glVertexAttrib2f( location, a2, b2 );  
        glVertex3f( x2, y2, z2 );  
    glEnd();  
}
```



Oregon State
University
Computer Graphics

Then you need to fill it per-vertex.

mjb - November 22, 2022

Checking for Errors

15

```
void  
CheckGLErrors( const char* caller )  
{  
    unsigned int glerr = glGetError();  
    if( glerr == GL_NO_ERROR )  
        return;  
    fprintf( stderr, "GL Error discovered from caller '%s': ", caller );  
    switch( glerr )  
    {  
        case GL_INVALID_ENUM:  
            fprintf( stderr, "Invalid enum.\n" );  
            break;  
        case GL_INVALID_VALUE:  
            fprintf( stderr, "Invalid value.\n" );  
            break;  
        case GL_INVALID_OPERATION:  
            fprintf( stderr, "Invalid Operation.\n" );  
            break;  
        case GL_STACK_OVERFLOW:  
            fprintf( stderr, "Stack overflow.\n" );  
            break;  
        case GL_STACK_UNDERFLOW:  
            fprintf( stderr, "Stack underflow.\n" );  
            break;  
        case GL_OUT_OF_MEMORY:  
            fprintf( stderr, "Out of memory.\n" );  
            break;  
        default:  
            fprintf( stderr, "Unknown OpenGL error: %d (0x%x)\n", glerr, glerr );  
    }  
}
```



Oregon State
University
Computer Graphics

It's not a bad idea to do this in all your OpenGL programs, even without shaders!

mjb - November 22, 2022

Writing a C++ Class to Handle Everything is Fairly Straightforward

16

Setup in InitGraphics():

```
GLSLProgram *Hyper = new GLSLProgram( );  
bool valid = Hyper->Create( "hyper.vert", "hyper.geom", "hyper.frag" );  
if( ! valid ) { ... }
```

This loads, compiles, and links the shader. It prints error messages if something went wrong.

Using the GPU program in Display():

```
int Polar = ???;  
float K = ???;  
Hyper->Use( );  
Hyper->SetUniformVariable( "uPolar", Polar );  
Hyper->SetUniformVariable( "uK", K );  
glBegin( GL_TRIANGLES );  
    Hyper->SetAttributeVariable( "aTemperature", T0 );  
    glVertex3f( x0, y0, z0 );  
    Hyper->SetAttributeVariable( "aTemperature", T1 );  
    glVertex3f( x1, y1, z1 );  
    Hyper->SetAttributeVariable( "aTemperature", T2 );  
    glVertex3f( x2, y2, z2 );  
glEnd( );
```

Reverting to the fixed-function pipeline in Display():

```
Hyper->UnUse( ); // Hyper->Use( 0 ) also works
```

Co


mjb - November 22, 2022

SPIR-V

17

SPIR-V is a file format that can be used to hold shader code that has been pre-compiled, but has not yet been turned into machine code. It was created as a way for software developers to pre-compile their code and then allow the vendor-specific driver to produce the final binary representation. There are four major advantages in doing things this way:

1. A software developer can more easily wring compiler errors from the code by having an external compiler that can be run independently from the application.
2. Vendors can still apply their optimization-magic in their device-specific drivers.
3. SPIR-V files can be read at the start of a program and be turned into machine code faster than the original GLSL files could have been turned into machine code.
4. Software developers can distribute their code without having to reveal the shaders' source code.



mjb - November 22, 2022


Reading SPIR-V-compiled Shaders

18

The new `glShaderBinary()` call replaces both `glCreateShader()` and `glCompileShader()`

```
FILE *fp = fopen( filename, "r" );
if( fp == NULL ) { ... }
fseek( fp, 0, SEEK_END );
int numBytes = ftell( fp ); // length of file - guaranteed to be a multiple of 4
GLchar *buffer = new GLchar [numBytes];
rewind( fp ); // same as: "fseek( in, 0, SEEK_SET )"
fread( buffer, 1, numBytes, fp );
fclose( fp );
```

```
GLuint shaders[2];
glShaderBinary( 2, shaders, GL_SHADER_BINARY_FORMAT_SPIR_V, buffer, numbytes );
GLuint program = glCreateProgram();
glAttachShader( program, shaders[0] );
glAttachShader( program, shaders[1] );
```



mjb - November 22, 2022

SPIR-V: Standard Portable Intermediate Representation for Vulkan

19

`glslangValidator shaderFile -G [-H] [-I<dir>] [-S <stage>] -o shaderBinaryFile.spv`

Shaderfile extensions:

.vert	Vertex
.tesc	Tessellation Control
.tese	Tessellation Evaluation
.geom	Geometry
.frag	Fragment
.comp	Compute

(Can be overridden by the `-S` option)

<code>-V</code>	Compile for Vulkan
<code>-G</code>	Compile for OpenGL
<code>-I</code>	Directory(ies) to look in for #includes
<code>-S</code>	Specify stage rather than get it from shaderfile extension
<code>-c</code>	Print out the maximum sizes of various properties



Oregon State
University
Computer Graphics

Windows: `glslangValidator.exe`
Linux: `setenv LD_LIBRARY_PATH /usr/local/common/gcc-6.3.0/lib64/`

mjb - November 22, 2022

How do you know if SPIR-V compiled successfully?

20

Same as C/C++ -- the compiler gives you no nasty messages.

Also, if you care, legal .spv files have a magic number of **0x07230203**

So, if you do an `od -x` on the .spv file, the magic number looks like this:

0203 0723 . . .



Oregon State
University
Computer Graphics



mjb - November 22, 2022